

Printing date 05.12.2022 Revision: 26.05.2022

1 Identification

- · Product identifier
- · Trade name: COLORQUICK
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Treasure Island Industrial Corp. No.2, 3rd Ave. S. Osmena Blvd.

North Reclamation Area

Cebu City 6000

PHILIPPINES

doo@treasureisland.com.ph

- · Further information obtainable from: Product safety department
- Emergency telephone number: During normal opening times: +63 32 232 05 13

2 Hazard identification

· Classification of the substance or mixture



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

Muta. 1B H340 May cause genetic defects.
Carc. 1B H350 May cause cancer.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Acute Tox 5 H333 May be harmful if inhaled

Acute Tox. 5 H333 May be harmful if inhaled. Aquatic Acute 2 H401 Toxic to aquatic life. CWPALB-00109

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



T; Toxic

R45-46: May cause cancer. May cause heritable genetic damage.

(Contd. on page 2)



Printing date 05.12.2022 Revision: 26.05.2022

Trade name: COLORQUICK

(Contd. of page 1)



Xn; Harmful

R65: Harmful: may cause lung damage if swallowed.

×

Xi; Irritant

R36/38: Irritating to eyes and skin.



N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R10: Flammable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· Label elements

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:





T Toxic

N Dangerous for the environment

Hazard-determining components of labelling:

Kerosene

Naphtha (petroleum), hydrodesulfurized heavy

· Risk phrases:

- 45 May cause cancer.
- 46 May cause heritable genetic damage.
- 10 Flammable.
- 36/38 Irritating to eyes and skin.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.

· Safety phrases:

- Avoid exposure obtain special instructions before use.
- 1/2 Keep locked up and out of the reach of children.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

· Special labelling of certain preparations:

Contains Methyl Ethyl Ketone-Oxime. May produce an allergic reaction.

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 3)





Printing date 05.12.2022 Revision: 26.05.2022

Trade name: COLORQUICK

· **vPvB:** Not applicable.

(Contd. of page 2)

	terisation: Mixtures ture of substances listed below with nonhazardous additions.	
Dangerous comp	onents:	
CAS: 8008-20-6	Kerosene Xn R65 Xi R38 N R51/53 R10 Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H335-H336 Aquatic Acute 2, H401	
CAS: 64475-85-0	MINERAL SPIRITS Xi R36/38 R10 → Flam. Liq. 3, H226 → Skin Irrit. 2, H315; Eye Irritation 2A, H319	
CAS: 13463-67-7	titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 µm] © Carc. 2, H351 Acute Tox. 5, H333	
CAS: 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy ☐ T Carc. Cat. 2, Muta. Cat. 2 R45-46 ☐ Xn R48/20-65 ☐ Flam. Liq. 3, H226 ☐ Muta. 1B, H340; Carc. 1B, H350; STOT RE 1, H372; Asp. Tox. 1, H304 ☐ Aquatic Chronic 2, H411 ☐ STOT SE 3, H336	
CAS: 22464-99-9	Zirconium Octoate Xn R20/22 Xi R36/38 ◆ Flam. Liq. 3, H226 Acute Tox. 3, H301 ↑ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irritation 2A, H319	
CAS: 136-52-7	cobalt bis(2-ethylhexanoate) Xn R22 Acute Tox. 3, H301	
CAS: 96-29-7	Methyl Ethyl Ketone-Oxime ☐ T R48/25 ☐ Xi R43 R52/53 ☐ STOT RE 1, H372 ☐ Skin Sens. 1, H317	



Printing date 05.12.2022 Revision: 26.05.2022

Trade name: COLORQUICK

(Contd. of page 3)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

(Contd. on page 5)





Printing date 05.12.2022 Revision: 26.05.2022

Trade name: COLORQUICK

(Contd. of page 4)

Protect against electrostatic charges.

Keep respiratory protective device available.

- Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls / personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

com or pin in	control parameters	
· Ingredients w	· Ingredients with limit values that require monitoring at the workplace:	
CAS: 8008-2	0-6 Kerosene	
REL (USA)	Long-term value: 100 mg/m³ Kerosine only	
TLV (USA)	Long-term value: 200 mg/m³ as total hydrocarbon vapor; Skin; A3	
CAS: 136-52-	CAS: 136-52-7 cobalt bis(2-ethylhexanoate)	
TLV (USA)	Long-term value: 0.02* mg/m³ as Co, A3; *inhalable; DSEN; RSEN; BEI	
CAS: 96-29-7	CAS: 96-29-7 Methyl Ethyl Ketone-Oxime	
WEEL (USA)	Long-term value: 10 ppm DSEN	

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the

(Contd. on page 6)





Printing date 05.12.2022 Revision: 26.05.2022

Trade name: COLORQUICK

(Contd. of page 5)

resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Physical and chemical properties	
Information on basic physical and chen	nical properties
General Information	
Appearance:	
Form:	Fluid
Colour:	White
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: 36 °C
Flash point:	23 - 60 °C
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive a vapour mixtures are possible.
Explosion limits:	······································
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	1.04 g/cm^3
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 7)



Printing date 05.12.2022 Revision: 26.05.2022

Trade name: COLORQUICK

(Contd.	of page	6)

	(Conta. of page
· Solvent content:	
Organic solvents:	56.0 %
VOC (EC)	55.99 %
Solids content:	48.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity
- · LD/LC50 values relevant for classification:

CAS: 13463-67-7 titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \, \mu m$]

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (rat)

- Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation Irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Carcinogenic.

The product can cause inheritable damage.

12 Ecological information

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish

(Contd. on page 8)





Printing date 05.12.2022 Revision: 26.05.2022

Trade name: COLORQUICK

(Contd. of page 7)

- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- $\cdot \textit{Other adverse effects} \ \textit{No further relevant information available}.$

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
ADR, IMDG, IATA	UN1263
UN proper shipping name	
ADR	1263 PAINT, ENVIRONMENTALLY HAZARDOUS
IMDG	PAINT (KEROSENE, Naphtha (petroleum hydrodesulfurized heavy), MARINE POLLUTANT
IATA	PAINT
Transport hazard class(es)	
ADR, IMDG	
*	
Class	3 Flammable liquids.
Label	3
IATA	
3	
Class	3 Flammable liquids.
Label	3
Packing group	
ADR, IMDG, IATA	III





Printing date 05.12.2022 Revision: 26.05.2022

Trade name: COLORQUICK

	(Contd. of page
· Environmental hazards:	Product contains environmentally hazardou substances: Kerosene
· Marine pollutant:	Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	: 30
· EMS Number:	F-E, <u>S-E</u>
· Transport in bulk according to Annex II of M	Narpol (1997)
and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALL HAZARDOUS

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Philippines Inventory of Chemicals and Chemical Substances	
CAS: 8008-20-6	Kerosene
CAS: 63148-69-6	ALKYD RESIN
CAS: 64475-85-0	MINERAL SPIRITS
CAS: 13463-67-7	titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \ \mu m$]
CAS: 112926-00-8	Precipitated silica (Silica-Amorphous)
CAS: 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy
CAS: 21645-51-2	aluminium hydroxide
CAS: 22464-99-9	Zirconium Octoate
CAS: 68551-41-7	Fatty acids, C6-19-branched, calcium salts,overbased
CAS: 1318-93-0	Montmorillonite
CAS: 136-52-7	cobalt bis(2-ethylhexanoate)
CAS: 8050-26-8	Resin acids and rosin acids, esters with pentaerythritol
CAS: 112-80-1	oleic acid, pure
CAS: 111-76-2	Normal Butyl Cellusolve
CAS: 14808-60-7	Silicon Dioxide
	(Contd. on page 1)





Printing date 05.12.2022 Revision: 26.05.2022

Trade name: COLORQUICK

(Contd. of page 9)

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H227 Combustible liquid.
- H301 Toxic if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H333 May be harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H340 May cause genetic defects.
- H350 May cause cancer.
- H351 Suspected of causing cancer.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H401 Toxic to aquatic life.
- H402 Harmful to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- R10 Flammable.
- R20/22 Harmful by inhalation and if swallowed.
- R22 Harmful if swallowed.
- R36/38 Irritating to eyes and skin.
- R38 Irritating to skin.
- *R43* May cause sensitisation by skin contact.
- R45 May cause cancer.
- R46 May cause heritable genetic damage.
- R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- R48/25 Toxic: danger of serious damage to health by prolonged exposure if swallowed.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- · Department issuing SDS: Product safety department

(Contd. on page 11)





Printing date 05.12.2022 Revision: 26.05.2022

Trade name: COLORQUICK

(Contd. of page 10)

· Contact: Mr. Ong

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Flam. Liq. 4: Flammable liquids - Category 4

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 5: Acute toxicity - Category 5

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation - Category 1

Muta. 1B: Germ cell mutagenicity - Category 1B

Carc. 1B: Carcinogenicity - Category 1B

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.