



DECORATEX PAINT

DESCRIPTION:

DECORATEX is a water-based type coating designed to produce varied textured finishes. It exhibits high elasticity thereby making it flexible, resistant to flaking and cracking, with good adhesion and at same time provides excellent filling property to hide surface imperfections, hence, eliminates extra cost of patching-up rough surfaces.

USE:

Suited for interior walls and ceilings. It can be applied to almost all types of primed surfaces such as cement board, concrete, bricks, asbestos, wood, metal, and other building materials.


COLOR:

White

FINISH:

Low Profile #3100 & High Profile # 3101

APPLICATION:



Textured / Regular Roller

Decoratex is supplied as ready to use. Spread out paint at even thickness with a textured paint roller. Allow to set for about 5-10 minutes. Roll-on lightly the roller to the paint surface with a uniform pressure in one direction to achieve the desired texture. Use water for clean-up.

DRYING TIME:

Dry to recoat; allow overnight drying prior to topcoat application

COVERAGE:

Approximately 5-6 sq. m./gallon

SURFACE PREPARATION:

The primed surface must be clean, free of dirt or any adhesion barrier. Dry thoroughly prior to finish coat application.

RECOMMENDED PRIMER:

Prima Flat Finish (for concrete)
Island Wood Primer & Sealer (for wood)
Epoxy Primer (for metal)

PACKAGING:

4L plastic container

SHELF LIFE:

3 years in unopened container

STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



Treasure Island
INDUSTRIAL CORPORATION

ISO 9001 CERTIFIED

Head Office Address:
No. 2, 3rd Avenue,
S.Osmefia Blvd., North
Reclamation Area, Cebu City,
6000, Philippines
www.islandpaints.com

Email:
info@treasureisland.com.ph
Tel # Head Office :
232-0513 to 17
Fax:
(63-32) 232-0518

Information Office:
83-35 Plaridel St.,
Cebu City, 6000,
Philippines

Tel # for Info Office :
254-2226
412-4113
412-4082
Fax:
(63-32) 255-2656



LABEL ELEMENTS:



Warning. May be harmful if swallowed. May be harmful if inhaled. Harmful to aquatic life with long lasting effects.

Contains: N/A

Precaution: Handle and open container with care. Do not empty into drains, dispose of these materials and its container at hazardous or special waste collection point. This material and its container must be disposed of as hazardous waste.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



Treasure Island
INDUSTRIAL CORPORATION

ISO 9001 CERTIFIED

Head Office Address:
No. 2, 3rd Avenue,
S.Osmeña Blvd., North
Reclamation Area, Cebu City,
6000, Philippines
www.islandpaints.com

Email:
info@treasureisland.com.ph
Tel # Head Office :
232-0513 to 17
Fax:
(63-32) 232-0518

Information Office:
83-35 Plaridel St.,
Cebu City, 6000,
Philippines

Tel # for Info Office :
254-2226
412-4113
412-4082
Fax:
(63-32) 255-2656