



EPOXY MARINE NON-SAG PUTTY

DESCRIPTION:

EPOXY MARINE NON-SAG PUTTY is a two packed epoxy polyamide-based product, designed as gap/patching filler and as an all-purpose adhesive. When properly mixed together (Part A & B), exhibits lasting toughness and firm cohesive strength with different substrates and highly resistant to water and chemicals.

USE:

As gap filler specially for sloping, vertical and overhead surfaces of application such as divider wall or ceiling, made of wood, plywood, fiberboard, cement board and many other construction materials.

As patching filler for unsound masonry, patch and seal cracked concrete, concrete joint, etc.

Also use in marine application as an encapsulation coating for wooden or fiber-casted boat.

COLOR:

Epoxy Marine Non-sag Putty (Part A)- Neutral
Epoxy Marine Non-sag Putty (Part B)- Gray

APPLICATION TOOLS:



Putty knife



Plastic or Rubber Palette

MIXING RATIO:

Epoxy Marine Non-sag Putty (Part A)- 1 PART
Epoxy Marine Non-sag Putty Hardener (Part B)- 1 PART

SURFACE PREPARATION:

- Surface for repair must be dust and oil free.
- Restore any loss adherent portion adjacent to area to repair.

CURING TIME:

20-24 hours

POT LIFE @ 30°C:

1-2 hours

NOTE: Pot life may vary depending on weather condition.

APPLICATION:

- Mix Part A and B until uniform color is attained.
- Apply evenly on substrate using a putty knife, plastic, or rubber palette.

COVERAGE:

3-4 sq.m./ liter set @ 1 mm thickness

PACKAGING:

2 Liter Set : 1 liter Part A and 1 Liter Part B

2 Gallon Set: 3.8L Part A and 3.8L Part B

SHELF LIFE:

3 years in unopened container

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

LABEL ELEMENTS:

PART A



Warning. Flammable liquid and vapour. Toxic to aquatic life with long lasting effects. Causes skin and serious eye irritation. May cause an allergic skin reaction. May be harmful if inhaled.

Contains: Diglycidyl ether of bisphenol A

Precaution. Keep out of the reach of children. Avoid contact with skin and eyes. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label.

PART B



Warning. Flammable liquid and vapor. Causes skin and serious eye irritation. May be harmful if inhaled.

Contains: Polyamide Resin

Precaution. Keep out of the reach of children. Wear suitable protective clothing and gloves. If swallowed, seek medical advice immediately and show this container or label. Dispose of this material and its container at hazardous or special waste collection point.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.