



INDUSTRIAL CHLO RUB PRIMER

DESCRIPTION:

INDUSTRIAL CHLO RUB PRIMER is a chlorinated rubber protective base coat for all coating system where chlorinated rubber topcoat is specified.

COLOR:

White


FINISH:

Flat

APPLICATION:



Brush



Roller



Spray

Reduction: 0-5%,

0-5%,

5-10%

Reducer/Cleaner: Industrial Chlo Rub 7902

Reducer

THEORETICAL COVERAGE

33.6 sq. m. / 4L @ 40 microns dry film thickness

DRYING TIME:

Dry to recoat : 6 hours minimum

Flash Point : 28°C

SURFACE PREPARATION:

New Masonry:

*Light sanding to remove excess or loosely adherent cement mortar.

*Oil and grease should be removed by solvent cleaning.

*Joint cracks must be patch-even with Epoxy Putty.

Repair:

Existing paint should be dry and free from loosely adherent old coat. If old coat is unidentified, better overcoat a small patch area with the primer, then check compatibility.

For normally smooth masonry surface, 1 coat is sufficient; over semi-rough plastering, 2 coats may be required. Priming is permissible even at low ambient surface temperature with allowable relative humidity of 80% or below.

PACKAGING:

4L lithographed round can

SHELF LIFE:

1 year in unopened container

STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



Warning: Flammable liquid and vapour. May cause cancer. Route of exposure: Inhalation. Causes skin irritation. May be harmful if inhaled. Harmful to aquatic life with long lasting effects.

Contains: Alkanes, C10-13, Chloro

Precaution: Keep out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable protective clothing and gloves. If swallowed, seek medical advice immediately and show this container or label.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.