



INDUSTRIAL HI-HEAT 990 ALUMINUM

DESCRIPTION:

INDUSTRIAL HI-HEAT 990 ALUMINUM is an alkyd modified resin especially formulated to resist high temperature exposure up to 100°C.

USE:

As protective coating for hot steel surfaces.

COLOR:

Aluminum


FINISH:

Sheen

APPLICATION:



Brush



Roller



Spray

REDUCTION:

Mayon Paint Thinner
5% of reducer

DRYING TIME:

Dry to Recoat : Allow 24 hours

THEORETICAL COVERAGE:

Approximately 7.5 sq. m. / L @ 40 microns DFT

SURFACE PREPARATION:

Surface to be painted should be clean and dry, free from dust, dirt, and other foreign matters.

For best metal protection:

New Steel:

Sand blast to SA 2 ½ or power tool cleaning to St3 to remove scale and corrosion.

For Maintenance:

Spot repair – power tool corroded and damaged areas. Scrape loose paints, intact and sound portion be cleaned, free of salt deposits and other barriers. Let dry before coating.

PACKAGING:

4L lithographed round can

SHELF LIFE:

2 years in unopened container

STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



LABEL ELEMENTS:



Danger: Highly flammable liquid and vapour. In contact with water releases flammable gases. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enter airways. Toxic to aquatic life with long lasting effects. Causes skin irritation. May cause drowsiness or dizziness. May be harmful if inhaled.

Contains: Naphtha (Petroleum), hydrotreated light, Methylbenzene, Solvent Naphtha (petroleum), light arom., Petroleum Resin

Precaution: Avoid exposure – obtain special instructions before use. Keep locked up and out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable protective clothing, gloves, and eye/face protection. In case of fire, use sand, carbon dioxide, or powdered extinguishing agent. Never use water. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.