

Technical Data Sheet

INDUSTRIAL S/F RUB SPORT COURT COATING

DESCRIPTION:

INDUSTRIAL S/F RUB SPORT COURT COATING is a single-packed synthetic rubber solvent-based coating.

SPECIAL FEATURES:

- Fast dry
- Hardwearing
- Non slippery
- Excellent adhesion & impact resistance
- Easy to clean

USE:

Industrial Sport Court Coating is intended for indoor/outdoor concrete floor, basketball, lawn tennis, badminton, gymnasium and similar.

COLOR:

Green and other color available upon request.

FINISH:

Semi-Flat and Flat

APPLICATION:





Brush

Roller

REDUCTION:

Sport Court Reducer

10% max based on volume

DRYING TIME:

Dry hard: 4 hours

THEORETICAL COVERAGE:

25-30 sq. m. / gal @ 40µm DFT

SURFACE PREPARATION:

Adhesion barriers like dust, dirt, oil must be removed. Dry Surface thoroughly prior to painting.

For smooth surfaces, seal the surface using Epoxy FC 1805FC Sealer and let dry overnight. Sand with grit paper (#240 or #400) then apply Epoxy Primer and let dry overnight. Sand with grit paper (#400) then apply 2 coats of Industrial Sport Court Coating paint.

For dented surfaces, apply Epoxy Marine Putty after the sealer and let dry overnight. Sand with grit paper (#240) on applied Marine Putty and recoat with Epoxy FC 1805FC Sealer and let dry overnight. Sand with grit paper (#240 or #400) then apply Epoxy Primer and let dry overnight. Sand with grit paper (#400) then apply 2 coats of Industrial Sport Court Coating paint.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



No. 2, 3rd Avenue, S.Osmeña Blvd., North Reclamation Area, Cebu City, 6000, Philippines www.islandpaints.com info@treasureisland.com.ph Tel # Head Office : 232-0513 to 17 Fax: (63-32) 232-0518 Information Office: 83-35 Plaridel St., Cebu City, 6000, Philippines Tel # for Info Office : 254-2226 412-4113

412-4113 412-4082 Fax:

(63-32) 255-2656



Technical Data Sheet

PACKAGING:

4L and 16L lithographed can

SHELF LIFE:

1 year in unopened container

STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

LABEL ELEMENTS:



Danger: Flammable liquid and vapour. May cause genetic defects. May cause cancer. Toxic to aquatic life with long lasting effects. Harmful if inhaled. Causes skin irritation. May be harmful in contact with skin. Toxic to aquatic life.

Contains: Solvent Naphtha (PETROLEUM), Light Arom, Xylene

Precaution: Avoid exposure-obtain special instructions before use. Keep locked up and out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable gloves and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



(63-32) 232-0518