

ISLAND 002 LACQUER FLO

DESCRIPTION:

ISLAND 002 LACQUER FLO is a blend of special solvents with excellent flow characteristics and good solvency.

USE:

A lacquer additive that retards drying time in order to have good flow or leveling especially during humid condition.

NOTE: Adding excess flo could affect drying and hardness of film surface.

COLOR/ APPEARANCE:

Water-white Clear Liquid

RECOMMENDED MIXING RATIO:

One fourth liter of Island 002 Lacquer Flo to a gallon of ready to spray lacquer will give best result under most weather conditions.

PACKAGING:

4L rectangular can

STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

LABEL ELEMENTS:



Warning: Flammable liquid and vapour. May cause cancer. Harmful in contact with skin. Harmful if inhaled. Causes skin and serious eye irritation. May be harmful if swallowed.

Contains: Normal Butyl Cellusolve, Dimethylbenzene

Precaution: Keep out of the reach of children. Wear suitable protective clothing and gloves. If swallowed, seek medical advice immediately and show this container or label. Dispose of this material and its container to hazardous or special waste collection point.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.