

Printing date 19.12.2022 Revision: 19.12.2022

1 Identification

- · Product identifier
- · Trade name: ISLAND 003 LACQUER THINNER
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Treasure Island Industrial Corp. No.2. 3rd Ave. S. Osmena Blvd.

North Reclamation Area

Cebu City 6000

PHILIPPINES

doo@treasureisland.com.ph

- · Further information obtainable from: Product safety department
- · Emergency telephone number: During normal opening times: +63 32 232 05 13

2 Hazard identification

· Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Muta. 1B H340 May cause genetic defects.
Carc. 1B H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 1 H370 Causes damage to the central nervous system and the visual organs.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)



Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 003 LACQUER THINNER

(Contd. of page 1)

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

T; Toxic

R45-46-39/23/24/25: May cause cancer. May cause heritable genetic damage. Toxic: danger of very serious

irreversible effects through inhalation, in contact with skin and if swallowed.

×

Xn; Harmful

R20/21/22-48/20-63-65: Harmful by inhalation, in contact with skin and if swallowed. Harmful: danger of

serious damage to health by prolonged exposure through inhalation. Possible risk of

harm to the unborn child. Harmful: may cause lung damage if swallowed.

×

Xi: Irritant

R36/38: Irritating to eyes and skin.

F; Highly flammable

R11: Highly flammable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· Label elements

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:





T Toxic

F Highly flammable

· Hazard-determining components of labelling:

Methanol

Methylbenzene

Naphtha (petroleum), hydrotreated light

Risk phrases:

45 May cause cancer.

46 May cause heritable genetic damage.

11 Highly flammable.

20/21/22 Also harmful by inhalation, in contact with skin and if swallowed.

36/38 Irritating to eyes and skin.

39/23/24/25 Also toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if

swallowed.

48/20 Also harmful: danger of serious damage to health by prolonged exposure through inhalation.

63 Possible risk of harm to the unborn child.

65 Harmful: may cause lung damage if swallowed.

(Contd. on page 3)





Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 003 LACQUER THINNER

(Contd. of page 2)

- · Safety phrases:
- *Avoid exposure obtain special instructions before use.*
- 1/2 Keep locked up and out of the reach of children.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

| · Description: Mix · Dangerous comp | ture of substances listed below with nonhazardous additions. | |
|--|--|--|
| CAS: 108-88-3 | Methylbenzene Xn R48/20-63-65 Xi R38 F R11 R67 Repr. Cat. 3 Flam. Liq. 2, H225 Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336 Acute Tox. 5, H303 | |
| CAS: 64742-49-0 | Naphtha (petroleum), hydrotreated light ☐ T Carc. Cat. 2, Muta. Cat. 2 R45-46 ☐ Xn R65 ☐ Flam. Liq. 2, H225 ☐ Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304 ☐ Aquatic Chronic 2, H411 ☐ Skin Irrit. 2, H315; STOT SE 3, H336 Aquatic Acute 2, H401 | |

PH ·

(Contd. on page 4)



Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 003 LACQUER THINNER

| | | (Contd. of page 3 |
|---------------|--|-------------------|
| CAS: 67-56-1 | Methanol T R23/24/25-39/23/24/25 F R11 F Flam. Liq. 2, H225 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 STOT SE 1, H370 Specific concentration limits: STOT SE 1; H370: $C \ge 10 \%$ STOT SE 2; H371: $3 \% \le C < 10 \%$ | |
| CAS: 67-63-0 | Isopropyl Alcohol Xi R36 FR11 R67 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 Acute Tox. 5, H333 | |
| CAS: 111-76-2 | Normal Butyl Cellusolve Xn R20/21/22 Xi R36/38 ♦ Flam. Liq. 3, H226 Eye Dam. 1, H318 ↑ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 | |
| CAS: 78-93-3 | Methyl ethyl ketone Xi R36 FR11 R66-67 → Flam. Liq. 2, H225 → Eye Irrit. 2, H319; STOT SE 3, H336 Acute Tox. 5, H303; Acute Tox. 5, H313 | |
| CAS: 67-64-1 | propanone Xi R36 F R11 R66-67 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 | |
| CAS: 123-86-4 | Butyl Ethanoate Xn R22 Xi R36/38 F+R12 R67 Flam. Liq. 3, H226 Acute Tox. 3, H301 Skin Irrit. 2, H315; Eye Irritation 2A, H319; STOT SE 3, H336 mation: For the wording of the listed hazard phrases refer to section 16. | |



Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 003 LACQUER THINNER

(Contd. of page 4)

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Call for a doctor immediately.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

PH





Revision: 19.12.2022 Printing date 19.12.2022

Trade name: ISLAND 003 LACQUER THINNER

(Contd. of page 5)

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

CAS: 67-63-0 Isopropyl Alcohol

PEL (USA) Long-term value: 980 mg/m³, 400 ppm

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls / personal protection

| Ingredients | Ingredients with limit values that require monitoring at the workplace: | |
|-----------------------------|---|--|
| CAS: 108-88-3 Methylbenzene | | |
| PEL (USA) | Long-term value: 200 ppm Ceiling limit: 300; 500* ppm *10-min peak per 8-hr shift | |
| REL (USA) | Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm | |
| TLV (USA) | Long-term value: 20 ppm BEI, OTO, A4 | |
| CAS: 67-56 | 6-1 Methanol | |
| PEL (USA) | Long-term value: 260 mg/m³, 200 ppm | |
| REL (USA) | Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm Skin | |
| TLV (USA) | Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEI | |

(Contd. on page 7)



Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 003 LACQUER THINNER

| | | (Contd. of page |
|------------|--|-----------------|
| REL (USA) | Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm | (coma. or pay |
| TLV (USA) | Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4 | |
| CAS: 111-7 | 6-2 Normal Butyl Cellusolve | |
| PEL (USA) | Long-term value: 240 mg/m³, 50 ppm Skin | |
| REL (USA) | Long-term value: 24 mg/m³, 5 ppm Skin | |
| TLV (USA) | Long-term value: 20 ppm BEI, A3 | |
| CAS: 78-93 | -3 Methyl ethyl ketone | |
| PEL (USA) | Long-term value: 590 mg/m³, 200 ppm | |
| REL (USA) | Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm | |
| TLV (USA) | Short-term value: 300 ppm Long-term value: 200 ppm BEI | |
| CAS: 67-64 | -1 propanone | |
| PEL (USA) | Long-term value: 2400 mg/m³, 1000 ppm | |
| REL (USA) | Long-term value: 590 mg/m³, 250 ppm | |
| TLV (USA) | Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI | |
| CAS: 123-8 | 6-4 Butyl Ethanoate | |
| PEL (USA) | Long-term value: 710 mg/m³, 150 ppm | |
| REL (USA) | Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm | |
| TLV (USA) | Short-term value: 150 ppm Long-term value: 50 ppm | |
| | - ** | (Contd. on pag |

PH ·





Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 003 LACQUER THINNER

(Contd. of page 7)

· Ingredients with biological limit values:

CAS: 108-88-3 Methylbenzene

BEI (USA) 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

CAS: 67-56-1 Methanol

BEI (USA) 15 mg/L

Medium: urine Time: end of shift

Parameter: Methanol (background, nonspecific)

CAS: 67-63-0 Isopropyl Alcohol

BEI (USA) 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

CAS: 111-76-2 Normal Butyl Cellusolve

BEI (USA) 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

CAS: 78-93-3 Methyl ethyl ketone

BEI (USA) 2 mg/L

Medium: urine Time: end of shift

Parameter: Methyl ethyl ketone (nonspecific)

CAS: 67-64-1 propanone

BEI (USA) 25 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

(Contd. on page 9)





Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 003 LACQUER THINNER

(Contd. of page 8)

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** 64.7 °C

• Flash point: $< 0 \, ^{\circ}C$

· Flammability (solid, gas): Not applicable.

(Contd. on page 10)



Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 003 LACQUER THINNER

| | (Contd. of page |
|---|--|
| Ignition temperature: | 425 °C |
| Decomposition temperature: | Not determined. |
| Auto-ignition temperature: | Product is not selfigniting. |
| Explosive properties: | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| Explosion limits: | |
| Lower: | 1.1 Vol % |
| Upper: | 44 Vol % |
| Vapour pressure at 20 °C: | 128 hPa |
| Density at 20 °C: | 0.81 g/cm³ |
| Relative density | Not determined. |
| Vapour density | Not determined. |
| Evaporation rate | Not determined. |
| Solubility in / Miscibility with | |
| water: | Not miscible or difficult to mix. |
| Partition coefficient: n-octanol/water: | Not determined. |
| Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| Solvent content: | |
| Organic solvents: | 100.0 % |
| VÕC (EC) | 100.00 % |
| Solids content: | 0.0 % |
| Other information | No further relevant information available. |

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

PH



Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 003 LACQUER THINNER

(Contd. of page 10)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

| Acute wan | · Acute toxicity | | | |
|-------------|---|-----------------------|--|--|
| · LD/LC50 v | · LD/LC50 values relevant for classification: | | | |
| CAS: 108- | CAS: 108-88-3 Methylbenzene | | | |
| Oral | LD50 | 5,000 mg/kg (rat) | | |
| Dermal | LD50 | 12,124 mg/kg (rabbit) | | |
| Inhalative | LC50/4 h | 5,320 mg/l (mouse) | | |
| CAS: 67-5 | CAS: 67-56-1 Methanol | | | |
| Oral | LD50 | 5,628 mg/kg (rat) | | |
| Dermal | LD50 | 15,800 mg/kg (rabbit) | | |
| CAS: 67-6 | CAS: 67-63-0 Isopropyl Alcohol | | | |
| Oral | LD50 | 5,045 mg/kg (rat) | | |
| Dermal | LD50 | 12,800 mg/kg (rabbit) | | |
| Inhalative | LC50/4 h | 30 mg/l (rat) | | |
| CAS: 111- | CAS: 111-76-2 Normal Butyl Cellusolve | | | |
| Oral | LD50 | 1,200 mg/kg (ATE) | | |
| | | 1,480 mg/kg (rat) | | |
| Dermal | LD50 | 400 mg/kg (rab) | | |
| CAS: 78-9. | CAS: 78-93-3 Methyl ethyl ketone | | | |
| Oral | LD50 | 3,300 mg/kg (rat) | | |
| Dermal | LD50 | 5,000 mg/kg (rabbit) | | |
| CAS: 67-6 | CAS: 67-64-1 propanone | | | |
| Oral | LD50 | 5,800 mg/kg (rat) | | |
| Dermal | LD50 | 20,000 mg/kg (rabbit) | | |
| | | | | |

- · Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation Irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

Carcinogenic.

The product can cause inheritable damage.

12 Ecological information

- · Toxicit
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

(Contd. on page 12)



Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 003 LACQUER THINNER

(Contd. of page 11)

- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

| UN-Number ADR, IMDG, IATA | UN1263 | |
|--|-----------------------------|--|
| UN proper shipping name | | |
| ADR | 1263 PAINT RELATED MATERIAL | |
| IMDG, IATA | PAINT RELATED MATERIAL | |
| Transport hazard class(es) | | |
| ADR, IMDG, IATA | | |
| Class | 3 Flammahla liquids | |
| Lahel | 3 Flammable liquids. 3 | |
| | <i>J</i> | |
| Packing group | 11 | |
| ADR, IMDG, IATA | II | |
| Environmental hazards: | Not applicable. | |
| C | Warning: Flammable liquids. | |
| Special precautions for user | | |
| Special precautions for user Hazard identification number (Kemler code): | 33 | |



Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 003 LACQUER THINNER

| | (Contd. of pag |
|---|--|
| Transport in bulk according to Annex II of and the IBC Code | f Marpol Not applicable. |
| Transport/Additional information: | nor apprication. |
| Transport/Additional information. | |
| · ADR | |
| Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: E2 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 500 ml |
| Transport category | 2 |
| IMDG | |
| Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: E2 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 500 ml |
| UN "Model Regulation": | UN 1263 PAINT RELATED MATERIAL, 3, II |

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Philippines Inventory of Chemicals and Chemical Substances

All ingredients are listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

H3 STOT SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed. H302 Harmful if swallowed.

(Contd. on page 14)





Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 003 LACQUER THINNER

| | (Contd. of page 13) |
|-------------|--|
| H303 | May be harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H311 | Toxic in contact with skin. |
| H312 | Harmful in contact with skin. |
| H313 | May be harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H332 | Harmful if inhaled. |
| H333 | May be harmful if inhaled. |
| H336 | May cause drowsiness or dizziness. |
| H340 | May cause genetic defects. |
| H350 | May cause cancer. |
| H361 | Suspected of damaging fertility or the unborn child. |
| H370 | Causes damage to organs. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H401 | Toxic to aquatic life. |
| H411 | Toxic to aquatic life with long lasting effects. |
| | |
| R11 | Highly flammable. |
| R12 | Extremely flammable. |
| R20/21/22 | Harmful by inhalation, in contact with skin and if swallowed. |
| R22 | Harmful if swallowed. |
| R23/24/25 | Toxic by inhalation, in contact with skin and if swallowed. |
| R36 | Irritating to eyes. |
| R36/38 | Irritating to eyes and skin. |
| R38 | Irritating to skin. |
| R39/23/24/2 | 5 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if |
| D 45 | swallowed. |
| R45 | May cause cancer. |
| R46 | May cause heritable genetic damage. |
| R48/20 | Harmful: danger of serious damage to health by prolonged exposure through inhalation. |
| R63 | Possible risk of harm to the unborn child. |
| R65 | Harmful: may cause lung damage if swallowed. |
| R66 | Repeated exposure may cause skin dryness or cracking. |
| R67 | Vapours may cause drowsiness and dizziness. |

· Contact: Mr. Ong

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2

(Contd. on page 15)





Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 003 LACQUER THINNER

(Contd. of page 14)

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 5: Acute toxicity - Category 5 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Muta. 1B: Germ cell mutagenicity – Category 1B Carc. 1B: Carcinogenicity - Category 1B Repr. 2: Reproductive toxicity – Category 2 STOT SE 1: Specific target organ toxicity (single exposure) – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Čategory 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

^{*} Data compared to the previous version altered.