

Revision: 19.12.2022 Printing date 19.12.2022

1 Identification

- · Product identifier
- · Trade name: ISLAND 005 WATER WHITE CLEAR GLOSS LACQUER
- · Article number: CWCNCV-00013
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Treasure Island Industrial Corp. No.2, 3rd Ave. S. Osmena Blvd. North Reclamation Area Cebu City 6000 **PHILIPPINES**

doo@treasureisland.com.ph

- · Further information obtainable from: Product safety department
- Emergency telephone number: During normal opening times: +63 32 232 05 13

2 Hazard identification

· Classification of the substance or mixture



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Muta. 1B H340 May cause genetic defects. Carc. 1B H350 May cause cancer. Repr. 1B H360 May damage fertility or the unborn child. STOT SE 2 H371 May cause damage to the central nervous system and the visual organs. STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Acute Tox. 4 H302 Harmful if swallowed. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. Eye Irritation 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

Acute Tox. 5 H313 May be harmful in contact with skin.

Aquatic Acute 3 H402 Harmful to aquatic life.

(Contd. on page 2)



Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 005 WATER WHITE CLEAR GLOSS LACQUER

(Contd. of page 1)

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects. CWCNCV-00013

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

May impair fertility. May cause harm to the unborn child.



Xn; Harmful

R20/21/22-48/20-68/20/21/22-65: Harmful by inhalation, in contact with skin and if swallowed. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed. Harmful: may cause lung damage if

swallowed.



Xi; Irritant

R36/38: Irritating to eyes and skin.



'+; Extremely flammable

R12: Extremely flammable.



N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· Label elements

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:







- Toxic
- F+Extremely flammable
- Dangerous for the environment

· Hazard-determining components of labelling:

Methanol Methylbenzene di-(2-ethylhexyl) phthalate

· Risk phrases:

60 May impair fertility.

61 May cause harm to the unborn child.

(Contd. on page 3)



Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 005 WATER WHITE CLEAR GLOSS LACQUER

(Contd. of page 2)

Extremely flammable. 12

20/21/22 Also harmful by inhalation, in contact with skin and if swallowed.

36/38 Irritating to eyes and skin.

48/20 Also harmful: danger of serious damage to health by prolonged exposure through inhalation. 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

68/20/21/22 Also harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.

65 Harmful: may cause lung damage if swallowed.

· Safety phrases:

- Avoid exposure obtain special instructions before use.
- 1/2 Keep locked up and out of the reach of children.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
- In case of accident or if you feel unwell, seek medical advice immediately (show the label where 45 possible).
- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition / information on ingredients

- · Chemical characterisation: Mixtures

Dangerous comp	oonents:	
CAS: 108-88-3	Methylbenzene Xn R48/20-63-65 Xi R38 FR11 R67 Repr. Cat. 3 Flam. Liq. 2, H225 Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336 Acute Tox. 5, H303	
CAS: 64742-49-	Naphtha (petroleum), hydrotreated light ☐ T Carc. Cat. 2, Muta. Cat. 2 R45-46 ☐ Xn R65 ☐ Flam. Liq. 2, H225 ☐ Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304 ☐ Aquatic Chronic 2, H411 ☐ Skin Irrit. 2, H315; STOT SE 3, H336 Aquatic Acute 2, H401	

(Contd. on page 4)



Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 005 WATER WHITE CLEAR GLOSS LACQUER

C1C 0001 70 0	N. 11 1	(Contd. of page
CAS: 9004-70-0	Nitrocellulose FR11	
CAS: 108-10-1	Methyl Isobutyl Ketone Xn R20 Xi R36/37 F R11 R66 Flam. Liq. 2, H225 Carc. 2, H351 Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H336 Acute Tox. 5, H303	
CAS: 111-76-2	Normal Butyl Cellusolve Xn R20/21/22 Xi R36/38 Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 67-56-1	Methanol I R23/24/25-39/23/24/25 F R11 F Flam. Liq. 2, H225 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 STOT SE 1, H370 Specific concentration limits: STOT SE 1; H370: $C \ge 10 \%$ STOT SE 2; H371: $3 \% \le C < 10 \%$	
CAS: 123-86-4	Butyl Ethanoate Xn R22 Xi R36/38 F+ R12 R67 ♦ Flam. Liq. 3, H226 Acute Tox. 3, H301 Skin Irrit. 2, H315; Eye Irritation 2A, H319; STOT SE 3, H336	
CAS: 1330-20-7	Dimethylbenzene Xn R20/21 Xi R38 R10 ♦ Flam. Liq. 3, H226 ↑ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 Acute Tox. 5, H303	

PH ·



Revision: 19.12.2022 Printing date 19.12.2022

Trade name: ISLAND 005 WATER WHITE CLEAR GLOSS LACQUER

		(Contd. of pag
CAS: 141-78-6	ETHYL ACETATE Xi R36 F R11 R66-67	
CAS: 78-93-3	 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 Methyl ethyl ketone Xi R36 	
	F R11 R66-67	
G19 (5 (2)	Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 Acute Tox. 5, H303; Acute Tox. 5, H313	
CAS: 67-63-0	Isopropyl Alcohol	
	Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 Acute Tox. 5, H333	
CAS: 117-81-7	di-(2-ethylhexyl) phthalate ☑ T Repr. Cat. 2 R60-61 ❖ Repr. 1B, H360	
·SVHC		·

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours, therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · *After swallowing:* Call for a doctor immediately.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.



Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 005 WATER WHITE CLEAR GLOSS LACQUER

(Contd. of page 5)

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

(Contd. on page 7)





Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 005 WATER WHITE CLEAR GLOSS LACQUER

(Contd. of page 6)

· Specific end use(s) No further relevant information available.

Additional Control par	information about design of technical facilities: No further data; see item 7. rameters
	s with limit values that require monitoring at the workplace:
CAS: 108-8	88-3 Methylbenzene
PEL (USA)	Long-term value: 200 ppm Ceiling limit: 300; 500* ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm
TLV (USA)	Long-term value: 20 ppm BEI, OTO, A4
CAS: 108-1	10-1 Methyl Isobutyl Ketone
PEL (USA)	Long-term value: 410 mg/m³, 100 ppm
REL (USA)	Short-term value: 300 mg/m³, 75 ppm Long-term value: 205 mg/m³, 50 ppm
TLV (USA)	Short-term value: 75 ppm Long-term value: 20 ppm BEI, A3
CAS: 111-7	76-2 Normal Butyl Cellusolve
PEL (USA)	Long-term value: 240 mg/m³, 50 ppm Skin
REL (USA)	Long-term value: 24 mg/m³, 5 ppm Skin
TLV (USA)	Long-term value: 20 ppm BEI, A3
CAS: 67-56	6-1 Methanol
PEL (USA)	Long-term value: 260 mg/m³, 200 ppm
REL (USA)	Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm Skin
TLV (USA)	Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEI
CAS: 123-8	86-4 Butyl Ethanoate
PEL (USA)	Long-term value: 710 mg/m³, 150 ppm
REL (USA)	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm
TLV (USA)	Short-term value: 150 ppm
	Long-term value: 50 ppm



Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 005 WATER WHITE CLEAR GLOSS LACQUER

C (C 1220	40 M D)	(Contd. of pa
	-20-7 Dimethylbenzene	
, ,	Long-term value: 435 mg/m³, 100 ppm	
REL (USA)	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
TIVALICAN	Short-term value: (150) ppm	
ILV (USA)	Long-term value: (100) NIC-20 ppm BEI, A4	
CAS: 141-	78-6 ETHYL ACETATE	
PEL (USA)	Long-term value: 1400 mg/m³, 400 ppm	
REL (USA)	Long-term value: 1400 mg/m³, 400 ppm	
TLV (USA)	Long-term value: 400 ppm	
CAS: 78-9.	3-3 Methyl ethyl ketone	
PEL (USA)	Long-term value: 590 mg/m³, 200 ppm	
REL (USA)	Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm	
TLV (USA)	Short-term value: 300 ppm Long-term value: 200 ppm BEI	
CAS: 67-6.	3-0 Isopropyl Alcohol	
PEL (USA)	Long-term value: 980 mg/m³, 400 ppm	
REL (USA)	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm	
TLV (USA)	Short-term value: 400 ppm	
, ,	Long-term value: 200 ppm BEI, A4	
CAS: 117-	81-7 di-(2-ethylhexyl) phthalate	
PEL (USA)	Long-term value: 5 mg/m³	
REL (USA)	Short-term value: 10 mg/m³	
	Long-term value: 5 mg/m³ See Pocket Guide App. A	
TLV (USA)	Long-term value: (5) mg/m³, NIC-0.03 ppm NIC-Skin, A3	

PH -





Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 005 WATER WHITE CLEAR GLOSS LACQUER

(Contd. of page 8) · Ingredients with biological limit values: CAS: 108-88-3 Methylbenzene BEI (USA) 0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene 0.03 mg/LMedium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background) CAS: 108-10-1 Methyl Isobutyl Ketone BEI (USA) 1 mg/L Medium: urine Time: end of shift Parameter: MIBK CAS: 111-76-2 Normal Butyl Cellusolve BEI (USA) 200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis) CAS: 67-56-1 Methanol BEI (USA) 15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific) CAS: 1330-20-7 Dimethylbenzene BEI (USA) 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids CAS: 78-93-3 Methyl ethyl ketone BEI (USA) 2 mg/L Medium: urine Time: end of shift Parameter: Methyl ethyl ketone (nonspecific) CAS: 67-63-0 Isopropyl Alcohol BEI (USA) 40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)

(Contd. on page 10)



Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 005 WATER WHITE CLEAR GLOSS LACQUER

(Contd. of page 9)

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Colour: According to product specification

· Odour: Characteristic
· Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

(Contd. on page 11)



Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 005 WATER WHITE CLEAR GLOSS LACQUER

	(Contd. of page
Initial boiling point and boiling range	2: 64.7 °C
Flash point:	< 0 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	240 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	9 Vol %
Vapour pressure at 20 °C:	105 hPa
Density at 20 °C:	0.91 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	74.2 %
Water:	0.1 %
VOC (EC)	74.21 %
Solids content:	19.2 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.



Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 005 WATER WHITE CLEAR GLOSS LACQUER

(Contd. of page 11)

		cological effects	
Acute toxi	-		
		evant for classification:	
		hylbenzene	
Oral	LD50	5,000 mg/kg (rat)	
Dermal	LD50	12,124 mg/kg (rabbit)	
	l	5,320 mg/l (mouse)	
		iyl Isobutyl Ketone	
Oral	LD50	2,080 mg/kg (rat)	
Dermal	LD50	16,000 mg/kg (rab)	
Inhalative	LC50/4 h	11 mg/l (ATE)	
		8.3-16.6 mg/l (rat)	
CAS: 111-	76-2 Norn	nal Butyl Cellusolve	
Oral	LD50	1,200 mg/kg (ATE)	
		1,480 mg/kg (rat)	
Dermal	LD50	400 mg/kg (rab)	
CAS: 67-5	6-1 Metha	inol	
Oral	LD50	5,628 mg/kg (rat)	
Dermal	LD50	15,800 mg/kg (rabbit)	
CAS: 1330	0-20-7 Dim	nethylbenzene	
Oral	LD50	4,300 mg/kg (rat)	
Dermal	LD50	2,000 mg/kg (rabbit)	
CAS: 78-9	3-3 Methy	ol ethyl ketone	
Oral	LD50	3,300 mg/kg (rat)	
Dermal	LD50	5,000 mg/kg (rabbit)	
CAS: 67-6	3-0 Isopro	ppyl Alcohol	
Oral	LD50	5,045 mg/kg (rat)	
Dermal	LD50	12,800 mg/kg (rabbit)	
Inhalative	LC50/4 h	30 mg/l (rat)	
CAS: 117-	81-7 di-(2-	-ethylhexyl) phthalate	
Oral	LD50	30,600 mg/kg (rat)	

- Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation Irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

(Contd. on page 13)





Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 005 WATER WHITE CLEAR GLOSS LACQUER

(Contd. of page 12)

Irritant

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number · ADR, IMDG, IATA	UN1263
· UN proper shipping name · ADR · IMDG, IATA	1263 PAINT RELATED MATERIAL PAINT RELATED MATERIAL

(Contd. on page 14)



Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 005 WATER WHITE CLEAR GLOSS LACQUER

(Contd. of page 13)

· Transport	hazard	class((es))
-------------	--------	--------	------	---

· ADR, IMDG, IATA



· Class	3 Flammable liquids.
· Label	3
· Packing group	
· ADR, IMDG, IATA	II
Environmental hazards:	Product contains environmentally hazardous substances:
	heptane
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids.
· EMS Number:	F-E, <u>S-E</u>
· Transport in bulk according to Annex I and the IBC Code	I of Marpol Not applicable.
Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· IMDG	
· Limited quantities (LQ)	500 ml
· Excepted quantities (EQ)	Code: E3
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 300 ml
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Philippines Inventory of Chemicals and Chemical Substances

All ingredients are listed.

- · *Directive 2012/18/EU*
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 15)



Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 005 WATER WHITE CLEAR GLOSS LACQUER

(Contd. of page 14)

- · National regulations:
- · Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant ph	
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H333	May be harmful if inhaled.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H361	Suspected of damaging fertility or the unborn child.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
R10	Flammable.
R11	Highly flammable.
R12	Extremely flammable.
R20	Harmful by inhalation.
R20/21	Harmful by inhalation and in contact with skin.
R20/21/22	Harmful by inhalation, in contact with skin and if swallowed.
R22	Harmful if swallowed.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R36	Irritating to eyes.
R36/37	Irritating to eyes and respiratory system.
R36/38	Irritating to eyes and skin.
	(Contd. on page 16)





Printing date 19.12.2022 Revision: 19.12.2022

Trade name: ISLAND 005 WATER WHITE CLEAR GLOSS LACQUER

(Contd. of page 15)

R38 Irritating to skin.

R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if

swallowed.

May cause cancer. R45

R46 May cause heritable genetic damage.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R60 May impair fertility.

May cause harm to the unborn child. R61 R63 Possible risk of harm to the unborn child. R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

· Department issuing SDS: Product safety department

· Contact: Mr. Ong

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 5: Acute toxicity - Category 5

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Muta. 1B: Germ cell mutagenicity - Category 1B

Carc. 1B: Carcinogenicity - Category 1B

Carc. 2: Carcinogenicity - Category 2

Repr. 1B: Reproductive toxicity – Category 1B Repr. 2: Reproductive toxicity – Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT SE 2: Specific target organ toxicity (single exposure) – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.