

ISLAND 007 ACRYLIC FLO

DESCRIPTION:

ISLAND 007 ACRYLIC FLO is a blend of special solvents with excellent flow characteristics and good solvency.

USE:

An additive for automotive acrylic to retard drying time in order to have good flow or leveling specially during humid condition.

NOTE : Adding excess flo could affect drying and hardness of film surface.

APPEARANCE:

Water white clear liquid

RECOMMENDED MIXING RATIO:

One fourth liter of Island Acrylic Flo to a gallon of ready to spray acrylic will give best result under most weather condition.

PACKAGING:

1L & 4L tin can

SHELF LIFE:

2 years in unopened container

STORAGE AND DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

LABEL ELEMENTS:



Warning: Flammable liquid and vapor. May damage fertility or the unborn child. Harmful if inhaled. Causes skin irritation. May be harmful if swallowed or in contact with skin.

Contains: Cellusolve Acetate, Dimethylbenzene

Precaution: Avoid exposure – obtain special instructions before use. Keep locked up and out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable protective clothing, gloves, and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.