

Safety Data Sheet according to GHS

Printing date 19.12.2022

Revision: 19.12.2022

1 Identification

- **Product identifier**
- **Trade name:** ISLAND 202 ACRYLIC THINNER
- **Article number:** CWCSVB-00042
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Treasure Island Industrial Corp.
No.2, 3rd Ave. S. Osmena Blvd.
North Reclamation Area
Cebu City 6000
PHILIPPINES
doo@treasureisland.com.ph
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:** During normal opening times: +63 32 232 05 13

2 Hazard identification

- **Classification of the substance or mixture**


 Flam. Liq. 2 H225 Highly flammable liquid and vapour.




Muta. 1B	H340 May cause genetic defects.
Carc. 1B	H350 May cause cancer.
Repr. 1B	H360 May damage fertility or the unborn child.
STOT RE 2	H373 May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1	H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2	H315 Causes skin irritation.
Eye Irritation 2A	H319 Causes serious eye irritation.
Acute Tox. 5	H303 May be harmful if swallowed.
Acute Tox. 5	H333 May be harmful if inhaled.

CWCSVB-00042

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



R60-61: May impair fertility. May cause harm to the unborn child.

(Contd. on page 2)

Safety Data Sheet according to GHS

Printing date 19.12.2022

Revision: 19.12.2022

Trade name: ISLAND 202 ACRYLIC THINNER

(Contd. of page 1)

**Xn; Harmful**

R20-48/20-65: Harmful by inhalation. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Harmful: may cause lung damage if swallowed.

**Xi; Irritant**

R36/38: Irritating to eyes and skin.

**N; Dangerous for the environment**

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **Label elements**

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**

**T Toxic****N Dangerous for the environment**

· **Hazard-determining components of labelling:**

Methylbenzene

Cellusolve Acetate

· **Risk phrases:**

60 May impair fertility.

61 May cause harm to the unborn child.

20 Also harmful by inhalation.

36/38 Irritating to eyes and skin.

48/20 Also harmful: danger of serious damage to health by prolonged exposure through inhalation.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

· **Safety phrases:**

53 Avoid exposure - obtain special instructions before use.

1/2 Keep locked up and out of the reach of children.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Contd. on page 3)

PH

Safety Data Sheet

according to GHS

Printing date 19.12.2022




























Revision: 19.12.2022

Trade name: ISLAND 202 ACRYLIC THINNER
· **vPvB:** Not applicable.

(Contd. of page 2)

3 Composition / information on ingredients

· **Chemical characterisation: Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

CAS: 111-15-9	Cellusolve Acetate  T Repr. Cat. 2 R60-61  Xn R20/21/22 R10  Flam. Liq. 3, H226  Repr. 1B, H360  Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	
CAS: 108-10-1	Methyl Isobutyl Ketone  Xn R20  Xi R36/37  F R11 R66  Flam. Liq. 2, H225  Carc. 2, H351  Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H336 Acute Tox. 5, H303	
CAS: 67-64-1	propanone  Xi R36  F R11 R66-67  Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 108-88-3	Methylbenzene  Xn R48/20-63-65  Xi R38  F R11 R67 Repr. Cat. 3  Flam. Liq. 2, H225  Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336 Acute Tox. 5, H303	
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light  T Carc. Cat. 2, Muta. Cat. 2 R45-46  Xn R65  Flam. Liq. 2, H225  Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; STOT SE 3, H336 Aquatic Acute 2, H401	

(Contd. on page 4)

Safety Data Sheet according to GHS

Printing date 19.12.2022


Revision: 19.12.2022

Trade name: ISLAND 202 ACRYLIC THINNER

(Contd. of page 3)


CAS: 78-93-3


Methyl ethyl ketone

 Xi R36

 F R11

R66-67

 Flam. Liq. 2, H225

 Eye Irrit. 2, H319; STOT SE 3, H336

Acute Tox. 5, H303; Acute Tox. 5, H313

· SVHC

CAS: 111-15-9

Cellulosolve Acetate

 · **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

 · **Description of first aid measures**

 · **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

 · **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

 · **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

 · **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

 · **After swallowing:** If symptoms persist consult doctor.

 · **Information for doctor:**

 · **Most important symptoms and effects, both acute and delayed** No further relevant information available.

 · **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

 · **Extinguishing media**

 · **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

 · **Special hazards arising from the substance or mixture** No further relevant information available.

 · **Advice for firefighters**

 · **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

 · **Personal precautions, protective equipment and emergency procedures** Not required.

 · **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 5)

Safety Data Sheet according to GHS

Printing date 19.12.2022

Revision: 19.12.2022

Trade name: ISLAND 202 ACRYLIC THINNER

(Contd. of page 4)

- **Methods and material for containment and cleaning up:**
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to item 13.
 Ensure adequate ventilation.
- **Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
- **Information about fire - and explosion protection:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls / personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

 · **Ingredients with limit values that require monitoring at the workplace:**
CAS: 111-15-9 Cellulose Acetate

PEL (USA)	Long-term value: 540 mg/m ³ , 100 ppm Skin
REL (USA)	Long-term value: 2.7 mg/m ³ , 0.5 ppm Skin
TLV (USA)	Long-term value: 5 ppm Skin; BEI

CAS: 108-10-1 Methyl Isobutyl Ketone

PEL (USA)	Long-term value: 410 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm
TLV (USA)	Short-term value: 75 ppm Long-term value: 20 ppm BEI, A3

(Contd. on page 6)

Safety Data Sheet

according to GHS

Printing date 19.12.2022

Revision: 19.12.2022

Trade name: ISLAND 202 ACRYLIC THINNER

(Contd. of page 5)

CAS: 67-64-1 propanone

PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm
 REL (USA) Long-term value: 590 mg/m³, 250 ppm
 TLV (USA) Short-term value: 500 ppm
 Long-term value: 250 ppm
 A4, BEI

CAS: 108-88-3 Methylbenzene

PEL (USA) Long-term value: 200 ppm
 Ceiling limit: 300; 500* ppm
 *10-min peak per 8-hr shift
 REL (USA) Short-term value: 560 mg/m³, 150 ppm
 Long-term value: 375 mg/m³, 100 ppm
 TLV (USA) Long-term value: 20 ppm
 BEI, OTO, A4

CAS: 78-93-3 Methyl ethyl ketone

PEL (USA) Long-term value: 590 mg/m³, 200 ppm
 REL (USA) Short-term value: 885 mg/m³, 300 ppm
 Long-term value: 590 mg/m³, 200 ppm
 TLV (USA) Short-term value: 300 ppm
 Long-term value: 200 ppm
 BEI

Ingredients with biological limit values:
CAS: 111-15-9 Cellulose Acetate

BEI (USA) 100 mg/g creatinine
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: 2-Ethoxyacetic acid

CAS: 108-10-1 Methyl Isobutyl Ketone

BEI (USA) 1 mg/L
 Medium: urine
 Time: end of shift
 Parameter: MIBK

CAS: 67-64-1 propanone

BEI (USA) 25 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Acetone (nonspecific)

(Contd. on page 7)

Safety Data Sheet

according to GHS

Printing date 19.12.2022

Revision: 19.12.2022

Trade name: ISLAND 202 ACRYLIC THINNER

(Contd. of page 6)

CAS: 108-88-3 Methylbenzene

BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

CAS: 78-93-3 Methyl ethyl ketone

BEI (USA)	2 mg/L Medium: urine Time: end of shift Parameter: Methyl ethyl ketone (nonspecific)
------------------	---

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8)

Safety Data Sheet according to GHS

Printing date 19.12.2022

Revision: 19.12.2022

Trade name: ISLAND 202 ACRYLIC THINNER

(Contd. of page 7)

- **Eye protection:**
Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	55.8-56.6 °C

- **Flash point:** < 0 °C

- **Flammability (solid, gas):** Not applicable.

- **Ignition temperature:** 215 °C

- **Decomposition temperature:** Not determined.

- **Auto-ignition temperature:** Product is not selfigniting.

- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Explosion limits:**

Lower:	1.2 Vol %
Upper:	13 Vol %

- **Vapour pressure at 20 °C:** 233 hPa

- **Density at 20 °C:** 0.83 g/cm³
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.

- **Partition coefficient: n-octanol/water:** Not determined.

- **Viscosity:**
- **Dynamic:** Not determined.

(Contd. on page 9)

PH

Safety Data Sheet according to GHS

Printing date 19.12.2022

Revision: 19.12.2022

Trade name: ISLAND 202 ACRYLIC THINNER

(Contd. of page 8)

Kinematic:	Not determined.
Solvent content:	
Organic solvents:	100.0 %
VOC (EC)	100.00 %
Solids content:	0.0 %
Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

LD/LC50 values relevant for classification:		
CAS: 111-15-9 Cellulose Acetate		
Oral	LD50	≤3,900 mg/kg (rat)
Dermal	LD50	10,300 mg/kg (rabbit)
CAS: 108-10-1 Methyl Isobutyl Ketone		
Oral	LD50	2,080 mg/kg (rat)
Dermal	LD50	16,000 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (ATE) 8.3-16.6 mg/l (rat)
CAS: 67-64-1 propanone		
Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
CAS: 108-88-3 Methylbenzene		
Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)
CAS: 78-93-3 Methyl ethyl ketone		
Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)

(Contd. on page 10)

PH

Safety Data Sheet according to GHS

Printing date 19.12.2022

Revision: 19.12.2022

Trade name: ISLAND 202 ACRYLIC THINNER

(Contd. of page 9)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** Irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **ADR, IMDG, IATA** UNI263

(Contd. on page 11)

PH

Safety Data Sheet


according to GHS

Printing date 19.12.2022

Revision: 19.12.2022

Trade name: ISLAND 202 ACRYLIC THINNER

(Contd. of page 10)

<ul style="list-style-type: none"> · UN proper shipping name · ADR · IMDG, IATA 	1263 PAINT RELATED MATERIAL PAINT RELATED MATERIAL
<ul style="list-style-type: none"> · Transport hazard class(es) · ADR, IMDG, IATA 	
	
<ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids. 3
<ul style="list-style-type: none"> · Packing group · ADR, IMDG, IATA 	III
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	Product contains environmentally hazardous substances: heptane, cyclohexane Yes
<ul style="list-style-type: none"> · Special precautions for user · Hazard identification number (Kemler code): · EMS Number: 	Warning: Flammable liquids. 90 F-E, <u>S-E</u>
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of Marpol and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<ul style="list-style-type: none"> · UN "Model Regulation": 	UN 1263 PAINT RELATED MATERIAL, 3, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Philippines Inventory of Chemicals and Chemical Substances**

All ingredients are listed.

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **Seveso category P5c** FLAMMABLE LIQUIDS

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

(Contd. on page 12)

PH

Safety Data Sheet according to GHS

Printing date 19.12.2022

Revision: 19.12.2022

Trade name: ISLAND 202 ACRYLIC THINNER

(Contd. of page 11)

· **National regulations:**· **Other regulations, limitations and prohibitive regulations**· **Substances of very high concern (SVHC) according to REACH, Article 57**

CAS: 111-15-9 Cellusolve Acetate

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H303 May be harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H313 May be harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H340 May cause genetic defects.

H350 May cause cancer.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

R10 Flammable.

R11 Highly flammable.

R20 Harmful by inhalation.

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

R36 Irritating to eyes.

R36/37 Irritating to eyes and respiratory system.

R38 Irritating to skin.

R45 May cause cancer.

R46 May cause heritable genetic damage.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R60 May impair fertility.

R61 May cause harm to the unborn child.

R63 Possible risk of harm to the unborn child.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

(Contd. on page 13)

Safety Data Sheet according to GHS

Printing date 19.12.2022

Revision: 19.12.2022

Trade name: ISLAND 202 ACRYLIC THINNER

(Contd. of page 12)

- **Department issuing SDS:** Product safety department
- **Contact:** Mr. Ong
- **Abbreviations and acronyms:**
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
 - ICAO: International Civil Aviation Organisation
 - ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - SVHC: Substances of Very High Concern
 - vPvB: very Persistent and very Bioaccumulative
 - Flam. Liq. 2: Flammable liquids – Category 2
 - Flam. Liq. 3: Flammable liquids – Category 3
 - Acute Tox. 4: Acute toxicity – Category 4
 - Acute Tox. 5: Acute toxicity – Category 5
 - Skin Irrit. 2: Skin corrosion/irritation – Category 2
 - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 - Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
 - Muta. 1B: Germ cell mutagenicity – Category 1B
 - Carc. 1B: Carcinogenicity – Category 1B
 - Carc. 2: Carcinogenicity – Category 2
 - Repr. 1B: Reproductive toxicity – Category 1B
 - Repr. 2: Reproductive toxicity – Category 2
 - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 - STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 - Asp. Tox. 1: Aspiration hazard – Category 1
 - Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
 - Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- *** Data compared to the previous version altered.**

PH