

Technical Data Sheet



ISLAND 300PP PATCHING POWDER

DESCRIPTION:

ISLAND 300PP PATCHING POWDER is a high quality, finely ground pure white powder intended to be inter-mixed at jobsite with an appropriate primer base paint to prepare putty. It does not influence yellow patches when applied under a finish coating.

RECOMMENDED USE:

The putty is used to even-up surface imperfections by filling hairline cracks, dentations, joints, corners and edges on concrete and wood.

MIXING RATIO:

For Concrete Surfaces:

Latex Primer 301 White - 4 Liters
Island 300PP Patching Powder - 0.7 kg. approx.

For Wood Surfaces:

Island Wood Primer and Sealer 801 White - 4Liters Island 300PP Patching Powder - 0.6 kg. approx.

PACKAGING:

1 kg. / bag

SHELF LIFE:

5 year in unopened container

STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.