



ISLAND AUTOMOTIVE TINTING COLOR

DESCRIPTION:

ISLAND AUTOMOTIVE TINTING COLOR is a nitrocellulose-based lacquer finish developed for a fast dry and durable system adaptable where a quick job is required.

USE:

For metal office equipment, wood furnishing, appliances, lighting, and other decorative fixtures.

COLOR:

570 Phthalo Blue
551 Phthalo Green
512 Yellow Oxide
580 Black
High Performance Red

APPLICATION:



Spray

REDUCTION:

Mayon Lacquer Thinner

MIXING RATIO:

1:1 by volume, Automotive Lacquer to
Mayon Lacquer Thinner

DRYING TIME:

Dry to handle : 10 - 15 minutes
Dry hard : 1 – 2 hours
Dry to recoat : 2 hours

COVERAGE:

Approximately 7.5-9.0 sq. m. / L @ 25 microns DFT

RECOMMENDED PRIMER:

Island Automotive Lacquer Primer Surfacer

PACKAGING:

1L & 4L lithographed round can

SHELF LIFE:

5 years in unopened container

STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



LABEL ELEMENTS:



Danger: Highly flammable liquid and vapour. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Causes skin and serious eye irritation. May be harmful if swallowed. May be harmful in contact with skin. May be harmful if inhaled. Harmful to aquatic life with long-lasting effects.

Contains: Solvent Naphtha (Petroleum), light arom., Naphtha (Petroleum), hydrotreated light, Dimethylbenzene, Di-(2-ethylhexyl)phthalate

Precautions: Avoid exposure – obtain special instructions before use. Keep locked up and out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable protective clothing, gloves, and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.