

ISLAND FLEXIGEL

DESCRIPTION:

ISLAND FLEXIGEL is a self-priming, premium grade and flexible water-proof exterior coating based on aqueous rubber-like polymer.

USE:

Recommended to be used as water-proofing paint for concrete walls

FEATURES:

- Exceptional water resistance
- Unmatched flexibility
- Excellent bonding property
- Good outdoor durability
- Can seal hairline cracks and crevices of concrete surfaces


FINISH:

Low gloss

APPLICATION:



Brush



Roller



Spray

REDUCTION:

Product is supplied ready to use or may be reduced with $\frac{1}{4}$ - $\frac{1}{2}$ liter of clean water for every gallon of paint for good brushability and leveling.

MIXING RATIO:

For Spray: add about 1 liter clean water for every gallon of paint.

For tinting: use Island Latex Tinting Color (ILTC).

DRYING TIME:

Dry to hard : 2-4 hours

Dry to recoat: 4-6 hours

THEORETICAL COVERAGE:

Approximately 20-25 sq. m. / 4L / coat

SURFACE PREPARATION:

Cure concrete surface for 28 days. Remove excess mortar, dirt, and other foreign matter. Treat the concrete with Island 400CN Concrete Neutralizer following the label instruction. Allow surface to dry overnight or more time depending on weather condition or location.

PACKAGING:

4L and 16L plastic container

SHELF LIFE:

2 years in unopened container

STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



LABEL ELEMENTS:



Warning: May cause an allergic skin reaction. May be harmful if swallowed. May be harmful if inhaled. Toxic to aquatic life.

Contains: Reaction Mass of: 5-Chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Precaution: Keep out of the reach of children. Avoid contact with skin. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.

