



### ISLAND GLAZING PUTTY 803 WHITE

#### DESCRIPTION:

**ISLAND GLAZING PUTTY WHITE** is a premium quality patching material in heavy paste -form prepared from combination of finely ground pigments in a synthetic alkyd resin.

#### USE:

Suited to spot repair surface imperfections like joints, cracks, dents, or deep wood grains of properly primed wood surfaces.

#### COLOR:

White to Dirty White

#### FINISH:

Flat

#### APPLICATION:



#### Putty Knife

Apply by putty knife in thin coat at a time until surface imperfections are even-up.

#### REDUCTION:

No thinning necessary.  
As cleaner, use Island Paint Thinner.

#### DRYING TIME:

Dry to touch : 1/2 – 1 hour  
Dry to sand : 4 hours minimum

#### SUGGESTED COAT:

Flatwall Enamel 800FW  
Interior Semi-Gloss 800SG  
Exterior Paint 800  
Quick Dry Enamel 900  
Gloss Enamel 800GE

*Caution : Don't overcoat with Nitro Lacquer based paint.*

#### COVERAGE:

Depend on depth and condition of dents.

#### PACKAGING:

1L and 4L lithographed round can

#### SHELF LIFE:

1 year in unopened container

#### STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.





## LABEL ELEMENTS:



**Warning:** Flammable liquid and vapour. May cause genetic defects. May cause cancer. Causes skin irritation. May be harmful if inhaled. Harmful to aquatic life with long-lasting effects.

**Contains:** Naphtha (Petroleum), hydrodesulfurized heavy

**Precaution:** Avoid exposure – obtain special instructions before use. Keep locked up and out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.

