

Safety Data Sheet according to GHS

Printing date 20.12.2022

Revision: 22.08.2022

1 Identification

- **Product identifier**
- **Trade name:** ISLAND INTERIOR FLATWALL ENAMEL 800FW WHITE
- **Article number:** CWPALB-00398
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Treasure Island Industrial Corp.
No.2, 3rd Ave. S. Osmena Blvd.
North Reclamation Area
Cebu City 6000
PHILIPPINES
doo@treasureisland.com.ph
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:** During normal opening times: +63 32 232 05 13

2 Hazard identification

- **Classification of the substance or mixture**



Flam. Liq. 3 H226 Flammable liquid and vapour.


 Carc. 1B H350 May cause cancer. Route of exposure: Inhalation.
 Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.


Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.


 Skin Irrit. 2 H315 Causes skin irritation.
 STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
 Acute Tox. 5 H333 May be harmful if inhaled.
 Aquatic Acute 2 H401 Toxic to aquatic life.
 CWPALB-00398

(Contd. on page 2)

Safety Data Sheet according to GHS

Printing date 20.12.2022

Revision: 22.08.2022

Trade name: ISLAND INTERIOR FLATWALL ENAMEL 800FW WHITE

(Contd. of page 1)

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xn; Harmful

R65: Harmful: may cause lung damage if swallowed.



Xi; Irritant

R38: Irritating to skin.



N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R10: Flammable.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **Label elements**

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



Xn Harmful

N Dangerous for the environment

· **Hazard-determining components of labelling:**

Kerosene

· **Risk phrases:**

10 Flammable.

38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

· **Safety phrases:**

2 Keep out of the reach of children.

13 Keep away from food, drink and animal feedingstuffs.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

46 If swallowed, seek medical advice immediately and show this container or label.

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

PH

(Contd. on page 3)

Safety Data Sheet according to GHS

Printing date 20.12.2022

Revision: 22.08.2022
























Trade name: ISLAND INTERIOR FLATWALL ENAMEL 800FW WHITE

(Contd. of page 2)

3 Composition / information on ingredients

- **Chemical characterisation:** *Mixtures*
- **Description:** *Mixture of substances listed below with nonhazardous additions.*

- *Dangerous components:*

· Dangerous components:	
CAS: 8008-20-6	<p><i>Kerosene</i></p> <p> <i>Xn R65</i>  <i>Xi R38</i>  <i>N R51/53</i> <i>R10</i></p> <p> <i>Flam. Liq. 3, H226</i>  <i>Asp. Tox. 1, H304</i>  <i>Aquatic Chronic 2, H411</i>  <i>Skin Irrit. 2, H315; STOT SE 3, H335-H336</i> <i>Aquatic Acute 2, H401</i></p>
CAS: 1332-58-7	<i>Kaolin</i>
CAS: 13463-67-7	<p><i>titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]</i></p> <p> <i>Carc. 2, H351</i> <i>Acute Tox. 5, H333</i></p>
CAS: 471-34-1	<i>Calcium Carbonate</i>
CAS: 1317-65-3	<p><i>Calcium Carbonate</i></p> <p> <i>Acute Tox. 4, H302</i> <i>Acute Tox. 5, H333; Skin Corr. 3, H316; Eye Irritation 2B, H320</i></p>
CAS: 67-56-1	<p><i>Methanol</i></p> <p> <i>T R23/24/25-39/23/24/25</i>  <i>F R11</i></p> <p> <i>Flam. Liq. 2, H225</i>  <i>Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331</i>  <i>STOT SE 1, H370</i> <i>Specific concentration limits: STOT SE 1; H370: C ≥ 10 %</i> <i>STOT SE 2; H371: 3 % ≤ C < 10 %</i></p>
	<p><i>Zirconium Octoate</i></p> <p> <i>Xn R20/22</i>  <i>Xi R36/38</i></p> <p> <i>Flam. Liq. 3, H226</i>  <i>Acute Tox. 3, H301</i>  <i>Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irritation 2A, H319</i></p>
	<p><i>Methyl Ethyl Ketone-Oxime</i></p> <p> <i>Xn R20/22</i>  <i>Xi R36</i></p> <p> <i>Acute Tox. 3, H331</i>  <i>Acute Tox. 4, H302; Eye Irritation 2A, H319</i> <i>Flam. Liq. 4, H227</i></p>

- Additional information:** For the wording of the listed hazard phrases refer to section 16.

PH

(Contd. on page 4)

Safety Data Sheet according to GHS

Printing date 20.12.2022

Revision: 22.08.2022

Trade name: ISLAND INTERIOR FLATWALL ENAMEL 800FW WHITE

(Contd. of page 3)

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.

(Contd. on page 5)

PH

Safety Data Sheet

according to GHS

Printing date 20.12.2022

Revision: 22.08.2022

Trade name: ISLAND INTERIOR FLATWALL ENAMEL 800FW WHITE

(Contd. of page 4)

- **Information about fire - and explosion protection:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls / personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

 · **Ingredients with limit values that require monitoring at the workplace:**
CAS: 8008-20-6 Kerosene

REL (USA)	Long-term value: 100 mg/m ³ Kerosine only
TLV (USA)	Long-term value: 200 mg/m ³ as total hydrocarbon vapor; Skin; A3

CAS: 1332-58-7 Kaolin

PEL (USA)	Long-term value: 15 * 5 ^{***} mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10 * 5 ^{***} mg/m ³ *total dust **respirable fraction
TLV (USA)	Long-term value: 2 * mg/m ³ E; as respirable fraction, A4

CAS: 471-34-1 Calcium Carbonate

PEL (USA)	Long-term value: 15 * 5 ^{***} mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10 * 5 ^{***} mg/m ³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn

CAS: 67-56-1 Methanol

PEL (USA)	Long-term value: 260 mg/m ³ , 200 ppm
REL (USA)	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV (USA)	Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEI

(Contd. on page 6)

Safety Data Sheet according to GHS

Printing date 20.12.2022

Revision: 22.08.2022

Trade name: ISLAND INTERIOR FLATWALL ENAMEL 800FW WHITE

(Contd. of page 5)

· Ingredients with biological limit values:
CAS: 67-56-1 Methanol

BEI (USA)	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
-----------	---

· Additional information: The lists valid during the making were used as basis.

· Exposure controls
· Personal protective equipment:
· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:


Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties
· General Information
· Appearance:

Form:	Fluid
--------------	-------

(Contd. on page 7)

PH

Safety Data Sheet

according to GHS

Printing date 20.12.2022

Revision: 22.08.2022

Trade name: ISLAND INTERIOR FLATWALL ENAMEL 800FW WHITE

(Contd. of page 6)

Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	175-325 °C
· Flash point:	23 - 60 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	229 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	1.48 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	29.4 %
Water:	0.1 %
VOC (EC)	29.45 %
Solids content:	70.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

(Contd. on page 8)

PH

Safety Data Sheet according to GHS

Printing date 20.12.2022

Revision: 22.08.2022

Trade name: ISLAND INTERIOR FLATWALL ENAMEL 800FW WHITE

(Contd. of page 7)

- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

CAS: 13463-67-7 titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (rat)

CAS: 471-34-1 Calcium Carbonate

Oral	LD50	6,450 mg/kg (rat)
------	------	-------------------

CAS: 67-56-1 Methanol

Oral	LD50	5,628 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

(Contd. on page 9)

Safety Data Sheet according to GHS

Printing date 20.12.2022

Revision: 22.08.2022

Trade name: ISLAND INTERIOR FLATWALL ENAMEL 800FW WHITE




(Contd. of page 8)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	UN1263
· ADR, IMDG, IATA	
· UN proper shipping name	1263 PAINT, ENVIRONMENTALLY HAZARDOUS
· ADR	PAINT (KEROSENE), MARINE POLLUTANT
· IMDG	PAINT
· IATA	
· Transport hazard class(es)	
· ADR, IMDG	
 	
· Class	3 Flammable liquids.
· Label	3
· IATA	
	
· Class	3 Flammable liquids.
· Label	3
· Packing group	III
· ADR, IMDG, IATA	
· Environmental hazards:	Product contains environmentally hazardous substances: Kerosene
· Marine pollutant:	Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)

(Contd. on page 10)

PH

Safety Data Sheet according to GHS

Printing date 20.12.2022

Revision: 22.08.2022

Trade name: ISLAND INTERIOR FLATWALL ENAMEL 800FW WHITE

(Contd. of page 9)

· Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, S-E
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

*

15 Regulatory information

 · **Safety, health and environmental regulations/legislation specific for the substance or mixture**

 · **Philippines Inventory of Chemicals and Chemical Substances**

CAS: 14807-96-6	Hydrated Magnesium Silicate
CAS: 8008-20-6	Kerosene
CAS: 1332-58-7	Kaolin
CAS: 13463-67-7	titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]
CAS: 63148-69-6	ALKYD RESIN
CAS: 471-34-1	Calcium Carbonate
CAS: 1317-65-3	Calcium Carbonate
CAS: 1318-93-0	Montmorillonite
CAS: 67-56-1	Methanol
CAS: 8002-43-5	Lecithin
CAS: 112926-00-8	Precipitated silica (Silica-Amorphous)
CAS: 21645-51-2	aluminium hydroxide
	Zirconium Octoate
CAS: 7732-18-5	water, distilled, conductivity or of similar purity
CAS: 57-11-4	stearic acid, pure

(Contd. on page 11)

PH

Safety Data Sheet according to GHS

Printing date 20.12.2022

Revision: 22.08.2022

Trade name: ISLAND INTERIOR FLATWALL ENAMEL 800FW WHITE

(Contd. of page 10)

CAS: 121-44-8	Triethanolamine
CAS: 136-52-7	cobalt bis(2-ethylhexanoate)
CAS: 14808-60-7	Silicon Dioxide
CAS: 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy
CAS: 3586-55-8	(Ethylendioxy)dimethanol
CAS: 55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
CAS: 111-76-2	Normal Butyl Cellusolve

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
 E2 Hazardous to the Aquatic Environment
 P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- | | |
|-----------|---|
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H227 | Combustible liquid. |
| H301 | Toxic if swallowed. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H311 | Toxic in contact with skin. |
| H315 | Causes skin irritation. |
| H316 | Causes mild skin irritation. |
| H319 | Causes serious eye irritation. |
| H320 | Causes eye irritation. |
| H331 | Toxic if inhaled. |
| H332 | Harmful if inhaled. |
| H333 | May be harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H351 | Suspected of causing cancer. |
| H370 | Causes damage to organs. |
| H401 | Toxic to aquatic life. |
| H411 | Toxic to aquatic life with long lasting effects. |
| | |
| R10 | Flammable. |
| R11 | Highly flammable. |
| R20/22 | Harmful by inhalation and if swallowed. |
| R23/24/25 | Toxic by inhalation, in contact with skin and if swallowed. |

(Contd. on page 12)

Safety Data Sheet according to GHS

Printing date 20.12.2022

Revision: 22.08.2022

Trade name: ISLAND INTERIOR FLATWALL ENAMEL 800FW WHITE

(Contd. of page 11)

- R36 Irritating to eyes.
 R36/38 Irritating to eyes and skin.
 R38 Irritating to skin.
 R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
 R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 R65 Harmful: may cause lung damage if swallowed.

· **Department issuing SDS:** Product safety department

· **Contact:** Mr. Ong

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Liq. 4: Flammable liquids – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 5: Acute toxicity – Category 5

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Corr. 3: Skin corrosion/irritation – Category 3

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Eye Irritation 2B: Serious eye damage/eye irritation – Category 2B

Carc. 1B: Carcinogenicity – Category 1B

Carc. 2: Carcinogenicity – Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered.**

PH