

Technical Data Sheet

ISLAND INTERIOR FLATWALL ENAMEL 800FW WHITE

DESCRIPTION:

ISLAND INT FLATWALL ENAMEL WHITE is an alkyd-based finish with velvet flat texture intended for interior application on wall and ceiling.

USE:

Suited purposely for interior finishing coat on wall and ceiling materials like properly primed wood, plywood, particle boards, etc.

COLOR:

White, maybe tinted to pastel shades with Island Oil Tinting Color.

FINISH:

Flat

APPLICATION:







REDUCTION:

Island 006 Paint Thinner.

Brush, Roller: add about 5% reducer : approximately 15% reducer Two coats is normally required for optimum

performance result.

DRYING TIME:

Dry to recoat: 12 – 24 hours

COVERAGE:

Approximately 25 – 30 sq. m. / 4L

SURFACE PREPARATION:

Surface roughness must be sanded, dust off, clean free of dirt or any adhesion barrier.

RECOMMENDED PRIMER:

Island Wood Primer and Sealer 801 White

PACKAGING:

1L, 4L, and 16L lithographed round cans.

SHELF LIFE:

2 years in unopened container

STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



No. 2, 3rd Avenue, S.Osmeña Blvd., North Reclamation Area, Cebu City, 6000, Philippines www.islandpaints.com

(63-32) 255-2656



Technical Data Sheet

LABEL ELEMENTS:



Danger. Flammable liquid and vapour. May cause cancer. Route of exposure: Inhalation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. Causes skin irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May be harmful if inhaled.

Contains: Kerosene

Precaution: Keep out of the reach of children. Keep away from food, drink, and animal feeding stuffs. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. If swallowed, seek medical advice immediately and show this container or label.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



Head Office Address:

(63-32) 255-2656