

Printing date 16.10.2024 Revision: 16.10.2024

1 Identification

- · Product identifier
- · Trade name: ISLAND METAL PRIMER 730 RED
- · Article number: CWPALB-00018
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Treasure Island Industrial Corp. No.2, 3rd Ave. S. Osmena Blvd. North Reclamation Area Cebu City 6000

PHILIPPINES

doo@treasureisland.com.ph

- · Further information obtainable from: Product safety department
- Emergency telephone number: During normal opening times: +63 32 232 05 13

2 Hazard identification

· Classification of the substance or mixture



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

Muta. 1B H340 May cause genetic defects.
Carc. 1B H350 May cause cancer.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Acute Tox. 5 H333 May be harmful if inhaled. Aquatic Acute 2 H401 Toxic to aquatic life.

CWPALB-00018/7

(Contd. on page 2)



Printing date 16.10.2024 Revision: 16.10.2024

Trade name: ISLAND METAL PRIMER 730 RED

(Contd. of page 1)

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



T; Toxic

R45-46: May cause cancer. May cause heritable genetic damage.



Xn; Harmful

R65: Harmful: may cause lung damage if swallowed.



Xi; Irritant

R38: Irritating to skin.



N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R10: Flammable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· Label elements

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:





T Toxic

N Dangerous for the environment

· Hazard-determining components of labelling:

Kerosene

Naphtha (petroleum), hydrodesulfurized heavy

· Risk phrases:

- 45 May cause cancer.
- 46 May cause heritable genetic damage.
- 10 Flammable.
- 38 Irritating to skin.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.

· Safety phrases:

- 53 Avoid exposure obtain special instructions before use.
- 1/2 Keep locked up and out of the reach of children.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

(Contd. on page 3)





Printing date 16.10.2024 Revision: 16.10.2024

Trade name: ISLAND METAL PRIMER 730 RED

(Contd. of page 2)

- · Special labelling of certain preparations:
- Contains Resin acids and rosin acids, esters with pentaerythritol. May produce an allergic reaction.
- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

| - | ture of substances listed below with nonhazardous additions. | |
|-----------------|--|--|
| Dangerous comp | | |
| CAS: 8008-20-6 | | |
| | Xn R65 | |
| | Xi R38 | |
| | N R51/53 | |
| | ♠ Flam. Liq. 3, H226 | |
| | ♦ Asp. Tox. 1, H304 | |
| | Aquatic Chronic 2, H411 | |
| | Skin Irrit. 2, H315; STOT SE 3, H335-H336 | |
| | Aquatic Acute 2, H401 | |
| CAS: 471-34-1 | Calcium Carbonate | |
| CAS: 64475-85-0 | MINERAL SPIRITS | |
| | X Xi R36/38 | |
| | $\overline{RI0}$ | |
| | ♦ Flam. Liq. 3, H226 | |
| | Skin Irrit. 2, H315; Eye Irritation 2A, H319 | |
| | Pigment Corrosion Inhibitor | |
| | X Xi R36/38 | |
| | ♦ Skin Irrit. 2, H315; Eye Irritation 2A, H319 | |
| | Zirconium Octoate | |
| | X n R20/22 | |
| | X Xi R36/38 | |

PH

(Contd. on page 4)



Printing date 16.10.2024 Revision: 16.10.2024

Trade name: ISLAND METAL PRIMER 730 RED

| | | (Contd. of page 3 |
|-----------------|--|-------------------|
| CAS: 8050-26-8 | Resin acids and rosin acids, esters with pentaerythritol Xn R20/22 Xn R42 Resp. Sens. 1B, H334 Acute Tox. 5, H303; Acute Tox. 5, H333 | |
| CAS: 64742-82-1 | Naphtha (petroleum), hydrodesulfurized heavy ☐ T Carc. Cat. 2, Muta. Cat. 2 R45-46 ☐ Xn R48/20-65 ☐ Flam. Liq. 3, H226 ☐ Muta. 1B, H340; Carc. 1B, H350; STOT RE 1, H372; Asp. Tox. 1, H304 ☐ Aquatic Chronic 2, H411 ☐ STOT SE 3, H336 | |
| | Methyl Ethyl Ketone-Oxime Xn R20/22 Xi R36 Acute Tox. 3, H331 Acute Tox. 4, H302; Eye Irritation 2A, H319 Flam. Liq. 4, H227 | |
| CAS: 136-52-7 | cobalt bis(2-ethylhexanoate) | |

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

РΗ





Printing date 16.10.2024 Revision: 16.10.2024

Trade name: ISLAND METAL PRIMER 730 RED

(Contd. of page 4)

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls / personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

CAS: 8008-20-6 Kerosene

REL (USA) Long-term value: 100 mg/m³

Kerosine only

(Contd. on page 6)



Printing date 16.10.2024 Revision: 16.10.2024

Trade name: ISLAND METAL PRIMER 730 RED

| | (Contd. of page 5) | |
|---------------------------------|--|--|
| TLV (USA) | Long-term value: 200 mg/m³ | |
| | as total hydrocarbon vapor; Skin; A3 | |
| CAS: 471-34-1 Calcium Carbonate | | |
| PEL (USA) | Long-term value: 15* 5** mg/m³ | |
| | *total dust **respirable fraction | |
| REL (USA) | Long-term value: 10* 5** mg/m³ | |
| , , | *total dust **respirable fraction | |
| TLV (USA) | TLV withdrawn | |
| | CAS: 136-52-7 cobalt bis(2-ethylhexanoate) | |
| TLV (USA) | Long-term value: 0.02* mg/m³ as Co, A3; *inhalable; DSEN; RSEN; BEI | |
| | as Co, A3; *inhalable; DSEN; RSEN; BEI | |
| | us Co, A3, immutaote, DSEN, RSEN, BEI | |

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Reep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)






Printing date 16.10.2024 Revision: 16.10.2024

Trade name: ISLAND METAL PRIMER 730 RED

(Contd. of page 6)

· Eye protection:



9 Physical and chemical properties

Information on basic physical and chemical properties

General Information · Appearance: Form: Liquid Colour: Red Odour: Characteristic · Odour threshold: Not determined. · pH-value: Not determined. · Change in condition Undetermined. Melting point/freezing point: Initial boiling point and boiling range: 36 °C 23 - 60 °C · Flash point: Flammability (solid, gas): Not applicable. Not determined. · Decomposition temperature: Product is not selfigniting. · Auto-ignition temperature: Product is not explosive. However, formation of explosive air/vapour · Explosive properties: mixtures are possible. · Explosion limits: Lower: Not determined. Upper: Not determined. Not determined. · Vapour pressure: · Density at 20 °C: 1.25 g/cm³ · Relative density Not determined. · Vapour density Not determined. · Evaporation rate Not determined. · Solubility in / Miscibility with Not miscible or difficult to mix. water: · Partition coefficient: n-octanol/water: Not determined. · Viscosity: Not determined. Dynamic: Kinematic: Not determined. · Solvent content: Organic solvents: 38.4 %

(Contd. on page 8)



Printing date 16.10.2024 Revision: 16.10.2024

Trade name: ISLAND METAL PRIMER 730 RED

(Contd. of page 7)

| VOC (EC) | 38.44 % |
|---------------------|--|
| Solids content: | 62.1 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity
- · LD/LC50 values relevant for classification:

CAS: 471-34-1 Calcium Carbonate

Oral LD50 6,450 mg/kg (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Carcinogenic.

The product can cause inheritable damage.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish

(Contd. on page 9)



Printing date 16.10.2024 Revision: 16.10.2024

Trade name: ISLAND METAL PRIMER 730 RED

(Contd. of page 8)

- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

| UN-Number ADR, IMDG, IATA | UN1263 |
|------------------------------|---|
| UN proper shipping name | |
| ADR | 1263 PAINT RELATED MATERIAL, ENVIRONMENTA HAZARDOUS |
| IMDG | PAINT RELATED MATERIAL (KEROSENE, Naph (petroleum), hydrodesulfurized heavy), MAR POLLUTANT |
| IATA | PAINT RELATED MATERIAL |
| Transport hazard class(es) | |

3

Class

3 Flammable liquids.

Label

(Contd. on page 10)





Printing date 16.10.2024 Revision: 16.10.2024

Trade name: ISLAND METAL PRIMER 730 RED

(Contd. of page 9) $\cdot IATA$ · Class 3 Flammable liquids. · Label · Packing group · ADR, IMDG, IATA III· Environmental hazards: Product contains environmentally hazardous substances: Kerosene · Marine pollutant: Symbol (fish and tree) Symbol (fish and tree) · Special marking (ADR): Warning: Flammable liquids. · Special precautions for user · Hazard identification number (Kemler code): 30 F-E,S-E· EMS Number: · Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · Limited quantities (LQ) 5LCode: E1 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · Transport category \cdot *IMDG* · Limited quantities (LQ) 5L· Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · UN "Model Regulation": UN 1263 PAINT RELATED MATERIAL, 3, III, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

| · Philippines Inventory of Chemicals and Chemical Substances | |
|--|-----------------------------|
| CAS: 8008-20-6 | Kerosene |
| CAS: 63148-69-6 | ALKYD RESIN |
| CAS: 14807-96-6 | Hydrated Magnesium Silicate |
| CAS: 471-34-1 | Calcium Carbonate |
| | (Contd. on page 11) |



Printing date 16.10.2024 Revision: 16.10.2024

Trade name: ISLAND METAL PRIMER 730 RED

| | (Contd. of page 10) |
|-----------------|--|
| CAS: 64475-85-0 | MINERAL SPIRITS |
| | Iron Oxide Orange |
| | Zirconium Octoate |
| CAS: 8050-26-8 | Resin acids and rosin acids, esters with pentaerythritol |
| CAS: 64742-82-1 | Naphtha (petroleum), hydrodesulfurized heavy |
| CAS: 1318-93-0 | Montmorillonite |
| CAS: 68551-41-7 | Fatty acids, C6-19-branched, calcium salts, overbased |
| CAS: 136-52-7 | cobalt bis(2-ethylhexanoate) |
| CAS: 112-80-1 | oleic acid, pure |
| CAS: 111-76-2 | BUTYL CELLOSOLVE |
| CAS: 14808-60-7 | Silicon Dioxide |

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category
- E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H227 Combustible liquid.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H303 May be harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H333 May be harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H340 May cause genetic defects.
- H350 May cause cancer.

(Contd. on page 12)





Printing date 16.10.2024 Revision: 16.10.2024

Trade name: ISLAND METAL PRIMER 730 RED

(Contd. of page 11) Causes damage to organs through prolonged or repeated exposure. H401 Toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects. R10 Flammable. R20/22 Harmful by inhalation and if swallowed. R22 Harmful if swallowed. R36 Irritating to eyes. R36/38 Irritating to eyes and skin. Irritating to skin. R38 R42 May cause sensitisation by inhalation. R45 May cause cancer. R46 May cause heritable genetic damage. R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. · Department issuing SDS: Product safety department Contact: Mr. Ong · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Flam. Liq. 4: Flammable liquids - Category 4 Acute Tox. 3: Acute toxicity - Category 3 Acute Tox. 5: Acute toxicity - Category 5 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Resp. Sens. 1B: Respiratory sensitisation – Category 1B Muta. 1B: Germ cell mutagenicity – Category 1B Carc. 1B: Carcinogenicity - Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.