



## ISLAND METAL PRIMER 730 RED

### DESCRIPTION:

**ISLAND METAL PRIMER RED** is an alkyd-based rust inhibiting primer for steel and iron surfaces with superior penetrating and surface wetting properties. It contains red iron oxide rust inhibiting pigment that provides full protection from rust and corrosion.

### RECOMMENDED USE:

Conventional primer for exterior or interior iron or steel surfaces.

### COLOR:

Reddish Brown


### FINISH:

Flat

### APPLICATION:



Brush



Roller



Spray

### REDUCTION:

Mayon Paint Thinner / Island 006 Paint Thinner  
Applied by brush and roller-approx. 5% reducer  
Applied by spray- approx. 10% or more reducer  
may be required.

### DRYING TIME:

Dry to recoat; allow overnight

### COVERAGE:

20-25 sq. m. / gallon @ 70 microns DFT

### SURFACE PREPARATION:

Metal surfaces must be clean and dry, free from rust, dust, grease, and other contaminants. Rusty areas must be prepared to a bright and clean metal before priming. For repainting works, signs of rust films must be removed until it shows a bright metal surface. Spot prime finish as in new metal surfaces.

### SUBSEQUENT COAT:

Most oil/ alkyd intermediate or finish coats

### PACKAGING:

1/4L, 1L, and 4L lithographed round can

### SHELF LIFE:

5 years in unopened can

### STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



## LABEL ELEMENTS:



**Danger.** Flammable liquid and vapor. May cause genetic defects. May cause cancer. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. Causes skin and serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May be harmful if inhaled.

**Contains:** Kerosene and Naphtha (petroleum), hydrodesulfurized heavy

**Precaution:** Avoid exposure – obtain special instructions before use. Keep locked up and out of the reach of children. Do not empty into drains, dispose of these materials and its container at hazardous or special waste collection point. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.

