

Safety Data Sheet according to GHS

Printing date 20.12.2022

Revision: 27.05.2022

1 Identification

- **Product identifier**
- **Trade name: ISLAND OIL TINTING COLORS**
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Treasure Island Industrial Corp.
No.2, 3rd Ave. S. Osmena Blvd.
North Reclamation Area
Cebu City 6000
PHILIPPINES
doo@treasureisland.com.ph
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:** During normal opening times: +63 32 232 05 13

2 Hazard identification

- **Classification of the substance or mixture**



Flam. Liq. 3 H226 Flammable liquid and vapour.



| | |
|-------------|--|
| Muta. 1B | H340 May cause genetic defects. |
| Carc. 1B | H350 May cause cancer. |
| Repr. 1A | H360 May damage fertility or the unborn child. |
| STOT RE 1 | H372 Causes damage to the central nervous system through prolonged or repeated exposure. |
| Asp. Tox. 1 | H304 May be fatal if swallowed and enters airways. |




Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



| | |
|-----------------|---|
| Skin Irrit. 2 | H315 Causes skin irritation. |
| Skin Sens. 1 | H317 May cause an allergic skin reaction. |
| STOT SE 3 | H336 May cause drowsiness or dizziness. |
| Aquatic Acute 3 | H402 Harmful to aquatic life. |

 CWPALB-00384

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



R45-46: May cause cancer. May cause heritable genetic damage.

(Contd. on page 2)

Safety Data Sheet
according to GHS

Printing date 20.12.2022

Revision: 27.05.2022

Trade name: ISLAND OIL TINTING COLORS

(Contd. of page 1)

**Xn; Harmful**

R48/20-65: Harmful: danger of serious damage to health by prolonged exposure through inhalation.
Harmful: may cause lung damage if swallowed.

**Xi; Irritant**

R38: Irritating to skin.

R10-52/53: Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

Label elements**Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:**T Toxic****Hazard-determining components of labelling:**

Kerosene

Naphtha (petroleum), hydrodesulfurized heavy

Risk phrases:

45 May cause cancer.

46 May cause heritable genetic damage.

10 Flammable.

38 Irritating to skin.

48/20 Also harmful: danger of serious damage to health by prolonged exposure through inhalation.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

Safety phrases:

53 Avoid exposure - obtain special instructions before use.

1/2 Keep locked up and out of the reach of children.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Special labelling of certain preparations:

Contains Methyl Ethyl Ketone-Oxime. May produce an allergic reaction.

Other hazards**Results of PBT and vPvB assessment****PBT: Not applicable.**

(Contd. on page 3)

PH

Safety Data Sheet

according to GHS

Printing date 20.12.2022

Revision: 27.05.2022
























Trade name: ISLAND OIL TINTING COLORS

 · **vPvB:** Not applicable.

(Contd. of page 2)

3 Composition / information on ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.
- **Dangerous components:**

| | | |
|-----------------|---|--|
| CAS: 8008-20-6 | Kerosene  Xn R65  Xi R38  N R51/53 R10  Flam. Liq. 3, H226  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; STOT SE 3, H335-H336 Aquatic Acute 2, H401 | |
| CAS: 64742-82-1 | Naphtha (petroleum), hydrodesulfurized heavy  T Carc. Cat. 2, Muta. Cat. 2 R45-46  Xn R48/20-65  Flam. Liq. 3, H226  Muta. 1B, H340; Carc. 1B, H350; STOT RE 1, H372; Asp. Tox. 1, H304  Aquatic Chronic 2, H411  STOT SE 3, H336 | |
| CAS: 67700-76-9 | alkyd resin  Xi R38  Skin Irrit. 2, H315 | |
| CAS: 471-34-1 | Calcium Carbonate | |
| | Carbon black  Expl. 1.4, H204  Flam. Liq. 3, H226; Self-react. C, H242  Muta. 1B, H340; Carc. 1B, H350; Repr. 1A, H360  Skin Irrit. 2, H315; Skin Sens. 1B, H317 Acute Tox. 5, H313; Aquatic Acute 3, H402; Aquatic Chronic 4, H413 | |
| CAS: 96-29-7 | Methyl Ethyl Ketone-Oxime  T R48/25  Xi R43 R52/53  STOT RE 1, H372  Skin Sens. 1, H317 Flam. Liq. 4, H227; Aquatic Acute 3, H402; Aquatic Chronic 3, H412 | |

 · **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- **Description of first aid measures**
- **General information:**
 Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)

Safety Data Sheet according to GHS

Printing date 20.12.2022

Revision: 27.05.2022

Trade name: ISLAND OIL TINTING COLORS

(Contd. of page 3)

- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

(Contd. on page 5)

Safety Data Sheet according to GHS

Printing date 20.12.2022

Revision: 27.05.2022

Trade name: ISLAND OIL TINTING COLORS

(Contd. of page 4)

 · **Specific end use(s)** No further relevant information available.

8 Exposure controls / personal protection

 · **Additional information about design of technical facilities:** No further data; see item 7.

 · **Control parameters**

 · **Ingredients with limit values that require monitoring at the workplace:**
CAS: 8008-20-6 Kerosene

| | |
|-----------|--|
| REL (USA) | Long-term value: 100 mg/m ³ Kerosine only |
| TLV (USA) | Long-term value: 200 mg/m ³ as total hydrocarbon vapor; Skin; A3 |

CAS: 471-34-1 Calcium Carbonate

| | |
|-----------|---|
| PEL (USA) | Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction |
| REL (USA) | Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction |
| TLV (USA) | TLV withdrawn |

Carbon black

| | |
|-----------|--|
| PEL (USA) | Long-term value: 3.5 mg/m ³ |
| REL (USA) | Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C |
| TLV (USA) | Long-term value: 3* mg/m ³ *inhalable fraction, A3 |

CAS: 96-29-7 Methyl Ethyl Ketone-Oxime

| | |
|------------|---------------------------------|
| WEEL (USA) | Long-term value: 10 ppm DSEN |
|------------|---------------------------------|

 · **Additional information:** The lists valid during the making were used as basis.

 · **Exposure controls**

 · **Personal protective equipment:**

 · **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.

 · **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

 · **Protection of hands:**


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

PH

Safety Data Sheet according to GHS

Printing date 20.12.2022

Revision: 27.05.2022

Trade name: ISLAND OIL TINTING COLORS

(Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Fluid

Colour:

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

Melting point/freezing point:

Undetermined.

Initial boiling point and boiling range: 150-200 °C

· **Flash point:**

23 - 60 °C

· **Flammability (solid, gas):**

Not applicable.

· **Decomposition temperature:**

Not determined.

· **Auto-ignition temperature:**

Product is not selfigniting.

· **Explosive properties:**

Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.

· **Explosion limits:**

Lower:

Not determined.

Upper:

Not determined.

· **Vapour pressure:**

Not determined.

· **Density at 20 °C:**

1.14 g/cm³

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **Evaporation rate**

Not determined.

(Contd. on page 7)

PH

Safety Data Sheet according to GHS

Printing date 20.12.2022

Revision: 27.05.2022

Trade name: ISLAND OIL TINTING COLORS

(Contd. of page 6)

| | |
|--|--|
| · Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| · Partition coefficient: n-octanol/water: | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 32.1 % |
| VOC (EC) | 32.08 % |
| Solids content: | 67.5 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· **LD/LC50 values relevant for classification:**

CAS: 471-34-1 Calcium Carbonate

Oral LD50 6,450 mg/kg (rat)

Carbon black

Oral LD50 10,000 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **Additional toxicological information:**
 The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
 Irritant
 Carcinogenic.
 The product can cause inheritable damage.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.

(Contd. on page 8)

PH

Safety Data Sheet according to GHS

Printing date 20.12.2022

Revision: 27.05.2022

Trade name: ISLAND OIL TINTING COLORS




(Contd. of page 7)

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
 Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
 Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---|
| · UN-Number · ADR, IMDG, IATA | UN1263 |
| · UN proper shipping name · ADR · IMDG · IATA | 1263 PAINT, ENVIRONMENTALLY HAZARDOUS PAINT (KEROSENE, Naphtha (petroleum), hydrodesulfurized heavy), MARINE POLLUTANT PAINT |
| · Transport hazard class(es) · ADR, IMDG <div style="text-align: center;">   </div> | 3 Flammable liquids. 3 |
| · IATA <div style="text-align: center;">  </div> | 3 Flammable liquids. |

(Contd. on page 9)

Safety Data Sheet according to GHS

Printing date 20.12.2022

Revision: 27.05.2022

Trade name: ISLAND OIL TINTING COLORS

(Contd. of page 8)

| | |
|--|---|
| · Label | 3 |
| · Packing group · ADR, IMDG, IATA | III |
| · Environmental hazards: · Marine pollutant: · Special marking (ADR): | Product contains environmentally hazardous substances: Kerosene No Symbol (fish and tree) Symbol (fish and tree) |
| · Special precautions for user · Hazard identification number (Kemler code): · EMS Number: | Warning: Flammable liquids. 30 F-E, S-E |
| · Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 |
| · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| · UN "Model Regulation": | UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS |

15 Regulatory information

 · **Safety, health and environmental regulations/legislation specific for the substance or mixture**

 · **Philippines Inventory of Chemicals and Chemical Substances**

| | |
|-----------------|--|
| CAS: 63148-69-6 | ALKYD RESIN |
| CAS: 8008-20-6 | Kerosene |
| CAS: 14807-96-6 | Hydrated Magnesium Silicate |
| CAS: 64742-82-1 | Naphtha (petroleum), hydrodesulfurized heavy |
| CAS: 471-34-1 | Calcium Carbonate |
| | Carbon black |
| CAS: 1318-93-0 | Montmorillonite |
| CAS: 14808-60-7 | Silicon Dioxide |

 · **Directive 2012/18/EU**

 · **Named dangerous substances - ANNEX I** None of the ingredients is listed.

 · **Seveso category**

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

 · **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

(Contd. on page 10)

PH

Safety Data Sheet according to GHS

Printing date 20.12.2022

Revision: 27.05.2022

Trade name: ISLAND OIL TINTING COLORS

(Contd. of page 9)

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations:**
- **Information about limitation of use:**
*Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.
 Exceptions can be made by the authorities in certain cases.*
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H204 Fire or projection hazard.
 - H226 Flammable liquid and vapour.
 - H227 Combustible liquid.
 - H242 Heating may cause a fire.
 - H304 May be fatal if swallowed and enters airways.
 - H313 May be harmful in contact with skin.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H335 May cause respiratory irritation.
 - H336 May cause drowsiness or dizziness.
 - H340 May cause genetic defects.
 - H350 May cause cancer.
 - H360 May damage fertility or the unborn child.
 - H372 Causes damage to organs through prolonged or repeated exposure.
 - H401 Toxic to aquatic life.
 - H402 Harmful to aquatic life.
 - H411 Toxic to aquatic life with long lasting effects.
 - H412 Harmful to aquatic life with long lasting effects.
 - H413 May cause long lasting harmful effects to aquatic life.
- R10 Flammable.
- R38 Irritating to skin.
- R43 May cause sensitisation by skin contact.
- R45 May cause cancer.
- R46 May cause heritable genetic damage.
- R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- R48/25 Toxic: danger of serious damage to health by prolonged exposure if swallowed.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- **Department issuing SDS:** Product safety department
- **Contact:** Mr. Ong
- **Abbreviations and acronyms:**
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent

(Contd. on page 11)

Safety Data Sheet
according to GHS

Printing date 20.12.2022

Revision: 27.05.2022

Trade name: ISLAND OIL TINTING COLORS

(Contd. of page 10)

PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Expl. 1.4: Explosives – Division 1.4
Flam. Liq. 3: Flammable liquids – Category 3
Flam. Liq. 4: Flammable liquids – Category 4
Self-react. C: Self-reactive substances and mixtures – Type C/D
Acute Tox. 5: Acute toxicity – Category 5
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
Muta. 1B: Germ cell mutagenicity – Category 1B
Carc. 1B: Carcinogenicity – Category 1B
Repr. 1A: Reproductive toxicity – Category 1A
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4
*** Data compared to the previous version altered.**

PH