

Technical Data Sheet

ISLAND SUPER KINIS SKIM COAT

DESCRIPTION:

ISLAND SUPER KINIS PREMIUM QUALITY SKIM COAT is a fast-setting polymer modified cement-based compound that provides smooth finish to interior/exterior concrete & gypsum surfaces. It has excellent bonding strength, excellent filling properties, good hydrophobicity are some important properties inherent to this product.

USE:

Exterior & interior plastering & patching

ADVANTAGES:

- Provides an excellent smooth finish, covers up uneven surfaces, ideal for decorative finishes
- Resistant to shrinkage cracking unlike ordinary apuro cement plaster
- Good water vapor permeability
- Thin layer application
- Non-sagging, ideal for overhead application
- Excellent bonding to concrete
- Cost effective
- Easy to apply & sand

COLOR:

Gray & White

FINISH:

Smooth

APPLICATION:





Putty Knife

Masonry Float

- Use a Masonry float or Putty knife in applying Island Super Kinis Premium Quality Skim Coat onto substrate.
- A second coat may be applied to increase thickness. Allow the first coat to dry 1 hour before applying a second coat.

COVERAGE:

20 sq.m /20 kg @ 1mm thickness (1 patch) Note: Coverage may vary depending on surface profile.

PACKAGING:

20 kg. / bag

SHELF LIFE:

1 year in unopened container

SURFACE PREPARATION:

Clean substrate to eliminate dust, dirt, oil, grease, or any contaminant that may inhibit bonding. Dampen concrete surface prior to application of Island Super Kinis Premium Quality Skim Coat.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.

www.islandpaints.com

(63-32) 255-2656



Technical Data Sheet



MIXING RATIO:

Skim Coat	20 kg. /bag
Tap Water	7.0-7.5 liters

1.) By Hand

Mix clean tap water to Island Super Kinis Premium Quality Skim Coat at ratio indicated in the mixing ratio table and mix manually.

2.) Mechanical Mixer

Add Clean tap water to Island Super Kinis Premium Quality Skim Coat at ratio indicated in the mixing ratio table. Mix until a soft creamy paste is formed.

> Open Time : 6-10 minutes Setting Time : 3-4 hours

LABEL ELEMENTS:



Warning: Harmful if swallowed. Causes mild skin and eve irritation.

Precaution: Use of goggles and gloves are highly recommended. In case of splashes, wash-off thoroughly with clean water.

STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.