



ISLAND WOOD PRIMER AND SEALER 801 WHITE

DESCRIPTION:

ISLAND WOOD PRIMER AND SEALER 801 WHITE is an Alkyd type primer for exterior and interior wood application. It has an excellent filling and sealing property and reduces surface absorption making it an ideal foundation for subsequent coats.

USE:

Suited for wood, wallboard, plywood, particle board and the like.

COLOR:

White


FINISH:

Flat

APPLICATION:



Brush



Roller



Spray

NOTE: One coat is normally applied as primer and sealer coat. To patch up joints and deep wood grain, use Island Glazing Putty 803 White.

REDUCTION:

Island 006 Paint Thinner

Brush & Roller : Use as is or add 1/4L per gallon.

Spray : 15 – 20% reduction

DRYING TIME:

Dry to recoat : Allow overnight

COVERAGE:

Approximately 25-30 sq. m. / gallon depending on surface porosity.

SURFACE PREPARATION:

Surface roughness must be sanded, then dust off, clean free of oil dirt. Let dry thoroughly prior to finishing coat.

SUGGESTED FINISH COAT:

All Alkyd based finishing coats like Island Quick Dry Enamel, Island Int. Flatwall En 800FW White, Interior Semi-Gloss Enamel or Island Ext. Gloss Enamel Finishes. In special cases, an emulsion-based paint may be applied as final coat.

PACKAGING:

1L and 4L lithographed can

SHELF LIFE:

2 years in unopened container

STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



LABEL ELEMENTS:



Danger: Flammable liquid and vapour. May cause genetic defects. May cause cancer. May cause damage to the central nervous system through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. Causes skin irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May be harmful if inhaled.

Contains: Kerosene, Naphtha (Petroleum), hydrodesulfurized heavy

Precaution: Avoid exposure – obtain special instructions before use. Keep locked up and out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.