

TECHNICAL DATA SHEET

ISLAND HI-SLIP WOOD LACQUER CLEAR GLOSS

DESCRIPTION:

Island Hi-Slip Wood Lacquer Clear Gloss is a water white clear nitro-cellulose based coating used as finishing over lacquer sanding sealer. It has accelerated drying time with better chemical and heat resistance.

USE:

For Wood furniture, panel boards, cabinet, wood trims and other crafts.

APPEARANCE:

Glossy, Flat, Semi-Gloss (10%, 20%, 35%, 40%, 50%)

RECOMMENDED THINNER:

Wood Lacquer Reducer

REDUCTION RATIO:

1:1 (Paint : Thinner)

DRYING TIME:

Dry to touch : 10 minutes

Dry to sand / recoat : allow 30 minutes

APPLICATION METHOD:



% NVm:

18 + / -1

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.







TECHNICAL DATA SHEET

THEORETICAL COVERAGE:

Approximately 8-12 sq. m. / L

PACKAGING:

3.75L gal and 200L drum

SAFETY PRECAUTION:

FLAMMABLE

- Keep away from heat and open flame.
- Use with adequate ventilation.
- Keep container closed when not in use.
- Avoid prolonged breathing of vapor.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



