

## TECHNICAL DATA SHEET

# ISLAND SUPER KINIS SKIM COAT

#### **DESCRIPTION:**

Island Super Kinis Skim Coat is a fast setting polymer modified cement-based compound that provides smooth finish to interior & exterior concrete surfaces. It has excellent bonding strength, excellent filling properties, good hydrophobicity are some important properties inherent to this product.

### **ADVANTAGES:**

- Provides an excellent smooth finish, covers up uneven surfaces; ideal for decorative finishes.
- Resistant to shrinkage craking unlike ordinary apuro cement plaster.
- Good water vapor permeability.
- Thin layer application.
- Non-sagging, ideal for overhead application.
- Excellent bonding to concrete.
- Cost effective.
- Easy to apply & sand.

### **USES:**

Exterior & interior plastering, patching & floor underlayment.

FINISH:

Smooth

**COLOR:** 

**Gray & White** 

**APPLICATION:** 

**Trowel or Putty Knife** 

### **SURFACE PREPARATION:**

Clean substrate to eliminate dust, dirt, oil, grease or any contaminant that may inhibit bonding. Dampen concrete surface prior to application of Island Super Kinis Skim Coat.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.







# TECHNICAL DATA SHEET

### **MIX RATIO:**

SKIM COAT	20 kg pack
TAP WATER	7.0-7.5 liter

### **MIXING INSTRUCTION:**

Add clean tap water at ratio indicated in table and mix until a soft creamy paste is formed. Let stand for 15 minutes then mix again. Mix occasionally to avoid drying on top layer.

Open Time : 5-10 minutes Setting Time : 3-5 hours

#### **COVERAGE:**

Approximately (1) kg/sq.m.

#### **PACKAGING:**

20 kg. / bag

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



