

Printing date 20.12.2022 Revision: 20.12.2022

1 Identification

- · Product identifier
- · Trade name: LIFE SG COLORS
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Treasure Island Industrial Corp.
No.2, 3rd Ave. S. Osmena Blvd.
North Reclamation Area
Cebu City 6000
PHILIPPINES
doo@treasureisland.com.ph

- · Further information obtainable from: Product safety department
- Emergency telephone number: During normal opening times: +63 32 232 05 13

2 Hazard identification

· Classification of the substance or mixture



Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Acute 2 H401 Toxic to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Sensitising

R43: May cause sensitisation by skin contact.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:



Xi Irritant

· Hazard-determining components of labelling:

1,2-benzisothiazol-3(2H)-one

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

(Contd. on page 2)





Printing date 20.12.2022 Revision: 20.12.2022

Trade name: LIFE SG COLORS

(Contd. of page 1)

· Risk phrases:

- 43 May cause sensitisation by skin contact.
- 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Safety phrases:

- 2 Keep out of the reach of children.
- 24/25 Avoid contact with skin and eyes.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 37 Wear suitable gloves.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- · Special labelling of certain preparations:

Keep out of the reach of children

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

		• , •	1	c ,•	•	7.
- 4	Comi	nasitian	/ int	ormatic	n on in	gredients
	CUIII		ועעע	OI III III III U	The Other Lines	z i cui ci i i s

- · Chemical characterisation: Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compo	onents:	
CAS: 13463-67-7	titanium dioxide [in powder form containing 1% or more of particles with aerodynamic diameter $\leq 10 \mu \text{m}$]	
	& Carc. 2, H351 Acute Tox. 5, H333	
CAS: 471-34-1	Calcium Carbonate	
CAS: 61790-53-2	Diatomaceous earth (Silica-Amorphous)	
CAS: 9004-62-0	2-hydroxyethyl cellulose T Repr. Cat. 1 R60-61 Xn R20/21/22 Xn R42/43 Xi R36 Resp. Sens. 1, H334; Repr. 1A, H360; Asp. Tox. 2, H305 Skin Sens. 1, H317 Acute Tox. 5, H303; Acute Tox. 5, H313; Acute Tox. 5, H333; Eye Irritation 2B, H320	

(Contd. on page 3)





Printing date 20.12.2022 Revision: 20.12.2022

Trade name: LIFE SG COLORS

		(Contd. of page
CAS: 60864-33-7	poly(oxy-1,2-ethanediyl), alpha-(phenylmethyl)-omega-(1,1,3,3-	
	tetramethylbutyl)phenoxy-	
	TR25	
	C R34	
	X Xn R21/22	
	★ Xi R36/37	
	Acute Tox. 2, H300; Acute Tox. 3, H311	
	♦ Skin Corr. 1B, H314; Eye Dam. 1, H318	
	♦ STOT SE 3, H335	
CAS: 330-54-1	diuron(ISO)	
	X Xn R22-40-48/22	
	N R50/53	
	Carc. Cat. 3	
	♦ Carc. 2, H351; STOT RE 2, H373	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
	♠ Acute Tox. 4, H302	
CAS: 10605-21-7	carbendazim (ISO)	
	W T Muta. Cat. 2, Repr. Cat. 2 R46-60-61	
	N R50/53	
	♦ Muta. 1B, H340; Repr. 1B, H360	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
	Skin Sens. 1, H317	
CAS: 26530-20-1	2-octyl-2H-isothiazol-3-one	
C115. 2000 0 20 1	₩ T R23/24	
	C R34	
	\times Xn R22	
	Xi R43	
	N R50/53	
	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330	
	Skin Corr. 1A, H314; Eye Dam. 1, H318	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
	1) Skin Sens. 1A, H317	
	Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	
CAS: 55065-84-0	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no.	
CAS. 33903-04-9	247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6]	
	(3:1)	
	₩ T R23/24/25	
	C R34	
	X Xi R43	
	N R50/53	
	Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330	
	Acute 10x. 5, H501; Acute 10x. 2, H510; Acute 10x. 2, H550 Skin Corr. 1C, H314; Eye Dam. 1, H318	
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
	1) Skin Sens. 1A, H317	
	Specific concentration limits: Skin Corr. 1C; H314: $C \ge 0.6\%$	
	Skin Irrit. 2; H315: $0.06\% \le C < 0.6$	
	SKM IFFU. 2, H313: 0.00 % ≤ C < 0.0	
	% Eye Dam. 1; H318: C ≥ 0.6 %	
	Eye Dam. 1, H318. C ≥ 0.0 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6	
	Eye Irrii. 2; H319: 0.00 % ≤ C < 0.0	
	% Skin Sens. 1A; H317: C ≥ 0.0015 %	
	SKIII SEIIS. 1A, ∏31/. C ≤ 0.0013 %	





Printing date 20.12.2022 Revision: 20.12.2022

Trade name: LIFE SG COLORS

(Contd. of page 3)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 5)





Printing date 20.12.2022 Revision: 20.12.2022

Trade name: LIFE SG COLORS

(Contd. of page 4)

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

8 Exposure controls / personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

CAS: 471-34-1 Calcium Carbonate

PEL (USA) Long-term value: 15*5** mg/m³

*total dust **respirable fraction

REL (USA) Long-term value: 10* 5** mg/m³
*total dust **respirable fraction

TLV (USA) TLV withdrawn

CAS: 61790-53-2 Diatomaceous earth (Silica-Amorphous)

PEL (USA) 20mppcf or 80mg/m3 /%SiO2

REL (USA) Long-term value: 6 mg/m³

See Pocket Guide App. C

TLV (USA) TLV withdrawn

CAS: 330-54-1 diuron(ISO)

REL (USA) Long-term value: 10 mg/m³

TLV (USA) Long-term value: 10 mg/m³

A4

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)





Printing date 20.12.2022 Revision: 20.12.2022

Trade name: LIFE SG COLORS

(Contd. of page 5)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling

Information on basis about all and all and	sical muon autica
Information on basic physical and chem General Information	ncai properties
Appearance:	
Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value at 20 °C:	8.5
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: 100 °C
Flash point:	Not applicable.
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure at 20 °C:	23 hPa
Density at 20 °C:	1.26 g/cm^3
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Fully miscible.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	0.0 %
Water:	32.5 %
VOC (EC)	0.00 %
Solids content:	45.8 %

(Contd. on page 7)





Printing date 20.12.2022 Revision: 20.12.2022

Trade name: LIFE SG COLORS

(Contd. of page 6)

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC50 values relevant for classification:				
CAS: 13463-67-7 titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]				
Oral	LD50	>20,000 mg/kg (rat)		
Dermal	LD50	>10,000 mg/kg (rabbit)		
Inhalative	LC50/4 h	>6.82 mg/l (rat)		
CAS: 471-34-1 Calcium Carbonate				
Oral	LD50	6,450 mg/kg (rat)		
CAS: 26530-20-1 2-octyl-2H-isothiazol-3-one				

0.10.2000	0 -0 0	- ciyi = 11 150 11111100 1
Oral	LD50	125 mg/kg (ATE)
Dermal	LD50	311 mg/kg (ATE)
Inhalative	I C50/4 h	0.27 mg/l (ATE)

Inhalative LC50/4 h 0.27 mg/l (ATE)

- · Primary irritant effect:
- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation Sensitisation possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish

(Contd. on page 8)





Printing date 20.12.2022 Revision: 20.12.2022

Trade name: LIFE SG COLORS

(Contd. of page 7)

- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground. Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

· UN-Number		
· ADR, ADN, IMDG, IATA	Void	
· UN proper shipping name		
· ADR, ADN, IMDG, IATA	Void	
· Transport hazard class(es)		
· ADR, ADN, IMDG, IATA		
· Class	Void	
· Packing group		
· ADR, IMDG, IATA	Void	
· Environmental hazards:		
· Marine pollutant:	No	
· Transport in bulk according to Annex	II of Marpol	
and the IBC Code	Not applicable.	
· UN "Model Regulation":	Void	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Philippines Inventory of Chemicals and Chemical Substances		
CAS: 7732-18-5	water, distilled, conductivity or of similar purity	
	titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 μ m]	
CAS: 471-34-1	Calcium Carbonate	

(Contd. on page 9)



Printing date 20.12.2022 Revision: 20.12.2022

Trade name: LIFE SG COLORS

	(0, 11, 5, -0)
CAS: 21645-51-2	aluminium hydroxide (Contd. of page 8)
	Diatomaceous earth (Silica-Amorphous)
	` · · · · · · · · · · · · · · · · · · ·
CAS: 8042-47-5	White mineral oil, petroleum
CAS: 9004-62-0	2-hydroxyethyl cellulose
CAS: 60864-33-7	poly(oxy-1,2-ethanediyl), alpha-(phenylmethyl)-omega-(1,1,3,3-tetramethylbutyl) phenoxy-
	Iron Hydroxide Oxide
CAS: 330-54-1	diuron(ISO)
CAS: 10605-21-7	carbendazim (ISO)
CAS: 9036-19-5	Polyethylene glycol octylphenyl ether
CAS: 3586-55-8	(Ethylendioxy)dimethanol
CAS: 26530-20-1	2-octyl-2H-isothiazol-3-one
	Polyethylene Glycol
CAS: 126-99-8	chloroprene (stabilized)
	Carbon black
CAS: 55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
CAS: 7631-86-9	Fumed Silica
CAS: 14807-96-6	Hydrated Magnesium Silicate
CAS: 50-00-0	Formaldehyde
CAS: 107-21-1	ethanediol
CAS: 67-56-1	Methanol
CAS: 10377-60-3	magnesium nitrate

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H300	Fatal if swallowed.
H301	Toxic if swallowed.
H302	Harmful if swallowed.

H303 May be harmful if swallowed.

H305 May be harmful if swallowed and enters airways.

H310 Fatal in contact with skin. H311 Toxic in contact with skin.

H313 May be harmful in contact with skin.H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H320 Causes eye irritation.

H330 Fatal if inhaled.

H333 May be harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

(Contd. on page 10)





Printing date 20.12.2022 Revision: 20.12.2022

Trade name: LIFE SG COLORS

(Contd. of page 9) H340 May cause genetic defects. H351 Suspected of causing cancer. H360 May damage fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. R20/21/22 Harmful by inhalation, in contact with skin and if swallowed. Harmful in contact with skin and if swallowed. R21/22 R22 Harmful if swallowed. R23/24 Toxic by inhalation and in contact with skin. R23/24/25 Toxic by inhalation, in contact with skin and if swallowed. Toxic if swallowed. R25 R34 Causes burns. R36 Irritating to eyes. Irritating to eyes and respiratory system. R36/37 R40 Limited evidence of a carcinogenic effect. R42/43 May cause sensitisation by inhalation and skin contact. R43 May cause sensitisation by skin contact. R46 May cause heritable genetic damage. R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed. R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R60 May impair fertility. R61 May cause harm to the unborn child. · Department issuing SDS: Product safety department · Contact: Mr. Ong Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 2: Acute toxicity - Category 2

Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 5: Acute toxicity — Category 5
Acute Tox. 5: Acute toxicity — Category 5

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irritation 2B: Serious eye damage/eye irritation – Category 2B

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Muta. 1B: Germ cell mutagenicity - Category 1B

Carc. 2: Carcinogenicity – Category 2

Repr. 1A: Reproductive toxicity - Category 1A

Repr. 1B: Reproductive toxicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 11)





Printing date 20.12.2022 Revision: 20.12.2022

Trade name: LIFE SG COLORS

(Contd. of page 10)

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 2: Aspiration hazard – Category 2
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* * Data compared to the previous version altered.