

PRIMA 200AE ACRYLIC EMULSION CLEAR

DESCRIPTION:

PRIMA 200AE ACRYLIC EMULSION CLEAR is a fine blend of water-based emulsion polymers that exhibits high gloss, flexibility, and a water-resistance property.

RECOMMENDED USE:

Suited as topcoat for pebbles, bricks & other masonry structures.


COLOR/APPEARANCE:

Liquid: Milky White
Film : Clear

APPLICATION:



Brush



Roller



Spray

REDUCTION:

Apply as is, no thinning is required.

DRYING TIME:

Dry to recoat : 4 hours

COVERAGE:

10-12 sq. m.

PACKAGING:

1L lithographed container, 4L plastic container

SHELF LIFE:

2 years in unopened container

STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

LABEL ELEMENTS:



Warning: May cause an allergic skin reaction. Harmful to aquatic life.

Contains: Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Precaution: Keep out of the reach of children. Avoid contact with skin. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label. Dispose of this material and its container to hazardous or special waste collection point.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.