



PRIMA 300CP CONCRETE PUTTY

DESCRIPTION:

PRIMA 300CP CONCRETE PUTTY is a water-based type patching material. It exhibits highly elastic film, good adhesion, and good filling property.

USE:

Suited for filling up dents, hairline cracks, dents, joints, corners and edges on concrete and cement plaster.

COLOR:

Off White

APPLICATION:



Putty Knife

APPLICATION METHOD:

1. Apply 1 coat Prima Primer 301 White to concrete. Let dry.
2. Use putty knife to fill up dents & hairline cracks with Prima 300CP Concrete Putty. Allow to dry overnight.
3. Sand to remove surface roughness.
4. Apply another coat of Prima Primer 301 White. Surface is now ready for topcoat.

DRYING TIME:

Dry to recoat : overnight

COVERAGE:

Approximately 5 – 6 sq. m. /gal

Note: Actual coverage depends on depth and condition of dents.

PACKAGING:

1L and 4L plastic container

SHELF LIFE:

2 years in unopened container

STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.