



ROOFKOTE

DESCRIPTION:

ROOFKOTE is an acrylic water-based coating with excellent durability and unmatched flexibility. Exhibits good adhesion, resist flaking, cracking, and chalking: a remarkable advantage over a conventional Portland type roof paint.

USE:

Best suited for galvanized iron, gutter, or downspout. Also for masonry, concrete tile roof or unglazed brick tile.

COLOR:

Available in various colors. Please refer to color chart.


FINISH:

Glossy

APPLICATION TOOLS:



Brush



Roller



Spray

REDUCTION:

FOR BRUSH & ROLLER APPLICATION

Apply as is or if necessary, add ¼ liter of clean water to a gallon of paint.

FOR SPRAY APPLICATION

Add approximately ¼ to ½ liter of clean water to a gallon of paint.

Apply two coats for optimum performance.

RECOMMENDED PRIMER:

Roofkote 370 Metaprime Gray

DRYING TIME:

Dry to recoat : 2-4 hours

SURFACE PREPARATION:

NEW GALVANIZED IRON ROOF:

- ✓ Dust off or remove all loosely adhering dirt or barrier thoroughly
- ✓ Chemical treatment on galvanized iron is optional.
- ✓ Dry up the surface completely prior to application of primer coat.

OLD AND RUSTY GALVANIZED IRON ROOF

- ✓ Spot rust must be sanded, or steel brushed.
- ✓ Treat with Island 440 RC Rust converter.
- ✓ Spot prime treated area with Island Epoxy Primer 130 Red Oxide and let dry.
- ✓ Other are with sound condition must be cleaned up and primed with Roofkote 370 Metaprime Gray
- ✓ Apply finish coat.

COVERAGE:

Approximately 25-30 sq.m./ 4 liters

PACKAGING:

4 L plastic containers

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35°C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

SHELF LIFE:

3 years in unopened container

LABEL ELEMENTS:



Warning. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

Precaution. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of as hazardous waste.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



Head Office Address:

No. 2, 3rd Avenue,
S.Osmeña Blvd., North
Reclamation Area, Cebu City,
6000, Philippines
www.islandpaints.com

Email:

info@treasureisland.com.ph

Tel # Head Office :

232-0513 to 17

Fax:

(63-32) 232-0518

Information Office:

83-35 Plaridel St.,
Cebu City, 6000,
Philippines

Tel # for Info Office :

254-2226

412-4113

412-4082

Fax:

(63-32) 255-2656