Safety Data Sheet
according to GHS

Printing date 27.04.2026 Revision: 27.04.2026

1 Identification

· **Product identifier**

· **Trade name: EPOXY FC 1805FC SEALER COAT**

· **Article number:** CWPEPB-00209
· **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Company Name : Treasure Island Chemical Corp.
Company Address: Sitio Pilit Cabancalan, 6014 City of Mandaue, Cebu Philippines
Email Address: ddo@treasureisland.com.ph
Contact No.: +63 32 346 49 54-55

· **Further information obtainable from:** Product safety department
· **Emergency telephone number:** During normal opening times: +63 32 232 05 13

*

2 Hazard identification

· **Classification of the substance or mixture**

GHS02 flame

Flam. Liq. 3	H226 Flammable liquid and vapour.

GHS07

Acute Tox. 4	H332 Harmful if inhaled.
Skin Irrit. 2	H315 Causes skin irritation.
Serious eye damage/irritation – Category 2A	H319 Causes serious eye irritation.
Acute Tox. 5	H313 May be harmful in contact with skin.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.

CWPEPB-00209

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

Xn; Harmful

R20/21: Harmful by inhalation and in contact with skin.

Xi; Irritant

R38: Irritating to skin.
R10: Flammable.

· **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
· **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)

Safety Data Sheet
according to GHS

Printing date 27.04.2026 Revision: 27.04.2026

Trade name: EPOXY FC 1805FC SEALER COAT

(Contd. of page 1)

· **Label elements**

· **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**

Xn Harmful

· **Hazard-determining components of labelling:**
Dimethylbenzene

· **Risk phrases:**
10 Flammable.
20/21 Harmful by inhalation and in contact with skin.
38 Irritating to skin.

· **Safety phrases:**
2 Keep out of the reach of children.
36/37 Wear suitable protective clothing and gloves.
46 If swallowed, seek medical advice immediately and show this container or label.
56 Dispose of this material and its container to hazardous or special waste collection point.

· **Special labelling of certain preparations:**
Contains Resin acids and rosin acids, esters with pentaerythritol. May produce an allergic reaction.
· **Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.

*
3 Composition / information on ingredients

· **Chemical characterisation: Mixtures**
· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 25036-25-3	Polymer of epoxy resin and bisphenol A Serious eye damage/irritation – Category 2B, H320	

(Contd. on page 3)

Safety Data Sheet
according to GHS

Printing date 27.04.2026 Revision: 27.04.2026

Trade name: EPOXY FC 1805FC SEALER COAT

(Contd. of page 2)

CAS: 1330-20-7	Dimethylbenzene Xn R20/21 Xi R38 R10 Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 Acute Tox. 5, H303	
CAS: 111-76-2	BUTYL CELLOSOLVE Xn R20/21/22 Xi R36/38 Flam. Liq. 3, H226 Acute Tox. 3, H331 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 8050-26-8	Resin acids and rosin acids, esters with pentaerythritol Xn R20/22 Xn R42 Resp. Sens. 1B, H334 Acute Tox. 5, H303; Acute Tox. 5, H333	
CAS: 556-67-2	octamethylcyclotetrasiloxane Xn R62 R53 Repr. Cat. 3 Flam. Liq. 3, H226 Repr. 2, H361 Aquatic Chronic 1, H410 PBT; vPvB	

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**
· **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
· **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:** Rinse opened eye for several minutes under running water.
· **After swallowing:** If symptoms persist consult doctor.
· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

Safety Data Sheet
according to GHS

Printing date 27.04.2026 Revision: 27.04.2026

Trade name: EPOXY FC 1805FC SEALER COAT

(Contd. of page 3)

5 Fire-fighting measures

· **Extinguishing media**
· **Suitable extinguishing agents:** CO2, sand, extinguishing powder. Do not use water.
· **For safety reasons unsuitable extinguishing agents:** Water with full jet
· **Special hazards arising from the substance or mixture** No further relevant information available.
· **Advice for firefighters**
· **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
· **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

· **Handling:**
· **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
· **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

· **Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.
· **Information about storage in one common storage facility:** Not required.
· **Further information about storage conditions:** Keep container tightly sealed.
· **Specific end use(s)** No further relevant information available.

*
8 Exposure controls / personal protection

· **Additional information about design of technical facilities:** No further data; see section 7.

(Contd. on page 5)

Safety Data Sheet
according to GHS

Printing date 27.04.2026 Revision: 27.04.2026

Trade name: EPOXY FC 1805FC SEALER COAT

(Contd. of page 4)

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**	
CAS: 1330-20-7 Dimethylbenzene	
PEL (USA)	Long-term value: 435 mg/m³, 100 ppm
REL (USA)	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm
TLV (USA)	Long-term value: 20 ppm BEI, A4
CAS: 111-76-2 BUTYL CELLOSOLVE	
PEL (USA)	Long-term value: 240 mg/m³, 50 ppm Skin
REL (USA)	Long-term value: 24 mg/m³, 5 ppm Skin
TLV (USA)	Long-term value: 97 mg/m³, 20 ppm BEI, A3
CAS: 556-67-2 octamethylcyclotetrasiloxane	
WEEL (USA)	Long-term value: 10* ppm *OARS WEEL

· **Ingredients with biological limit values:**	
CAS: 1330-20-7 Dimethylbenzene	
BEI (USA)	0.3 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
CAS: 111-76-2 BUTYL CELLOSOLVE	
BEI (USA)	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
· **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 6)

Safety Data Sheet
according to GHS

Printing date 27.04.2026 Revision: 27.04.2026

Trade name: EPOXY FC 1805FC SEALER COAT

(Contd. of page 5)

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

*

9 Physical and chemical properties

· **Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Fluid
Colour:	Clear to slightly hazy
· **Odour:**	Characteristic
· **Odour threshold:**	Not determined.
· **pH-value:**	Not determined.
· **Change in condition**	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	137-143 °C
· **Flash point:**	23 - 60 °C
· **Flammability**	Flammable.
· **Auto-ignition temperature:**	240 °C
· **Decomposition temperature:**	Not determined.
· **Ignition temperature:**	Product is not selfigniting.
· **Explosive properties:**	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 7)

Safety Data Sheet
according to GHS

Printing date 27.04.2026 Revision: 27.04.2026

Trade name: EPOXY FC 1805FC SEALER COAT

(Contd. of page 6)

· **Explosion limits:**	
Lower:	1.1 Vol %
Upper:	7 Vol %
· **Vapour pressure at 20 °C:**	6.7 hPa
· **Density at 20 °C:**	1.06 g/cm³
· **Relative density**	Not determined.
· **Vapour density**	Not determined.
· **Evaporation rate**	Not determined.
· **Solubility in / Miscibility with water:**	Not miscible or difficult to mix.
· **Partition coefficient: n-octanol/water:**	Not determined.
· **Viscosity:**	
Dynamic:	Not determined.
Kinematic:	Not determined.
· **Solvent content:**	
Organic solvents:	48.0 %
VOC (EC)	48.02 %
Solids content:	52.5 %
· **Other information**	No further relevant information available.

10 Stability and reactivity

· **Reactivity** No further relevant information available.
· **Chemical stability**
· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
· **Possibility of hazardous reactions** No dangerous reactions known.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** No dangerous decomposition products known.

*

11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity**

· **LD/LC50 values relevant for classification:**		
CAS: 1330-20-7 Dimethylbenzene		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
CAS: 111-76-2 BUTYL CELLOSOLVE		
Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (rat)

(Contd. on page 8)

Safety Data Sheet
according to GHS

Printing date 27.04.2026 Revision: 27.04.2026

Trade name: EPOXY FC 1805FC SEALER COAT

(Contd. of page 7)

Dermal	LD50	400 mg/kg (rab)
Inhalative	LC50/4 h	3 mg/l (ATE)

· **Primary irritant effect:**
· **Skin corrosion/irritation** Irritant to skin and mucous membranes.
· **Serious eye damage/irritation** No irritating effect.
· **Respiratory or skin sensitisation** No sensitising effects known.
· **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant

12 Ecological information

· **Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **Persistence and degradability** No further relevant information available.
· **Behaviour in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.
· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**
· **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**
· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**	
· **ADR, IMDG, IATA**	UN1263
· **UN proper shipping name**	
· **ADR**	1263 PAINT

(Contd. on page 9)

Safety Data Sheet
according to GHS

Printing date 27.04.2026 Revision: 27.04.2026

Trade name: EPOXY FC 1805FC SEALER COAT

(Contd. of page 8)

· **IMDG, IATA**	PAINT
· **Transport hazard class(es)**	
· **ADR, IMDG, IATA**	
· **Class**	3 Flammable liquids.
· **Label**	3
· **Packing group**	
· **ADR, IMDG, IATA**	III
· **Environmental hazards:**	
· **Marine pollutant:**	No
· **Special precautions for user**	Warning: Flammable liquids.
· **Hazard identification number (Kemler code):**	30
· **EMS Number:**	F-E,S-E
· **Transport in bulk according to Annex II of Marpol and the IBC Code**	Not applicable.
· **Transport/Additional information:**	
· **ADR**	
· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· **Transport category**	3
· **IMDG**	
· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· **UN "Model Regulation":**	UN 1263 PAINT, 3, III

*
15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Philippines Inventory of Chemicals and Chemical Substances**

All ingredients are listed.

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.
· **Seveso category** P5c FLAMMABLE LIQUIDS
· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

(Contd. on page 10)

Safety Data Sheet
according to GHS

Printing date 27.04.2026 Revision: 27.04.2026

Trade name: EPOXY FC 1805FC SEALER COAT

(Contd. of page 9)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H303 May be harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H320 Causes eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H333 May be harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H361 Suspected of damaging fertility or the unborn child.
H410 Very toxic to aquatic life with long lasting effects.

R10 Flammable.
R20/21 Harmful by inhalation and in contact with skin.
R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
R20/22 Harmful by inhalation and if swallowed.
R36/38 Irritating to eyes and skin.
R38 Irritating to skin.
R42 May cause sensitisation by inhalation.
R53 May cause long-term adverse effects in the aquatic environment.
R62 Possible risk of impaired fertility.

· **Department issuing SDS:** Product safety department
· **Contact:** Mr. Ong
· **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 5: Acute toxicity – Category 5
Acute Tox. 4: Acute toxicity – Category 4

(Contd. on page 11)

Safety Data Sheet
according to GHS

Printing date 27.04.2026 *Revision: 27.04.2026*

Trade name: EPOXY FC 1805FC SEALER COAT

(Contd. of page 10)

Acute Tox. 3: Acute toxicity – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Serious eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A
Serious eye damage/irritation – Category 2B: Serious eye damage/eye irritation – Category 2B
Resp. Sens. 1B: Respiratory sensitisation – Category 1B
Repr. 2: Reproductive toxicity – Category 2
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **** Data compared to the previous version altered.***

Safety Data Sheet
according to GHS

Printing date 13.05.2026 Revision: 13.05.2026

1 Identification

· **Product identifier**

· **Trade name: EPOXY FC 111FC HARDENER**

· **Article number:** CWPEPB-03895
· **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Company Name : Treasure Island Chemical Corp.
Company Address: Sitio Pilit Cabancalan, 6014 City of Mandaue, Cebu Philippines
Email Address: ddo@treasureisland.com.ph
Contact No.: +63 32 346 49 54-55

· **Further information obtainable from:** Product safety department
· **Emergency telephone number:** During normal opening times: +63 32 232 05 13

*

2 Hazard identification

· **Classification of the substance or mixture**

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Serious eye damage/irritation – Category 2A H319 Causes serious eye irritation.

Acute Tox. 5 H333 May be harmful if inhaled.
I-0434

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

Xn; Harmful

R20/21: Harmful by inhalation and in contact with skin.

Xi; Irritant

R38: Irritating to skin.

· **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
· **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)

Safety Data Sheet
according to GHS

Printing date 13.05.2026 Revision: 13.05.2026

Trade name: EPOXY FC 111FC HARDENER

(Contd. of page 1)

· **Label elements**

· **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



Xn Harmful
Xi Irritant

· **Hazard-determining components of labelling:**
Dimethylbenzene

· **Risk phrases:**
20/21 Harmful by inhalation and in contact with skin.
38 Irritating to skin.

· **Safety phrases:**
2 Keep out of the reach of children.
36/37 Wear suitable protective clothing and gloves.
46 If swallowed, seek medical advice immediately and show this container or label.
56 Dispose of this material and its container to hazardous or special waste collection point.

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition / information on ingredients

· **Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 1330-20-7	Dimethylbenzene Xn R20/21 Xi R38 R10 Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 Acute Tox. 5, H303	
CAS: 67-63-0	Isopropyl Alcohol Xi R36 F R11 R67 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 Acute Tox. 5, H333	

(Contd. on page 3)

Safety Data Sheet
according to GHS

Printing date 13.05.2026 Revision: 13.05.2026

Trade name: EPOXY FC 111FC HARDENER

(Contd. of page 2)

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**
· **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
· **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:** Rinse opened eye for several minutes under running water.
· **After swallowing:** If symptoms persist consult doctor.
· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**
· **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
· **Special hazards arising from the substance or mixture** No further relevant information available.
· **Advice for firefighters**
· **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures** Not required.
· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
· **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

· **Handling:**
· **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

(Contd. on page 4)

Safety Data Sheet
according to GHS

Printing date 13.05.2026 Revision: 13.05.2026

Trade name: EPOXY FC 111FC HARDENER

(Contd. of page 3)

· **Information about fire - and explosion protection:** No special measures required.

· **Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.
· **Information about storage in one common storage facility:** Not required.
· **Further information about storage conditions:** Keep container tightly sealed.
· **Specific end use(s)** No further relevant information available.

8 Exposure controls / personal protection

· **Additional information about design of technical facilities:** No further data; see section 7.

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**	
CAS: 1330-20-7 Dimethylbenzene	
PEL (USA)	Long-term value: 435 mg/m³, 100 ppm
REL (USA)	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm
TLV (USA)	Long-term value: 20 ppm BEI, A4
CAS: 67-63-0 Isopropyl Alcohol	
PEL (USA)	Long-term value: 980 mg/m³, 400 ppm
REL (USA)	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
TLV (USA)	Short-term value: 984 mg/m³, 400 ppm Long-term value: 491 mg/m³, 200 ppm BEI, A4

· **Ingredients with biological limit values:**	
CAS: 1330-20-7 Dimethylbenzene	
BEI (USA)	0.3 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
CAS: 67-63-0 Isopropyl Alcohol	
BEI (USA)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.

(Contd. on page 5)

Safety Data Sheet
according to GHS

Printing date 13.05.2026 Revision: 13.05.2026

Trade name: EPOXY FC 111FC HARDENER

(Contd. of page 4)

Avoid contact with the skin.
Avoid contact with the eyes and skin.

· **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Goggles recommended during refilling

9 Physical and chemical properties

· **Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Fluid
Colour:	Yellowish
· **Odour:**	Characteristic
· **Odour threshold:**	Not determined.
· **pH-value:**	Not determined.
· **Change in condition**	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	82 °C
· **Flash point:**	Not applicable.
· **Flammability**	Not applicable.
· **Auto-ignition temperature:**	390 °C
· **Decomposition temperature:**	Not determined.
· **Ignition temperature:**	Product is not selfigniting.
· **Explosive properties:**	Not determined.

(Contd. on page 6)

Safety Data Sheet
according to GHS

Printing date 13.05.2026 Revision: 13.05.2026

Trade name: EPOXY FC 111FC HARDENER

(Contd. of page 5)

· **Explosion limits:**	
Lower:	1.2 Vol %
Upper:	12 Vol %
· **Vapour pressure at 20 °C:**	43 hPa
· **Density at 20 °C:**	0.89 g/cm³
· **Relative density**	Not determined.
· **Vapour density**	Not determined.
· **Evaporation rate**	Not determined.
· **Solubility in / Miscibility with water:**	Not miscible or difficult to mix.
· **Partition coefficient: n-octanol/water:**	Not determined.
· **Viscosity:**	
Dynamic:	Not determined.
Kinematic:	Not determined.
· **Solvent content:**	
Organic solvents:	46.4 %
VOC (EC)	46.36 %
Solids content:	27.0 %
· **Other information**	No further relevant information available.

10 Stability and reactivity

· **Reactivity** No further relevant information available.
· **Chemical stability**
· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
· **Possibility of hazardous reactions** No dangerous reactions known.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity**

· **LD/LC50 values relevant for classification:**

CAS: 1330-20-7 Dimethylbenzene		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
CAS: 67-63-0 Isopropyl Alcohol		
Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)

(Contd. on page 7)

Safety Data Sheet
according to GHS

Printing date 13.05.2026 Revision: 13.05.2026

Trade name: EPOXY FC 111FC HARDENER

(Contd. of page 6)

Inhalative	LC50/4 h	30 mg/l (rat)

· **Primary irritant effect:**
· **Skin corrosion/irritation** Irritant to skin and mucous membranes.
· **Serious eye damage/irritation** No irritating effect.
· **Respiratory or skin sensitisation** No sensitising effects known.
· **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant

12 Ecological information

· **Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **Persistence and degradability** No further relevant information available.
· **Behaviour in environmental systems:**
· **Bioaccumulative potential** No further relevant information available.
· **Mobility in soil** No further relevant information available.
· **Additional ecological information:**
· **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.
· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**
· **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**
· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**	
· **ADR, IMDG, IATA**	UN1263
· **UN proper shipping name**	
· **ADR**	1263 PAINT
· **IMDG, IATA**	PAINT

(Contd. on page 8)

Safety Data Sheet
according to GHS

Printing date 13.05.2026 Revision: 13.05.2026

Trade name: EPOXY FC 111FC HARDENER

(Contd. of page 7)

· **Transport hazard class(es)**

· **ADR, IMDG, IATA**

· **Class**	3 Flammable liquids.
· **Label**	3
· **Packing group**	
· **ADR, IMDG, IATA**	I
· **Environmental hazards:**	
· **Marine pollutant:**	No
· **Special precautions for user**	Warning: Flammable liquids.
· **Hazard identification number (Kemler code):**	30
· **EMS Number:**	F-E,S-E
· **Transport in bulk according to Annex II of Marpol and the IBC Code**	Not applicable.
· **Transport/Additional information:**	
· **ADR**	
· **Limited quantities (LQ)**	500 ml
· **Excepted quantities (EQ)**	Code: E3 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 300 ml
· **Transport category**	1
· **IMDG**	
· **Limited quantities (LQ)**	500 ml
· **Excepted quantities (EQ)**	Code: E3 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 300 ml
· **UN "Model Regulation":**	UN 1263 PAINT, 3, I

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Philippines Inventory of Chemicals and Chemical Substances**	
CAS: 1330-20-7	Dimethylbenzene
CAS: 67-63-0	Isopropyl Alcohol
CAS: 90-72-2	2,4,6-tris(dimethylaminomethyl)phenol

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.
· **Seveso category** P5c FLAMMABLE LIQUIDS

(Contd. on page 9)

Safety Data Sheet
according to GHS

Printing date 13.05.2026 Revision: 13.05.2026

Trade name: EPOXY FC 111FC HARDENER

(Contd. of page 8)

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H303 May be harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H333 May be harmful if inhaled.
H336 May cause drowsiness or dizziness.

R10 Flammable.
R11 Highly flammable.
R20/21 Harmful by inhalation and in contact with skin.
R36 Irritating to eyes.
R38 Irritating to skin.
R67 Vapours may cause drowsiness and dizziness.

· **Department issuing SDS:** Product safety department
· **Contact:** Mr. Ong
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 5: Acute toxicity – Category 5
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Serious eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
· *** Data compared to the previous version altered.**