Safety Data Sheet
according to GHS

Printing date 22.04.2026 Revision: 22.04.2026

1 Identification

· **Product identifier**

· **Trade name: PRIMA FLAT LATEX COLORS**
· **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Company Name : Treasure Island Chemical Corp.
Company Address: Sitio Pilit Cabancalan, 6014 City of Mandaue, Cebu Philippines
Email Address: ddo@treasureisland.com.ph
Contact No.: +63 32 346 49 54-55

· **Further information obtainable from:** Product safety department
· **Emergency telephone number:** During normal opening times: +63 32 232 05 13

*
2 Hazard identification

· **Classification of the substance or mixture**

GHS07

Acute Tox. 4	H302 Harmful if swallowed.
Skin Sens. 1	H317 May cause an allergic skin reaction.
Acute Tox. 5	H333 May be harmful if inhaled.
Aquatic Acute 3	H402 Harmful to aquatic life.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

Xi; Sensitising

R43: May cause sensitisation by skin contact.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
· **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
· **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **Label elements**

· **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**

Xi Irritant

(Contd. on page 2)

Safety Data Sheet
according to GHS

Printing date 22.04.2026 Revision: 22.04.2026

Trade name: PRIMA FLAT LATEX COLORS

(Contd. of page 1)

· **Hazard-determining components of labelling:**
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

· **Risk phrases:**
43 May cause sensitisation by skin contact.
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Safety phrases:**
2 Keep out of the reach of children.
24/25 Avoid contact with skin and eyes.
29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
37 Wear suitable gloves.
46 If swallowed, seek medical advice immediately and show this container or label.
· **Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.

3 Composition / information on ingredients

· **Chemical characterisation: Mixtures**
· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**		
CAS: 13463-67-7	titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] Carc. 2, H351 Acute Tox. 5, H333	
CAS: 1332-58-7	Kaolin	
CAS: 471-34-1	Calcium Carbonate	
CAS: 111-46-6	Diethylene Glycol Xn R22 Acute Tox. 4, H302	

(Contd. on page 3)

Safety Data Sheet
according to GHS

Printing date 22.04.2026 Revision: 22.04.2026

Trade name: PRIMA FLAT LATEX COLORS

(Contd. of page 2)

CAS: 111-76-2	BUTYL CELLOSOLVE Xn R20/21/22 Xi R36/38 Flam. Liq. 3, H226 Acute Tox. 3, H331 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 9004-62-0	2-hydroxyethyl cellulose T Repr. Cat. 1 R60-61 Xn R20/21/22 Xn R42/43 Xi R36 Resp. Sens. 1, H334; Repr. 1A, H360; Asp. Tox. 2, H305 Skin Sens. 1, H317 Acute Tox. 5, H303; Acute Tox. 5, H313; Acute Tox. 5, H333; Serious eye damage/irritation – Category 2B, H320	
CAS: 60864-33-7	poly(oxy-1,2-ethanediyl), alpha-(phenylmethyl)-omega-(1,1,3,3-tetramethylbutyl)phenoxy- T R25 C R34 Xn R21/22 Xi R36/37 Acute Tox. 2, H300; Acute Tox. 3, H311 Skin Corr. 1B, H314; Eye Dam. 1, H318 STOT SE 3, H335	
CAS: 7664-41-7	Ammonia T R23 C R34 N R50 R10 Press. Gas C, H280 Acute Tox. 3, H331 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Acute Tox. 4, H302 Flam. Gas 2, H221	
CAS: 330-54-1	diuron(ISO) Xn R22-40-48/22 N R50/53 Carc. Cat. 3 Carc. 1B, H350; STOT RE 2, H373 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
CAS: 10605-21-7	carbendazim (ISO) T Muta. Cat. 2, Repr. Cat. 2 R46-60-61 N R50/53 Muta. 1B, H340; Repr. 1B, H360 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1, H317	

(Contd. on page 4)

Safety Data Sheet
according to GHS

Printing date 22.04.2026 Revision: 22.04.2026

Trade name: PRIMA FLAT LATEX COLORS

(Contd. of page 3)

CAS: 26530-20-1	2-octyl-2H-isothiazol-3-one T R23/24 C R34 Xn R22 Xi R43 N R50/53 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330 Skin Corr. 1A, H314; Eye Dam. 1, H318 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1A, H317 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	
CAS: 55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) T R23/24/25 C R34 Xi R43 N R50/53 Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330 Skin Corr. 1C, H314; Eye Dam. 1, H318 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1A, H317 Specific concentration limits: Skin Corr. 1C; H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**
· **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:** Rinse opened eye for several minutes under running water.
· **After swallowing:** If symptoms persist consult doctor.
· **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**
· **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
· **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 5)

Safety Data Sheet
according to GHS

Printing date 22.04.2026 Revision: 22.04.2026

Trade name: PRIMA FLAT LATEX COLORS

(Contd. of page 4)

· ***Advice for firefighters***
· ***Protective equipment:*** *No special measures required.*

6 Accidental release measures

· ***Personal precautions, protective equipment and emergency procedures*** *Not required.*
· ***Environmental precautions:***
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
· ***Methods and material for containment and cleaning up:***
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
· ***Reference to other sections***
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

· ***Handling:***
· ***Precautions for safe handling***
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
· ***Information about fire - and explosion protection:*** *No special measures required.*

· ***Conditions for safe storage, including any incompatibilities***
· ***Storage:***
· ***Requirements to be met by storerooms and receptacles:*** *No special requirements.*
· ***Information about storage in one common storage facility:*** *Not required.*
· ***Further information about storage conditions:*** *None.*
· ***Specific end use(s)*** *No further relevant information available.*

8 Exposure controls / personal protection

· ***Additional information about design of technical facilities:*** *No further data; see section 7.*

· ***Control parameters***

· ***Ingredients with limit values that require monitoring at the workplace:***	
CAS: 1332-58-7 Kaolin	
PEL (USA)	*Long-term value: 15* 5** mg/m³ *total dust **respirable fraction*
REL (USA)	*Long-term value: 10* 5** mg/m³ *total dust **respirable fraction*

(Contd. on page 6)

Safety Data Sheet
according to GHS

Printing date 22.04.2026 Revision: 22.04.2026

Trade name: PRIMA FLAT LATEX COLORS

(Contd. of page 5)

TLV (USA)	Long-term value: 2* mg/m³ E; respirable particulate matter, A4
CAS: 471-34-1 Calcium Carbonate	
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn
CAS: 111-46-6 Diethylene Glycol	
WEEL (USA)	Long-term value: 10 mg/m³
CAS: 111-76-2 BUTYL CELLOSOLVE	
PEL (USA)	Long-term value: 240 mg/m³, 50 ppm Skin
REL (USA)	Long-term value: 24 mg/m³, 5 ppm Skin
TLV (USA)	Long-term value: 97 mg/m³, 20 ppm BEI, A3
CAS: 7664-41-7 Ammonia	
PEL (USA)	Long-term value: 35 mg/m³, 50 ppm
REL (USA)	Short-term value: 27 mg/m³, 35 ppm Long-term value: 18 mg/m³, 25 ppm
TLV (USA)	Short-term value: 24 mg/m³, 35 ppm Long-term value: 17 mg/m³, 25 ppm
CAS: 330-54-1 diuron(ISO)	
REL (USA)	Long-term value: 10 mg/m³
TLV (USA)	Long-term value: 10 mg/m³ A4

· **Ingredients with biological limit values:**

CAS: 111-76-2 BUTYL CELLOSOLVE	
BEI (USA)	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**
· **Personal protective equipment:**
· **General protective and hygienic measures:**
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
· **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 7)

Safety Data Sheet
according to GHS

Printing date 22.04.2026 Revision: 22.04.2026

Trade name: PRIMA FLAT LATEX COLORS

(Contd. of page 6)

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Goggles recommended during refilling

9 Physical and chemical properties

· **Information on basic physical and chemical properties**	
· **General Information**	
· **Appearance:**	
Form:	Fluid
Colour:	According to product specification
· **Odour:**	Characteristic
· **Odour threshold:**	Not determined.
· **pH-value:**	Not determined.
· **Change in condition**	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	100 °C
· **Flash point:**	Not applicable.
· **Flammability**	Not applicable.
· **Decomposition temperature:**	Not determined.
· **Ignition temperature:**	Product is not selfigniting.
· **Explosive properties:**	Product does not present an explosion hazard.
· **Explosion limits:**	
Lower:	Not determined.
Upper:	Not determined.
· **Vapour pressure at 20 °C:**	23 hPa
· **Density at 20 °C:**	1.45 g/cm³
· **Relative density**	Not determined.
· **Vapour density**	Not determined.

(Contd. on page 8)

Safety Data Sheet
according to GHS

Printing date 22.04.2026 Revision: 22.04.2026

Trade name: PRIMA FLAT LATEX COLORS

(Contd. of page 7)

· **Evaporation rate**	Not determined.
· **Solubility in / Miscibility with water:**	Fully miscible.
· **Partition coefficient: n-octanol/water:**	Not determined.
· **Viscosity:**	
Dynamic:	Not determined.
Kinematic:	Not determined.
· **Solvent content:**	
Organic solvents:	2.0 %
Water:	45.2 %
VOC (EC)	8.04 %
Solids content:	53.7 %
· **Other information**	No further relevant information available.

10 Stability and reactivity

· **Reactivity** No further relevant information available.
· **Chemical stability**
· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
· **Possibility of hazardous reactions** No dangerous reactions known.
· **Conditions to avoid** No further relevant information available.
· **Incompatible materials:** No further relevant information available.
· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**
· **Acute toxicity**

· **LD/LC50 values relevant for classification:**		
CAS: 13463-67-7 titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]		
Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (rat)
CAS: 471-34-1 Calcium Carbonate		
Oral	LD50	6,450 mg/kg (rat)
CAS: 111-46-6 Diethylene Glycol		
Oral	LD50	12,565 mg/kg (rat)
Dermal	LD50	11,890 mg/kg (rabbit)
CAS: 111-76-2 BUTYL CELLOSOLVE		
Oral	LD50	1,200 mg/kg (ATE)

(Contd. on page 9)

Safety Data Sheet
according to GHS

Printing date 22.04.2026 Revision: 22.04.2026

Trade name: PRIMA FLAT LATEX COLORS

(Contd. of page 8)

		1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)
Inhalative	LC50/4 h	3 mg/l (ATE)
CAS: 7664-41-7 Ammonia		
Oral	LD50	350 mg/kg (rat)
Inhalative	LC50/4 h	2,000 mg/l (rat)
CAS: 26530-20-1 2-octyl-2H-isothiazol-3-one		
Oral	LD50	125 mg/kg (ATE)
Dermal	LD50	311 mg/kg (ATE)
Inhalative	LC50/4 h	0.27 mg/l (ATE)

· ***Primary irritant effect:***
· ***Skin corrosion/irritation*** *No irritant effect.*
· ***Serious eye damage/irritation*** *No irritating effect.*
· ***Respiratory or skin sensitisation*** *Sensitisation possible through skin contact.*
· ***Additional toxicological information:***
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological information

· ***Toxicity***
· ***Aquatic toxicity:*** *No further relevant information available.*
· ***Persistence and degradability*** *No further relevant information available.*
· ***Behaviour in environmental systems:***
· ***Bioaccumulative potential*** *No further relevant information available.*
· ***Mobility in soil*** *No further relevant information available.*
· ***Ecotoxical effects:***
· ***Remark:*** *Harmful to fish*
· ***Additional ecological information:***
· ***General notes:***
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
· ***Results of PBT and vPvB assessment***
· ***PBT:*** *Not applicable.*
· ***vPvB:*** *Not applicable.*
· ***Other adverse effects*** *No further relevant information available.*

13 Disposal considerations

· ***Waste treatment methods***
· ***Recommendation***
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10)

Safety Data Sheet
according to GHS

Printing date 22.04.2026 Revision: 22.04.2026

Trade name: PRIMA FLAT LATEX COLORS

(Contd. of page 9)

· **Uncleaned packaging:**
· **Recommendation:** Disposal must be made according to official regulations.
· **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

*
14 Transport information

· **UN-Number**	
· **ADR, IMDG, IATA**	Void
· **UN proper shipping name**	
· **ADR, IMDG, IATA**	Void
· **Transport hazard class(es)**	
· **ADR, ADN, IMDG, IATA**	
· **Class**	Void
· **Packing group**	
· **ADR, IMDG, IATA**	Void
· **Environmental hazards:**	
· **Marine pollutant:**	No
· **Transport in bulk according to Annex II of Marpol and the IBC Code**	Not applicable.
· **UN "Model Regulation":**	Void

*
15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Philippines Inventory of Chemicals and Chemical Substances**	
CAS: 7732-18-5	water, distilled, conductivity or of similar purity
CAS: 13463-67-7	titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]
CAS: 14807-96-6	Hydrated Magnesium Silicate
CAS: 1332-58-7	Kaolin
CAS: 471-34-1	Calcium Carbonate
CAS: 57516-68-4	STYRENE ACRYLATE COPOLYMER
CAS: 111-46-6	Diethylene Glycol
CAS: 112926-00-8	Precipitated silica (Silica-Amorphous)
CAS: 21645-51-2	aluminium hydroxide
CAS: 111-76-2	BUTYL CELLOSOLVE
CAS: 9004-62-0	2-hydroxyethyl cellulose
CAS: 8042-47-5	White mineral oil, petroleum
CAS: 60864-33-7	poly(oxy-1,2-ethanediyl), alpha-(phenylmethyl)-omega-(1,1,3,3-tetramethylbutyl)phenoxy-

(Contd. on page 11)

Safety Data Sheet
according to GHS

Printing date 22.04.2026 Revision: 22.04.2026

Trade name: PRIMA FLAT LATEX COLORS

(Contd. of page 10)

CAS: 7664-41-7	Ammonia
CAS: 330-54-1	diuron(ISO)
CAS: 10605-21-7	carbendazim (ISO)
CAS: 9036-19-5	Polyethylene glycol octylphenyl ether
CAS: 64-19-7	acetic acid
CAS: 1336-21-6	ammonia
CAS: 3586-55-8	(Ethylendioxy)dimethanol
	Polyethylene Glycol
CAS: 26530-20-1	2-octyl-2H-isothiazol-3-one
CAS: 55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.
· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**
H221 Flammable gas.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H300 Fatal if swallowed.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H303 May be harmful if swallowed.
H305 May be harmful if swallowed and enters airways.
H310 Fatal in contact with skin.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H313 May be harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H320 Causes eye irritation.
H330 Fatal if inhaled.
H331 Toxic if inhaled.
H333 May be harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H340 May cause genetic defects.
H350 May cause cancer.
H351 Suspected of causing cancer.

(Contd. on page 12)

Safety Data Sheet
according to GHS

Printing date 22.04.2026 Revision: 22.04.2026

Trade name: PRIMA FLAT LATEX COLORS

(Contd. of page 11)

H360 May damage fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

R10 Flammable.
R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
R21/22 Harmful in contact with skin and if swallowed.
R22 Harmful if swallowed.
R23 Toxic by inhalation.
R23/24 Toxic by inhalation and in contact with skin.
R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
R25 Toxic if swallowed.
R34 Causes burns.
R36 Irritating to eyes.
R36/37 Irritating to eyes and respiratory system.
R36/38 Irritating to eyes and skin.
R40 Limited evidence of a carcinogenic effect.
R42/43 May cause sensitisation by inhalation and skin contact.
R43 May cause sensitisation by skin contact.
R46 May cause heritable genetic damage.
R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.
R50 Very toxic to aquatic organisms.
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R60 May impair fertility.
R61 May cause harm to the unborn child.

· **Department issuing SDS:** Product safety department
· **Contact:** Mr. Ong
· **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 2: Flammable gases – Category 2
Press. Gas C: Gases under pressure – Compressed gas
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 2: Acute toxicity – Category 2
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 5: Acute toxicity – Category 5
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Corr. 1C: Skin corrosion/irritation – Category 1C

(Contd. on page 13)

Safety Data Sheet
according to GHS

Printing date 22.04.2026 *Revision: 22.04.2026*

Trade name: PRIMA FLAT LATEX COLORS

(Contd. of page 12)

Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Serious eye damage/irritation – Category 2B: Serious eye damage/eye irritation – Category 2B
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Muta. 1B: Germ cell mutagenicity – Category 1B
Carc. 1B: Carcinogenicity – Category 1B
Carc. 2: Carcinogenicity – Category 2
Repr. 1A: Reproductive toxicity – Category 1A
Repr. 1B: Reproductive toxicity – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 2: Aspiration hazard – Category 2
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **** Data compared to the previous version altered.***