



Safety Data Sheet according to GHS

Printing date 08.04.2026

Revision: 08.04.2026

1 Identification

- **Product identifier**
- **Trade name: PRIMA SATIN COLORS**
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Company Name : Treasure Island Chemical Corp.
Company Address: Sitio Pilit Cabancalan, 6014 City of Mandaue, Cebu Philippines
Email Address: ddo@treasureisland.com.ph
Contact No.: +63 32 346 49 54-55
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:** During normal opening times: +63 32 232 05 13

2 Hazard identification

- **Classification of the substance or mixture**



GHS07

- Skin Sens. 1 H317 May cause an allergic skin reaction.
- Acute Tox. 5 H333 May be harmful if inhaled.
- Aquatic Acute 3 H402 Harmful to aquatic life.
- Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.
CWPWAB-04024

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
- **Label elements**
- **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Risk phrases:**
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- **Safety phrases:**
29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
60 This material and its container must be disposed of as hazardous waste.
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.

(Contd. on page 2)



Safety Data Sheet
according to GHS

Printing date 08.04.2026

Revision: 08.04.2026

Trade name: PRIMA SATIN COLORS

(Contd. of page 1)

· **vPvB:** Not applicable.

3 Composition / information on ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 13463-67-7	titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]	
	Carc. 2, H351 Acute Tox. 5, H333	
CAS: 471-34-1	Calcium Carbonate	
CAS: 112926-00-8	Precipitated silica (Silica-Amorphous)	
CAS: 330-54-1	diuron(ISO)	
	Xn R22-40-48/22 N R50/53 Carc. Cat. 3	
	Carc. 1B, H350; STOT RE 2, H373 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
CAS: 10605-21-7	carbendazim (ISO)	
	T Muta. Cat. 2, Repr. Cat. 2 R46-60-61 N R50/53	
	Muta. 1B, H340; Repr. 1B, H360 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1, H317	

(Contd. on page 3)

PH



Safety Data Sheet
according to GHS

Printing date 08.04.2026

Revision: 08.04.2026

Trade name: **PRIMA SATIN COLORS**

(Contd. of page 2)

CAS: 26530-20-1	<p>2-octyl-2H-isothiazol-3-one</p> <p> T R23/24 C R34 Xn R22 Xi R43 N R50/53</p> <p> Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330 Skin Corr. 1A, H314; Eye Dam. 1, H318 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1A, H317 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %</p>	
CAS: 55965-84-9	<p>reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)</p> <p> T R23/24/25 C R34 Xi R43 N R50/53</p> <p> Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330 Skin Corr. 1C, H314; Eye Dam. 1, H318 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1A, H317 Specific concentration limits: Skin Corr. 1C; H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %</p>	

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)



Safety Data Sheet
according to GHS

Printing date 08.04.2026

Revision: 08.04.2026

Trade name: PRIMA SATIN COLORS

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about fire - and explosion protection:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls / personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 471-34-1 Calcium Carbonate	
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn
CAS: 112926-00-8 Precipitated silica (Silica-Amorphous)	
PEL (USA)	20mppcf or 80mg/m ³ /%SiO ₂

(Contd. on page 5)



Safety Data Sheet
according to GHS

Printing date 08.04.2026

Revision: 08.04.2026

Trade name: PRIMA SATIN COLORS

(Contd. of page 4)

REL (USA)	Long-term value: 6 mg/m ³ See Pocket Guide App. C
TLV (USA)	TLV withdrawn
CAS: 330-54-1 diuron(ISO)	
REL (USA)	Long-term value: 10 mg/m ³
TLV (USA)	Long-term value: 10 mg/m ³ A4

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:** Wash hands before breaks and at the end of work.

· **Respiratory protection:** Not required.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Goggles recommended during refilling

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:** Fluid

· **Colour:** According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· **Melting point/freezing point:** Undetermined.

· **Initial boiling point and boiling range:** 100 °C

· **Flash point:** Not applicable.

· **Flammability** Not applicable.

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

(Contd. on page 6)



Safety Data Sheet
according to GHS

Printing date 08.04.2026

Revision: 08.04.2026

Trade name: **PRIMA SATIN COLORS**

(Contd. of page 5)

· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure at 20 °C:	23 hPa
· Density at 20 °C:	1.29 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Fully miscible.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.9 %
Water:	53.5 %
VOC (EC)	13.84 %
Solids content:	46.3 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· LD/LC50 values relevant for classification:		
CAS: 13463-67-7 titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]		
Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)

(Contd. on page 7)



Safety Data Sheet
according to GHS

Printing date 08.04.2026

Revision: 08.04.2026

Trade name: PRIMA SATIN COLORS

(Contd. of page 6)

Inhalative	LC50/4 h	>6.82 mg/l (rat)
CAS: 471-34-1 Calcium Carbonate		
Oral	LD50	6,450 mg/kg (rat)
CAS: 26530-20-1 2-octyl-2H-isothiazol-3-one		
Oral	LD50	125 mg/kg (ATE)
Dermal	LD50	311 mg/kg (ATE)
Inhalative	LC50/4 h	0.27 mg/l (ATE)

- **Primary irritant effect:**
- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

PH

(Contd. on page 8)



Safety Data Sheet
according to GHS

Printing date 08.04.2026

Revision: 08.04.2026

Trade name: PRIMA SATIN COLORS

(Contd. of page 7)

14 Transport information

· UN-Number · ADR, IMDG, IATA	Void
· UN proper shipping name · ADR, IMDG, IATA	Void
· Transport hazard class(es) · ADR, ADN, IMDG, IATA · Class	Void
· Packing group · ADR, IMDG, IATA	Void
· Environmental hazards:	Not applicable.
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· UN "Model Regulation":	Void

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture	
· Philippines Inventory of Chemicals and Chemical Substances	
CAS: 7732-18-5	water, distilled, conductivity or of similar purity
CAS: 13463-67-7	titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]
CAS: 57516-68-4	STYRENE ACRYLATE COPOLYMER
CAS: 471-34-1	Calcium Carbonate
CAS: 14807-96-6	Hydrated Magnesium Silicate
CAS: 25265-77-4	Texanol
CAS: 112926-00-8	Precipitated silica (Silica-Amorphous)
CAS: 21645-51-2	aluminium hydroxide
CAS: 8042-47-5	White mineral oil, petroleum
CAS: 111-46-6	Diethylene Glycol
CAS: 124-68-5	2-amino-2-methylpropanol
CAS: 330-54-1	diuron(ISO)
CAS: 10605-21-7	carbendazim (ISO)
CAS: 27646-80-6	2-Methyl-2-(methylamino)propan-1-ol
CAS: 64-19-7	acetic acid
CAS: 1336-21-6	ammonia
CAS: 3586-55-8	(Ethylendioxy)dimethanol
CAS: 26530-20-1	2-octyl-2H-isothiazol-3-one

(Contd. on page 9)



Safety Data Sheet according to GHS

Printing date 08.04.2026

Revision: 08.04.2026

Trade name: PRIMA SATIN COLORS

(Contd. of page 8)

CAS: 55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
-----------------	---

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H301 Toxic if swallowed.
 - H310 Fatal in contact with skin.
 - H311 Toxic in contact with skin.
 - H314 Causes severe skin burns and eye damage.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H318 Causes serious eye damage.
 - H319 Causes serious eye irritation.
 - H330 Fatal if inhaled.
 - H333 May be harmful if inhaled.
 - H340 May cause genetic defects.
 - H350 May cause cancer.
 - H351 Suspected of causing cancer.
 - H360 May damage fertility or the unborn child.
 - H373 May cause damage to organs through prolonged or repeated exposure.
 - H400 Very toxic to aquatic life.
 - H410 Very toxic to aquatic life with long lasting effects.
-
- R22 Harmful if swallowed.
 - R23/24 Toxic by inhalation and in contact with skin.
 - R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
 - R34 Causes burns.
 - R40 Limited evidence of a carcinogenic effect.
 - R43 May cause sensitisation by skin contact.
 - R46 May cause heritable genetic damage.
 - R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.
 - R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 - R60 May impair fertility.
 - R61 May cause harm to the unborn child.

- **Department issuing SDS:** Product safety department
- **Contact:** Mr. Ong
- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 10)



Safety Data Sheet according to GHS

Printing date 08.04.2026

Revision: 08.04.2026

Trade name: PRIMA SATIN COLORS

(Contd. of page 9)

VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 2: Acute toxicity – Category 2
Acute Tox. 5: Acute toxicity – Category 5
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Muta. 1B: Germ cell mutagenicity – Category 1B
Carc. 1B: Carcinogenicity – Category 1B
Carc. 2: Carcinogenicity – Category 2
Repr. 1B: Reproductive toxicity – Category 1B
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4
· *** Data compared to the previous version altered.**

PH