



Safety Data Sheet according to GHS

Printing date 09.03.2026

Revision: 09.03.2026

1 Identification

· **Product identifier**

· **Trade name:** TEX-A-KOTE PRIMER 2800 WHITE

· **Article number:** CWPACB-00025

· **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Company Name : Treasure Island Chemical Corp.

Company Address: Sitio Pilit Cabancalan, 6014 City of Mandaue, Cebu Philippines

Email Address: ddo@treasureisland.com.ph

Contact No.: +63 32 346 49 54-55

· **Further information obtainable from:** Product safety department

· **Emergency telephone number:** During normal opening times: +63 32 232 05 13

2 Hazard identification

· **Classification of the substance or mixture**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Carc. 1A H350 May cause cancer. Route of exposure: Inhalation

Repr. 1A H360 May damage fertility or the unborn child.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Acute Tox. 5 H333 May be harmful if inhaled.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
CWPACB-00025

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



T; Toxic

R60-61: May impair fertility. May cause harm to the unborn child.



Xn; Harmful

R20/21: Harmful by inhalation and in contact with skin.



Xi; Irritant

(Contd. on page 2)

PH



Safety Data Sheet according to GHS

Printing date 09.03.2026

Revision: 09.03.2026

Trade name: TEX-A-KOTE PRIMER 2800 WHITE

(Contd. of page 1)

R38: Irritating to skin.

R10-52/53: Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **Label elements**

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



T Toxic

· **Hazard-determining components of labelling:**

Dimethylbenzene
di-(2-ethylhexyl) phthalate

· **Risk phrases:**

60 May impair fertility.

61 May cause harm to the unborn child.

10 Flammable.

20/21 Also harmful by inhalation and in contact with skin.

38 Irritating to skin.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Safety phrases:**

53 Avoid exposure - obtain special instructions before use.

1/2 Keep locked up and out of the reach of children.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition / information on ingredients

· **Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



Safety Data Sheet
according to GHS

Printing date 09.03.2026

Revision: 09.03.2026

Trade name: **TEX-A-KOTE PRIMER 2800 WHITE**

(Contd. of page 2)

Dangerous components:

CAS: 471-34-1	Calcium Carbonate	
CAS: 1330-20-7	Dimethylbenzene Xn R20/21 Xi R38 R10 Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 Acute Tox. 5, H303	
CAS: 13463-67-7	titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] Carc. 2, H351 Acute Tox. 5, H333	
CAS: 95-63-6	1,2,4-trimethylbenzene Xn R20 Xi R36/37/38 N R51/53 R10 Flam. Liq. 3, H226 Aquatic Chronic 2, H411 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Acute Tox. 5, H303	
CAS: 108-67-8	1,3,5-trimethylbenzene Xi R37 N R51/53 R10 Flam. Liq. 3, H226 Aquatic Chronic 2, H411 STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: C $\geq$ 25 %	
CAS: 117-81-7	di-(2-ethylhexyl) phthalate T Repr. Cat. 2 R60-61 Repr. 1B, H360	

(Contd. on page 4)

PH



Safety Data Sheet according to GHS

Printing date 09.03.2026

Revision: 09.03.2026

Trade name: **TEX-A-KOTE PRIMER 2800 WHITE**

(Contd. of page 3)

CAS: 98-82-8	isopropylbenzene Xn R65 Xi R37 N R51/53 R10 Flam. Liq. 3, H226 Carc. 1B, H350; Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Acute Tox. 4, H302; STOT SE 3, H335 Acute Tox. 5, H333	
CAS: 111-76-2	BUTYL CELLOSOLVE Xn R20/21/22 Xi R36/38 Flam. Liq. 3, H226 Acute Tox. 3, H331 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319	

· SVHC

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 5)



Safety Data Sheet according to GHS

Printing date 09.03.2026

Revision: 09.03.2026

Trade name: TEX-A-KOTE PRIMER 2800 WHITE

(Contd. of page 4)

- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls / personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.

(Contd. on page 6)



Safety Data Sheet
according to GHS

Printing date 09.03.2026

Revision: 09.03.2026

Trade name: TEX-A-KOTE PRIMER 2800 WHITE

(Contd. of page 5)

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 471-34-1 Calcium Carbonate

PEL (USA) Long-term value: 15* 5** mg/m³
*total dust **respirable fraction

REL (USA) Long-term value: 10* 5** mg/m³
*total dust **respirable fraction

TLV (USA) TLV withdrawn

CAS: 1330-20-7 Dimethylbenzene

PEL (USA) Long-term value: 435 mg/m³, 100 ppm

REL (USA) Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV (USA) Long-term value: 20 ppm
BEL, A4

CAS: 95-63-6 1,2,4-trimethylbenzene

REL (USA) Long-term value: 125 mg/m³, 25 ppm

TLV (USA) Long-term value: 10 ppm

CAS: 108-67-8 1,3,5-trimethylbenzene

REL (USA) Long-term value: 125 mg/m³, 25 ppm

TLV (USA) Long-term value: 10 ppm

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

PEL (USA) Long-term value: 5 mg/m³

REL (USA) Short-term value: 10 mg/m³
Long-term value: 5 mg/m³
See Pocket Guide App. A

TLV (USA) Long-term value: 0.1 mg/m³
Skin, A3

CAS: 98-82-8 isopropylbenzene

PEL (USA) Long-term value: 245 mg/m³, 50 ppm
Skin

REL (USA) Long-term value: 245 mg/m³, 50 ppm
Skin

TLV (USA) Long-term value: 25 mg/m³, 5 ppm
A3

CAS: 111-76-2 BUTYL CELLOSOLVE

PEL (USA) Long-term value: 240 mg/m³, 50 ppm
Skin

REL (USA) Long-term value: 24 mg/m³, 5 ppm
Skin

TLV (USA) Long-term value: 97 mg/m³, 20 ppm
BEL, A3

(Contd. on page 7)



Safety Data Sheet
according to GHS

Printing date 09.03.2026

Revision: 09.03.2026

Trade name: TEX-A-KOTE PRIMER 2800 WHITE

(Contd. of page 6)

· Ingredients with biological limit values:

CAS: 1330-20-7 Dimethylbenzene

BEI (USA) 0.3 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

BEI (USA) 5 µg/g creatinine
Medium: -
Time: Postshift
Parameter: MEHP (population-based)

20 µg/g creatinine
Medium: -
Time: Postshift
Parameter: MEHHP (population-based)

15 µg/g creatinine
Medium: -
Time: Postshift
Parameter: MEOHP (population-based)

25 µg/g creatinine
Medium: -
Time: Postshift
Parameter: MECPP (population-based)

CAS: 111-76-2 BUTYL CELLOSOLVE

BEI (USA) 200 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: Butoxyacetic acid (BAA) (with hydrolysis)

· Additional information: The lists valid during the making were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 8)



Safety Data Sheet
according to GHS

Printing date 09.03.2026

Revision: 09.03.2026

Trade name: TEX-A-KOTE PRIMER 2800 WHITE

(Contd. of page 7)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

*

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Fluid
· Colour:	White
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	137-143 °C

· **Flash point:** 23 - 60 °C

· **Flammability** Flammable.

· **Auto-ignition temperature:** 450 °C

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 9)

PH



Safety Data Sheet
according to GHS

Printing date 09.03.2026

Revision: 09.03.2026

Trade name: TEX-A-KOTE PRIMER 2800 WHITE

(Contd. of page 8)

· Explosion limits:	
Lower:	0.7 Vol %
Upper:	7.5 Vol %
· Vapour pressure at 20 °C:	6.7 hPa
· Density at 20 °C:	1.43 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	25.9 %
VOC (EC)	25.87 %
Solids content:	67.8 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· **LD/LC50 values relevant for classification:**

CAS: 471-34-1 Calcium Carbonate

Oral	LD50	6,450 mg/kg (rat)
------	------	-------------------

CAS: 1330-20-7 Dimethylbenzene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

(Contd. on page 10)



Safety Data Sheet according to GHS

Printing date 09.03.2026

Revision: 09.03.2026

Trade name: **TEX-A-KOTE PRIMER 2800 WHITE**

(Contd. of page 9)

CAS: 13463-67-7 titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (rat)

CAS: 95-63-6 1,2,4-trimethylbenzene

Oral	LD50	5,000 mg/kg (rat)
------	------	-------------------

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

Oral	LD50	30,600 mg/kg (rat)
Dermal	LD50	25,000 mg/kg (rabbit)

CAS: 98-82-8 isopropylbenzene

Oral	LD50	1,400 mg/kg (rat)
Dermal	LD50	12,300 mg/kg (rabbit)
Inhalative	LC50/4 h	24.7 mg/l (mouse)

CAS: 111-76-2 BUTYL CELLOSOLVE

Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)
Inhalative	LC50/4 h	3 mg/l (ATE)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful
Irritant

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 11)



Safety Data Sheet according to GHS

Printing date 09.03.2026

Revision: 09.03.2026

Trade name: **TEX-A-KOTE PRIMER 2800 WHITE**

(Contd. of page 10)

- Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|--|
| · UN-Number
· ADR, IMDG, IATA | UN1263 |
| · UN proper shipping name
· ADR
· IMDG, IATA | 1263 PAINT
PAINT |
| · Transport hazard class(es)
· ADR, IMDG, IATA | |
|  | |
| · Class
· Label | 3 Flammable liquids.
3 |
| · Packing group
· ADR, IMDG, IATA | III |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user
· Hazard identification number (Kemler code):
· EMS Number: | Warning: Flammable liquids.
30
F-E, <u>S-E</u> |
| · Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR
· Limited quantities (LQ) | 5L |

(Contd. on page 12)



Safety Data Sheet
according to GHS

Printing date 09.03.2026

Revision: 09.03.2026

Trade name: TEX-A-KOTE PRIMER 2800 WHITE

(Contd. of page 11)

· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· IMDG	5L
· Limited quantities (LQ)	Code: E1
· Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Philippines Inventory of Chemicals and Chemical Substances**

CAS: 471-34-1	Calcium Carbonate
CAS: 1330-20-7	Dimethylbenzene
CAS: 14807-96-6	Hydrated Magnesium Silicate
CAS: 13463-67-7	titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]
CAS: 95-63-6	1,2,4-trimethylbenzene
CAS: 108-67-8	1,3,5-trimethylbenzene
CAS: 117-81-7	di-(2-ethylhexyl) phthalate
CAS: 98-82-8	isopropylbenzene
CAS: 1302-78-9	bentonite
CAS: 112926-00-8	Precipitated silica (Silica-Amorphous)
CAS: 21645-51-2	aluminium hydroxide
CAS: 8002-43-5	Lecithin
CAS: 111-76-2	BUTYL CELLOSOLVE
CAS: 8050-26-8	Resin acids and rosin acids, esters with pentaerythritol
CAS: 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy
CAS: 112-80-1	oleic acid, pure
CAS: 14808-60-7	Silicon Dioxide

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P5c FLAMMABLE LIQUIDS**

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

(Contd. on page 13)

PH



Safety Data Sheet according to GHS

Printing date 09.03.2026

Revision: 09.03.2026

Trade name: TEX-A-KOTE PRIMER 2800 WHITE

(Contd. of page 12)

· **National regulations:**

· **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H303 May be harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H333 May be harmful if inhaled.

H335 May cause respiratory irritation.

H350 May cause cancer.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H411 Toxic to aquatic life with long lasting effects.

R10 Flammable.

R20 Harmful by inhalation.

R20/21 Harmful by inhalation and in contact with skin.

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

R36/37/38 Irritating to eyes, respiratory system and skin.

R36/38 Irritating to eyes and skin.

R37 Irritating to respiratory system.

R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R60 May impair fertility.

R61 May cause harm to the unborn child.

R65 Harmful: may cause lung damage if swallowed.

· **Department issuing SDS:** Product safety department

· **Contact:** Mr. Ong

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 14)



Safety Data Sheet
according to GHS

Printing date 09.03.2026

Revision: 09.03.2026

Trade name: TEX-A-KOTE PRIMER 2800 WHITE

(Contd. of page 13)

VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 5: Acute toxicity – Category 5
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Carc. 1A: Carcinogenicity – Category 1A
Carc. 1B: Carcinogenicity – Category 1B
Carc. 2: Carcinogenicity – Category 2
Repr. 1A: Reproductive toxicity – Category 1A
Repr. 1B: Reproductive toxicity – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
· *** Data compared to the previous version altered.**

PH