



Safety Data Sheet
according to GHS

Printing date 10.03.2026

Revision: 10.03.2026

1 Identification


- **Product identifier**
- **Trade name:** TEX-A-KOTE SG 2800SG WHITE
- **Article number:** CWPACB-00026
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Company Name : Treasure Island Chemical Corp.
Company Address: Sitio Pilit Cabancalan, 6014 City of Mandaue, Cebu Philippines
Email Address: ddo@treasureisland.com.ph
Contact No.: +63 32 346 49 54-55
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:** During normal opening times: +63 32 232 05 13

2 Hazard identification

- **Classification of the substance or mixture**



Flam. Liq. 3 H226 Flammable liquid and vapour.




Muta. 1B H340 May cause genetic defects.
 Carc. 1B H350 May cause cancer.
 Repr. 1B H360 May damage fertility or the unborn child.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
 Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Acute Tox. 4 H332 Harmful if inhaled.
 Skin Irrit. 2 H315 Causes skin irritation.
 Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
 CWPACB-00026

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



R45-46-60-61: May cause cancer. May cause heritable genetic damage. May impair fertility. May cause harm to the unborn child.

(Contd. on page 2)



Safety Data Sheet
according to GHS

Printing date 10.03.2026

Revision: 10.03.2026

Trade name: TEX-A-KOTE SG 2800SG WHITE

(Contd. of page 1)



Xn; Harmful

R20: Harmful by inhalation.



Xi; Irritant

R38: Irritating to skin.

R10-52/53: Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

Label elements

Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:



T Toxic

Hazard-determining components of labelling:

Solvent naphtha (petroleum), light arom.

Naphtha (petroleum), heavy alkylate

di-(2-ethylhexyl) phthalate

Risk phrases:

45 May cause cancer.

46 May cause heritable genetic damage.

60 May impair fertility.

61 May cause harm to the unborn child.

10 Flammable.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

38 Irritating to skin.

20 Also harmful by inhalation.

Safety phrases:

53 Avoid exposure - obtain special instructions before use.

1/2 Keep locked up and out of the reach of children.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

(Contd. on page 3)



Safety Data Sheet
according to GHS

Printing date 10.03.2026

Revision: 10.03.2026

Trade name: **TEX-A-KOTE SG 2800SG WHITE**

· **vPvB:** Not applicable.

(Contd. of page 2)

3 Composition / information on ingredients

· **Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 64742-95-6	Solvent naphtha (petroleum), light arom. T Carc. Cat. 2, Muta. Cat. 2 R45-46 Xn R65 Flam. Liq. 3, H226 Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304 Acute Tox. 4, H332 Acute Tox. 5, H313	
CAS: 13463-67-7	titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] Carc. 2, H351 Acute Tox. 5, H333	
CAS: 1317-65-3	Calcium Carbonate Acute Tox. 4, H302 Acute Tox. 5, H333; Skin Corr. 3, H316; Serious eye damage/irritation – Category 2B, H320	
CAS: 95-63-6	1,2,4-trimethylbenzene Xn R20 Xi R36/37/38 N R51/53 R10 Flam. Liq. 3, H226 Aquatic Chronic 2, H411 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Acute Tox. 5, H303	
CAS: 471-34-1	Calcium Carbonate	
CAS: 117-81-7	di-(2-ethylhexyl) phthalate T Repr. Cat. 2 R60-61 Repr. 1B, H360	

(Contd. on page 4)



Safety Data Sheet
according to GHS

Printing date 10.03.2026

Revision: 10.03.2026

Trade name: TEX-A-KOTE SG 2800SG WHITE

(Contd. of page 3)

CAS: 67-64-1	<p>propanone</p> <p> Xi R36</p> <p> F R11</p> <p>R66-67</p> <p> Flam. Liq. 2, H225</p> <p> Eye Irrit. 2, H319; STOT SE 3, H336</p>	
CAS: 1330-20-7	<p>Dimethylbenzene</p> <p> Xn R20/21</p> <p> Xi R38</p> <p>R10</p> <p> Flam. Liq. 3, H226</p> <p> Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315</p> <p>Acute Tox. 5, H303</p>	
CAS: 108-67-8	<p>1,3,5-trimethylbenzene</p> <p> Xi R37</p> <p> N R51/53</p> <p>R10</p> <p> Flam. Liq. 3, H226</p> <p> Aquatic Chronic 2, H411</p> <p> STOT SE 3, H335</p> <p>Specific concentration limit: STOT SE 3; H335: C ≥ 25 %</p>	
CAS: 98-82-8	<p>isopropylbenzene</p> <p> Xn R65</p> <p> Xi R37</p> <p> N R51/53</p> <p>R10</p> <p> Flam. Liq. 3, H226</p> <p> Carc. 1B, H350; Asp. Tox. 1, H304</p> <p> Aquatic Chronic 2, H411</p> <p> Acute Tox. 4, H302; STOT SE 3, H335</p> <p>Acute Tox. 5, H333</p>	
CAS: 64741-65-7	<p>Naphtha (petroleum), heavy alkylate</p> <p> T Carc. Cat. 2, Muta. Cat. 2 R45-46</p> <p> Xn R65</p> <p> Flam. Liq. 3, H226</p> <p> Acute Tox. 3, H331</p> <p> Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304</p> <p>Acute Tox. 5, H313</p>	

· SVHC

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.

(Contd. on page 5)



Safety Data Sheet according to GHS

Printing date 10.03.2026

Revision: 10.03.2026

Trade name: TEX-A-KOTE SG 2800SG WHITE

(Contd. of page 4)

- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

(Contd. on page 6)



Safety Data Sheet
according to GHS

Printing date 10.03.2026

Revision: 10.03.2026

Trade name: TEX-A-KOTE SG 2800SG WHITE

(Contd. of page 5)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls / personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 95-63-6 1,2,4-trimethylbenzene

REL (USA) Long-term value: 125 mg/m³, 25 ppm

TLV (USA) Long-term value: 10 ppm

CAS: 471-34-1 Calcium Carbonate

PEL (USA) Long-term value: 15* 5** mg/m³
*total dust **respirable fraction

REL (USA) Long-term value: 10* 5** mg/m³
*total dust **respirable fraction

TLV (USA) TLV withdrawn

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

PEL (USA) Long-term value: 5 mg/m³

REL (USA) Short-term value: 10 mg/m³
Long-term value: 5 mg/m³
See Pocket Guide App. A

TLV (USA) Long-term value: 0.1 mg/m³
Skin, A3

CAS: 67-64-1 propanone

PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm

REL (USA) Long-term value: 590 mg/m³, 250 ppm

TLV (USA) Short-term value: 1187 mg/m³, 500 ppm
Long-term value: 594 mg/m³, 250 ppm
A4, BEI

CAS: 1330-20-7 Dimethylbenzene

PEL (USA) Long-term value: 435 mg/m³, 100 ppm

REL (USA) Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV (USA) Long-term value: 20 ppm
BEI, A4

CAS: 108-67-8 1,3,5-trimethylbenzene

REL (USA) Long-term value: 125 mg/m³, 25 ppm

(Contd. on page 7)



Safety Data Sheet
according to GHS

Printing date 10.03.2026

Revision: 10.03.2026

Trade name: TEX-A-KOTE SG 2800SG WHITE

(Contd. of page 6)

TLV (USA)	Long-term value: 10 ppm
CAS: 98-82-8 isopropylbenzene	
PEL (USA)	Long-term value: 245 mg/m ³ , 50 ppm Skin
REL (USA)	Long-term value: 245 mg/m ³ , 50 ppm Skin
TLV (USA)	Long-term value: 25 mg/m ³ , 5 ppm A3

· Ingredients with biological limit values:

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

BEI (USA)	5 µg/g creatinine Medium: - Time: Postshift Parameter: MEHP (population-based)
	20 µg/g creatinine Medium: - Time: Postshift Parameter: MEHHP (population-based)
	15 µg/g creatinine Medium: - Time: Postshift Parameter: MEOHP (population-based)
	25 µg/g creatinine Medium: - Time: Postshift Parameter: MECPP (population-based)

CAS: 67-64-1 propanone

BEI (USA)	25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----------	--

CAS: 1330-20-7 Dimethylbenzene

BEI (USA)	0.3 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

· Additional information: The lists valid during the making were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.

(Contd. on page 8)



Safety Data Sheet
according to GHS

Printing date 10.03.2026

Revision: 10.03.2026

Trade name: TEX-A-KOTE SG 2800SG WHITE

(Contd. of page 7)

Store protective clothing separately.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Fluid
Colour:	White
· Odour:	Characteristic
· Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	162 °C

· Flash point: 23 - 60 °C

· Flammability Flammable.

· Auto-ignition temperature: 450 °C

· Decomposition temperature: Not determined.

(Contd. on page 9)



Safety Data Sheet
according to GHS

Printing date 10.03.2026

Revision: 10.03.2026

Trade name: TEX-A-KOTE SG 2800SG WHITE

(Contd. of page 8)

· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	0.7 Vol %
Upper:	7.5 Vol %
· Vapour pressure:	Not determined.
· Density at 20 °C:	1.17 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	36.6 %
VOC (EC)	36.63 %
Solids content:	57.7 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· LD/LC50 values relevant for classification:		
CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6,800 mg/kg (rat)

(Contd. on page 10)



Safety Data Sheet
according to GHS

Printing date 10.03.2026

Revision: 10.03.2026

Trade name: TEX-A-KOTE SG 2800SG WHITE

(Contd. of page 9)

Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
CAS: 13463-67-7 titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]		
Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (rat)
CAS: 95-63-6 1,2,4-trimethylbenzene		
Oral	LD50	5,000 mg/kg (rat)
CAS: 471-34-1 Calcium Carbonate		
Oral	LD50	6,450 mg/kg (rat)
CAS: 117-81-7 di-(2-ethylhexyl) phthalate		
Oral	LD50	30,600 mg/kg (rat)
Dermal	LD50	25,000 mg/kg (rabbit)
CAS: 67-64-1 propanone		
Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
CAS: 1330-20-7 Dimethylbenzene		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
CAS: 98-82-8 isopropylbenzene		
Oral	LD50	1,400 mg/kg (rat)
Dermal	LD50	12,300 mg/kg (rabbit)
Inhalative	LC50/4 h	24.7 mg/l (mouse)
CAS: 64741-65-7 Naphtha (petroleum), heavy alkylate		
Oral	LD50	>6,000 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>7.8 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Carcinogenic.

The product can cause inheritable damage.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.

(Contd. on page 11)



Safety Data Sheet
according to GHS

Printing date 10.03.2026

Revision: 10.03.2026

Trade name: TEX-A-KOTE SG 2800SG WHITE


(Contd. of page 10)

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
*Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
 Do not allow product to reach ground water, water course or sewage system, even in small quantities.
 Danger to drinking water if even extremely small quantities leak into the ground.
 Harmful to aquatic organisms*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **ADR, IMDG, IATA** UNI263
- **UN proper shipping name**
- **ADR** 1263 PAINT
- **IMDG, IATA** PAINT
- **Transport hazard class(es)**
- **ADR, IMDG, IATA**
- 
- **Class** 3 Flammable liquids.
- **Label** 3
- **Packing group**
- **ADR, IMDG, IATA** III

(Contd. on page 12)



Safety Data Sheet
according to GHS

Printing date 10.03.2026

Revision: 10.03.2026

Trade name: TEX-A-KOTE SG 2800SG WHITE

(Contd. of page 11)

· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, S-E
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Philippines Inventory of Chemicals and Chemical Substances**

All ingredients are listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P5c** FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

CAS: 117-81-7 | di-(2-ethylhexyl) phthalate

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

PH

(Contd. on page 13)



Safety Data Sheet
according to GHS

Printing date 10.03.2026

Revision: 10.03.2026

Trade name: TEX-A-KOTE SG 2800SG WHITE

(Contd. of page 12)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 *Highly flammable liquid and vapour.*
 - H226 *Flammable liquid and vapour.*
 - H302 *Harmful if swallowed.*
 - H303 *May be harmful if swallowed.*
 - H304 *May be fatal if swallowed and enters airways.*
 - H312 *Harmful in contact with skin.*
 - H313 *May be harmful in contact with skin.*
 - H315 *Causes skin irritation.*
 - H316 *Causes mild skin irritation.*
 - H319 *Causes serious eye irritation.*
 - H320 *Causes eye irritation.*
 - H331 *Toxic if inhaled.*
 - H332 *Harmful if inhaled.*
 - H333 *May be harmful if inhaled.*
 - H335 *May cause respiratory irritation.*
 - H336 *May cause drowsiness or dizziness.*
 - H340 *May cause genetic defects.*
 - H350 *May cause cancer.*
 - H351 *Suspected of causing cancer.*
 - H360 *May damage fertility or the unborn child.*
 - H411 *Toxic to aquatic life with long lasting effects.*
-
- R10 *Flammable.*
 - R11 *Highly flammable.*
 - R20 *Harmful by inhalation.*
 - R20/21 *Harmful by inhalation and in contact with skin.*
 - R36 *Irritating to eyes.*
 - R36/37/38 *Irritating to eyes, respiratory system and skin.*
 - R37 *Irritating to respiratory system.*
 - R38 *Irritating to skin.*
 - R45 *May cause cancer.*
 - R46 *May cause heritable genetic damage.*
 - R51/53 *Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*
 - R60 *May impair fertility.*
 - R61 *May cause harm to the unborn child.*
 - R65 *Harmful: may cause lung damage if swallowed.*
 - R66 *Repeated exposure may cause skin dryness or cracking.*
 - R67 *Vapours may cause drowsiness and dizziness.*

· Department issuing SDS: Product safety department

· Contact: Mr. Ong

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

(Contd. on page 14)



Safety Data Sheet according to GHS

Printing date 10.03.2026

Revision: 10.03.2026

Trade name: TEX-A-KOTE SG 2800SG WHITE

(Contd. of page 13)

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

ELINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 5: Acute toxicity – Category 5

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Corr. 3: Skin corrosion/irritation – Category 3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Serious eye damage/irritation – Category 2B: Serious eye damage/eye irritation – Category 2B

Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1B: Carcinogenicity – Category 1B

Carc. 2: Carcinogenicity – Category 2

Repr. 1B: Reproductive toxicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**