



Safety Data Sheet
according to GHS

Printing date 27.04.2026

Revision: 27.04.2026

1 Identification

- **Product identifier**
- **Trade name:** **TEX-A-KOTE TINTING COLORS**
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Company Name : Treasure Island Chemical Corp.
Company Address: Sitio Pilit Cabancalan, 6014 City of Mandaue, Cebu Philippines
Email Address: ddo@treasureisland.com.ph
Contact No.: +63 32 346 49 54-55
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:** During normal opening times: +63 32 232 05 13

2 Hazard identification

- **Classification of the substance or mixture**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Muta. 1B H340 May cause genetic defects.
Carc. 1B H350 May cause cancer.
Repr. 1A H360 May damage fertility or the unborn child.
STOT RE 2 H373 May cause damage to the central nervous system through prolonged or repeated exposure.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.
Acute Tox. 5 H333 May be harmful if inhaled.
Skin Corr. 3 H316 Causes mild skin irritation.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



T; Toxic

R45-46-60-61: May cause cancer. May cause heritable genetic damage. May impair fertility. May cause harm to the unborn child.



Xn; Harmful

(Contd. on page 2)



Safety Data Sheet
according to GHS

Printing date 27.04.2026

Revision: 27.04.2026

Trade name: TEX-A-KOTE TINTING COLORS

(Contd. of page 1)

R65: Harmful: may cause lung damage if swallowed.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

Label elements

Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Code letter and hazard designation of product:



T Toxic

Hazard-determining components of labelling:

Solvent naphtha (petroleum), light arom.

Naphtha (petroleum), hydrodesulfurized heavy di-(2-ethylhexyl) phthalate

Risk phrases:

45 May cause cancer.

46 May cause heritable genetic damage.

60 May impair fertility.

61 May cause harm to the unborn child.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

Safety phrases:

53 Avoid exposure - obtain special instructions before use.

1/2 Keep locked up and out of the reach of children.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3 Composition / information on ingredients

Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



Safety Data Sheet
according to GHS

Printing date 27.04.2026

Revision: 27.04.2026

Trade name: TEX-A-KOTE TINTING COLORS

(Contd. of page 2)

Dangerous components:

CAS: 64742-95-6	Solvent naphtha (petroleum), light arom. T Carc. Cat. 2, Muta. Cat. 2 R45-46 Xn R65 Flam. Liq. 3, H226 Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304 Acute Tox. 4, H332 Acute Tox. 5, H313	
CAS: 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy T Carc. Cat. 2, Muta. Cat. 2 R45-46 Xn R48/20-65 Flam. Liq. 3, H226 Muta. 1B, H340; Carc. 1B, H350; STOT RE 1, H372; Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336	
CAS: 95-63-6	1,2,4-trimethylbenzene Xn R20 Xi R36/37/38 N R51/53 R10 Flam. Liq. 3, H226 Aquatic Chronic 2, H411 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Acute Tox. 5, H303	
	Carbon black Expl. 1.4, H204 Flam. Liq. 3, H226; Self-react. C, H242 Muta. 1B, H340; Carc. 1B, H350; Repr. 1A, H360 Skin Irrit. 2, H315; Skin Sens. 1B, H317 Acute Tox. 5, H313; Aquatic Acute 3, H402; Aquatic Chronic 4, H413	
CAS: 117-81-7	di-(2-ethylhexyl) phthalate T Repr. Cat. 2 R60-61 Repr. 1B, H360	
CAS: 64742-94-5	Solvent naphtha (petroleum), heavy arom. Xn R65 Asp. Tox. 1, H304	

(Contd. on page 4)



Safety Data Sheet
according to GHS

Printing date 27.04.2026

Revision: 27.04.2026

Trade name: TEX-A-KOTE TINTING COLORS

(Contd. of page 3)

CAS: 67-64-1	<p>propanone</p> <p> Xi R36</p> <p> F R11</p> <p>R66-67</p> <p> Flam. Liq. 2, H225</p> <p> Eye Irrit. 2, H319; STOT SE 3, H336</p>	
CAS: 108-67-8	<p>1,3,5-trimethylbenzene</p> <p> Xi R37</p> <p> N R51/53</p> <p>R10</p> <p> Flam. Liq. 3, H226</p> <p> Aquatic Chronic 2, H411</p> <p> STOT SE 3, H335</p> <p>Specific concentration limit: STOT SE 3; H335: C ≥ 25 %</p>	
CAS: 98-82-8	<p>isopropylbenzene</p> <p> Xn R65</p> <p> Xi R37</p> <p> N R51/53</p> <p>R10</p> <p> Flam. Liq. 3, H226</p> <p> Carc. 1B, H350; Asp. Tox. 1, H304</p> <p> Aquatic Chronic 2, H411</p> <p> Acute Tox. 4, H302; STOT SE 3, H335</p> <p>Acute Tox. 5, H333</p>	
CAS: 123-86-4	<p>Butyl Ethanoate</p> <p> Xn R22</p> <p> Xi R36/38</p> <p> F+ R12</p> <p>R67</p> <p> Flam. Liq. 3, H226</p> <p> Acute Tox. 3, H301</p> <p> Skin Irrit. 2, H315; Serious eye damage/irritation – Category 2A, H319; STOT SE 3, H336</p>	

· SVHC

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 5)



Safety Data Sheet according to GHS

Printing date 27.04.2026

Revision: 27.04.2026

Trade name: TEX-A-KOTE TINTING COLORS

(Contd. of page 4)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls / personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.

(Contd. on page 6)



Safety Data Sheet
according to GHS

Printing date 27.04.2026

Revision: 27.04.2026

Trade name: TEX-A-KOTE TINTING COLORS

(Contd. of page 5)

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 95-63-6 1,2,4-trimethylbenzene

REL (USA) Long-term value: 125 mg/m³, 25 ppm

TLV (USA) Long-term value: 10 ppm

Carbon black

PEL (USA) Long-term value: 3.5 mg/m³

REL (USA) Long-term value: 3.5* mg/m³
*0.1 in presence of PAHs; See Pocket Guide Apps.A+C

TLV (USA) Long-term value: 3* mg/m³
*inhalable fraction, A3

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

PEL (USA) Long-term value: 5 mg/m³

REL (USA) Short-term value: 10 mg/m³
Long-term value: 5 mg/m³
See Pocket Guide App. A

TLV (USA) Long-term value: 0.1 mg/m³
Skin, A3

CAS: 67-64-1 propanone

PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm

REL (USA) Long-term value: 590 mg/m³, 250 ppm

TLV (USA) Short-term value: 1187 mg/m³, 500 ppm
Long-term value: 594 mg/m³, 250 ppm
A4, BEI

CAS: 108-67-8 1,3,5-trimethylbenzene

REL (USA) Long-term value: 125 mg/m³, 25 ppm

TLV (USA) Long-term value: 10 ppm

CAS: 98-82-8 isopropylbenzene

PEL (USA) Long-term value: 245 mg/m³, 50 ppm
Skin

REL (USA) Long-term value: 245 mg/m³, 50 ppm
Skin

TLV (USA) Long-term value: 25 mg/m³, 5 ppm
A3

CAS: 123-86-4 Butyl Ethanoate

PEL (USA) Long-term value: 710 mg/m³, 150 ppm

REL (USA) Short-term value: 950 mg/m³, 200 ppm
Long-term value: 710 mg/m³, 150 ppm

TLV (USA) Short-term value: 712 mg/m³, 150 ppm
Long-term value: 238 mg/m³, 50 ppm

(Contd. on page 7)



Safety Data Sheet
according to GHS

Printing date 27.04.2026

Revision: 27.04.2026

Trade name: TEX-A-KOTE TINTING COLORS

(Contd. of page 6)

Ingredients with biological limit values:

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

BEI (USA)	5 µg/g creatinine Medium: - Time: Postshift Parameter: MEHP (population-based)
	20 µg/g creatinine Medium: - Time: Postshift Parameter: MEHHP (population-based)
	15 µg/g creatinine Medium: - Time: Postshift Parameter: MEOHP (population-based)
	25 µg/g creatinine Medium: - Time: Postshift Parameter: MECPP (population-based)

CAS: 67-64-1 propanone

BEI (USA)	25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----------	--

Additional information: The lists valid during the making were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 8)



Safety Data Sheet
according to GHS

Printing date 27.04.2026

Revision: 27.04.2026

Trade name: TEX-A-KOTE TINTING COLORS

(Contd. of page 7)

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	162 °C

· **Flash point:** Not applicable.

· **Flammability** Not applicable.

· **Auto-ignition temperature:** 485 °C

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Not determined.

· **Explosion limits:**

· Lower:	1.1 Vol %
· Upper:	7 Vol %

· **Vapour pressure:** Not determined.

· Density at 20 °C:	0.94 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.

(Contd. on page 9)



Safety Data Sheet
according to GHS

Printing date 27.04.2026

Revision: 27.04.2026

Trade name: TEX-A-KOTE TINTING COLORS

(Contd. of page 8)

· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	50.7 %
Water:	1.3 %
VOC (EC)	50.74 %
Solids content:	40.7 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

· LD/LC50 values relevant for classification:		
CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
CAS: 95-63-6 1,2,4-trimethylbenzene		
Oral	LD50	5,000 mg/kg (rat)
Carbon black		
Oral	LD50	10,000 mg/kg (rat)
CAS: 117-81-7 di-(2-ethylhexyl) phthalate		
Oral	LD50	30,600 mg/kg (rat)
Dermal	LD50	25,000 mg/kg (rabbit)

(Contd. on page 10)



Safety Data Sheet
according to GHS

Printing date 27.04.2026

Revision: 27.04.2026

Trade name: TEX-A-KOTE TINTING COLORS

(Contd. of page 9)

CAS: 67-64-1 propanone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)

CAS: 98-82-8 isopropylbenzene

Oral	LD50	1,400 mg/kg (rat)
Dermal	LD50	12,300 mg/kg (rabbit)
Inhalative	LC50/4 h	24.7 mg/l (mouse)

- **Primary irritant effect:**
- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

- Carcinogenic.
- The product can cause inheritable damage.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 11)



Safety Data Sheet
according to GHS

Printing date 27.04.2026


Revision: 27.04.2026

Trade name: TEX-A-KOTE TINTING COLORS

(Contd. of page 10)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number · ADR, IMDG, IATA	UNI263
· UN proper shipping name · ADR · IMDG, IATA	1263 PAINT PAINT
· Transport hazard class(es) · ADR, IMDG, IATA	
	
· Class · Label	3 Flammable liquids. 3
· Packing group · ADR, IMDG, IATA	I
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · Hazard identification number (Kemler code): · EMS Number:	Warning: Flammable liquids. 30 F-E, <u>S-E</u>
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	500 ml Code: E3 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 300 ml
· Transport category	1
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	500 ml Code: E3 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 300 ml

(Contd. on page 12)



Safety Data Sheet
according to GHS

Printing date 27.04.2026

Revision: 27.04.2026

Trade name: TEX-A-KOTE TINTING COLORS

(Contd. of page 11)

· UN "Model Regulation": UN 1263 PAINT, 3, I

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Philippines Inventory of Chemicals and Chemical Substances**

All ingredients are listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P5c FLAMMABLE LIQUIDS**

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

CAS: 117-81-7 | di-(2-ethylhexyl) phthalate

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H204 Fire or projection hazard.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H242 Heating may cause a fire.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H303 May be harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H313 May be harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H333 May be harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H340 May cause genetic defects.

(Contd. on page 13)



Safety Data Sheet
according to GHS

Printing date 27.04.2026

Revision: 27.04.2026

Trade name: TEX-A-KOTE TINTING COLORS

(Contd. of page 12)

- H350 May cause cancer.
- H360 May damage fertility or the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H402 Harmful to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.
- R10 Flammable.
- R11 Highly flammable.
- R12 Extremely flammable.
- R20 Harmful by inhalation.
- R22 Harmful if swallowed.
- R36 Irritating to eyes.
- R36/37/38 Irritating to eyes, respiratory system and skin.
- R36/38 Irritating to eyes and skin.
- R37 Irritating to respiratory system.
- R45 May cause cancer.
- R46 May cause heritable genetic damage.
- R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R60 May impair fertility.
- R61 May cause harm to the unborn child.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

· **Department issuing SDS:** Product safety department

· **Contact:** Mr. Ong

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organisation
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- SVHC: Substances of Very High Concern
- vPvB: very Persistent and very Bioaccumulative
- Expl. 1.4: Explosives – Division 1.4
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Self-react. C: Self-reactive substances and mixtures – Type C/D
- Acute Tox. 3: Acute toxicity – Category 3
- Acute Tox. 5: Acute toxicity – Category 5
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Skin Corr. 3: Skin corrosion/irritation – Category 3
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

(Contd. on page 14)



Safety Data Sheet
according to GHS

Printing date 27.04.2026

Revision: 27.04.2026

Trade name: TEX-A-KOTE TINTING COLORS

(Contd. of page 13)

Serious eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
Muta. 1B: Germ cell mutagenicity – Category 1B
Carc. 1B: Carcinogenicity – Category 1B
Repr. 1A: Reproductive toxicity – Category 1A
Repr. 1B: Reproductive toxicity – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4
*** Data compared to the previous version altered.**

PH