



STAR ELASTOMER

DESCRIPTION:

STAR ELASTOMER is a decorative self-priming, waterproof coating for interior and exterior concrete surfaces. Dries to a Satin Finish with good weathering, resistant against destructive effect of UV from sunlight, low odor, lead free and environmentally friendly.

USE:

Finish coat for exterior and interior vertical or sloping masonry surfaces, such as, concrete walls, structure, roof tile, brick, concrete casting, facade, canopy, ledge, and in some case, may be even applied to properly primed wood and metal. Not recommended for horizontal concrete surfaces that hold still or pooled water.

COLOR:

White and variety of 30 readily available shades (refer to chart). Our series #2 Fan Deck offer additional 240 shades which can be availed thru our dispensing machine outlets.


FINISH:

Satin

APPLICATION:



Brush



Roller



Spray

REDUCTION:

FOR BRUSH & ROLLER APPLICATION

Apply as is or if necessary, add ¼ liter of clean water to a gallon of paint.

FOR SPRAY APPLICATION

Add approximately ¼ to ½ liter of clean water to a gallon of paint.

Apply two coats for optimum performance.

DRYING TIME:

Dry to recoat : 2-4 hours

SURFACE PREPARATION:

Remove oils, dirt, dust, laitance, and other contaminants.

**Aged concrete for 28 days*

A. For New Concrete:

Treat surface with Island 400CN Concrete Neutralizer in plain water; 1 part vol. plain water. Refer to Island 400CN Concrete Neutralizer TDS for more info.

B. For Old Chalky Surfaces:

Sand with # 60 grit sandpaper, wash down with high pressured water, dry up surface, now ready for coating.

COVERAGE:

20 – 25 sq. m. / 4L depending on surface roughness.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.

**PACKAGING:**

4 L plastic container

STORAGE & DISPOSAL:

Keep container tightly close when not in use. Do not store above 35 ° C. Disposal must be made according to government regulations.

SHELF LIFE:

3 years in unopened container

LABEL ELEMENTS:

Warning: Causes skin irritation. May be harmful if inhaled. Harmful to aquatic life with long lasting effects.

Contains: N-Butyl Acrylate

Precaution: Keep out of the reach of children. Avoid contact with skin. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label. Dispose of this material and its container to hazardous or special waste collection point.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.

