Island®
PREMIUM PAINTS
Does it Better

Technical Data Sheet

COLORQuick

DESCRIPTION:

COLORQuick Enamel is an alkyd-based coating especially formulated to provide good gloss, and excellent adhesion over wood and metal surfaces.

USE:

As a general-purpose finishing coat on wood and metal surfaces.

COLOR/APPEARANCE:

900 White
30 Pre-mixed Color *(Refer to color chart)*

FINISH:

Gloss

APPLICATION:



REDUCTION:

Mayon Paint Thinner

Brush & Roller: use as is or about 5% reduction
Spray : approximately 10-15% reduction

SURFACE PREPARATION:

For New Wood Substrate:
Sand the substrate using sand paper grit #120 to get rid of any imperfections. Surface must be dried and cleaned, free from dirt, dust and other contaminants that may inhibit bonding.

For Old Wood Substrate:
Scrape all loosely existing paint using scraper or mechanical sander. Sand with sand paper grit #120 to roughen the surface for better adhesion. Surface must be dried and cleaned. Free from dirt, dust, and other contaminants that may be inhibit bonding. Oil, grease and other chemical contaminants must be removed by solvent wiping preferably using Mayon Lacquer Thinner.

For New Metal Substrate
Light sanding using sand paper grit #100 or 120. Surface must be wiped with Mayon Lacquer Thinner for solvent wiping to eliminate other contaminants.

For Old Metal Substrate
Old paint must be sanded off. Rusted portions must be sanded using sand paper grit #100/120 or steel brushed. Surface must be dried, free of dirt, dust, rust, & other contaminants prior to application.

RECOMMENDED PRIMER:

Wood: Island Wood Primer and Sealer 801 White
Metal: Island Metal Primer 700 Red Oxide
Island Metal Primer 730 Red
Island Metal Primer 7411 Zinc Yellow
Island Epoxy Primers *(For Old & Rusted Metal Substrates)*

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests; neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislation are observed.

Rev. 0

ISO 9001 CERTIFIED
Treasure Island
CHEMICAL CORPORATION

PRIMA SUPER KINIS SKIM COAT WHITE
MAYON CONCRETO BOND
EPOXSEAL EQUIP TILE ADHESIVE

HEAD OFFICE
CEBU
No. 2 3rd Avenue,
S. Osmeña Boulevard,
North Reclamation Area,
Cebu City, Philippines

Tel: (032) 232-0513 to 17
Fax: (032) 232-0518

LUZON
CAVITE
1530 ME,
Barangay Toclong
Kawit, Cavite

Tel: (046) 434-2229

VISAYAS
CEBU SHOWROOM
A.S Fortuna Street,
Mandaue City

Tel: (032) 345-2139
Fax: (032) 345-2130

MINDANAO
DAVAO
No.8 NR
El Rio St. Subdivision
Bacaca Road, Davao City

Tel: (082) 224-3409
Fax: (082) 222-8476

EMAIL
sales@islandpaints.com

WEBSITE
www.islandpaints.com

Island® PREMIUM PAINTS
Does it Better

Technical Data Sheet

APPLICATION GUIDELINES:

For Wood Substrate

Apply Island Wood Primer and Sealer 801 White and allow it to dry overnight. Apply Island Glazing Putty 803 White using a putty knife to cover joints and nail heads, then allow it to dry for four (4) hours before applying Island Wood Primer and Sealer to the areas covered with putty. Let it dry overnight, then apply two (2) coats of ColorQuick paint by roller, brush, or spray. Allow 24 hours before recoating.

For Metal Substrate

Prime the surface with Island Metal Primer 700 Red Oxide, 730 Red, 7411 Zinc Yellow, or Island Epoxy Primers for old and rusted metal substrates. Allow the primer to dry overnight. Apply ColorQuick paint to the properly primed surface by roller, brush, or spray. If a second coat is necessary, allow 24 hours to dry before recoating.

DRYING TIME:

Dry to recoat: Allow 12 – 24 hours

THEORETICAL COVERAGE:

Approximately 20 – 25 sq. m. per gallon @ 35 – 40 microns DFT depending on surface profile

PACKAGING:

1/4L, 1L, and 4L lithographed round can
16L lithographed round can *(Available for CQ 900 White only)*

SHELF LIFE:

2 years or 5 years in unopened container depending on color *(Refer to Shelf Life Masterlist)*
NOTE: High humidity might reduce the shelf-life of the product.

STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 ^{0}C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

LABEL ELEMENTS:

Danger: Flammable liquid and vapor. May cause genetic defects. May cause cancer. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effect. Causes skin and serious eye irritation. May cause respiratory irritation and drowsiness or dizziness. May be harmful if inhaled.

Contains: Kerosene, Naphtha (petroleum), hydrodesulfurized heavy, solvent naphtha (petroleum), light arom.

Precaution. Avoid exposure – obtain special instructions before use. Keep locked up and out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests; neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislation are observed.

Rev. 0

ISO 9001 CERTIFIED
Treasure Island CHEMICAL CORPORATION

PRIMA · SUPER KINIS SKIN COAT WHITE · MAYON · CONCRETO BOND · EPOXSEAL · EQUIP TILE ADHESIVE

HEAD OFFICE
CEBU
No. 2 3rd Avenue,
S. Osmeña Boulevard,
North Reclamation Area,
Cebu City, Philippines
Tel: (032) 232-0513 to 17
Fax: (032) 232-0518

LUZON
CAVITE
1530 ME,
Barangay Toclong
Kawit, Cavite
Tel: (046) 434-2229

VISAYAS
CEBU SHOWROOM
A.S Fortuna Street,
Mandaue City
Tel: (032) 345-2139
Fax: (032) 345-2130

MINDANAO
DAVAO
No.8 NR
El Rio St. Subdivision
Bacaca Road, Davao City
Tel: (082) 224-3409
Fax: (082) 222-8476

EMAIL
sales@islandpaints.com

WEBSITE
www.islandpaints.com