



## INDUSTRIAL SPORT COURT COATING

### DESCRIPTION:

**INDUSTRIAL SPORT COURT COATING** is a single-packed synthetic rubber solvent-based coating.

### USE:

Industrial Sport Court Coating is intended for indoor and outdoor concrete floors, including basketball, lawn tennis, badminton, gymnasium, pickleball, and roof decks.

### FEATURES:

- Fast dry
- Hardwearing
- Non slippery
- Excellent adhesion & impact resistance
- Easy to clean


### COLOR/APPEARANCE:

Custom colors available upon request only

### FINISH:

Semi-Flat

### APPLICATION:



Brush

Roller

### REDUCTION:

Sport Court Reducer

*Up to approximately 10% reduction, based on volume*

### SURFACE PREPARATION:

Adhesion barriers such as dust, dirt and oil must be removed. Dry the surface thoroughly before painting. Seal the surface using Epoxy FC 1805FC Sealer and allow it to dry overnight.

### RECOMMENDED PRIMER:

Sealer: Epoxy FC 1805FC Sealer Coat

Primer: Island Epoxy Primers – 100 White, 130 Red Oxide, 160 Gray, and 180 Black

### APPLICATION GUIDELINES:

#### For Smooth Surfaces:

Sand the sealed surface with #240 or #400 sandpaper, then apply with Epoxy Primer and let dry overnight. Sand with #400 sandpaper, then apply two coats of Industrial Sport Court Coating paint.

#### For Dented Surfaces:

After sealing, apply Epoxseal Putty and let it dry overnight. Sand with #400 sandpaper. Recoat with Epoxy FC 1805FC Sealer Coat and let it dry overnight. Sand with #240 or #400 sandpaper, then apply Epoxy Primer and let dry overnight. Sand with #400 sandpaper, then apply two coats of Industrial Sport Court Coating.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests; neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislation are observed.

Rev. 0



ISO 9001 CERTIFIED

**Treasure Island**  
CHEMICAL CORPORATION

PRIMA



EPOXSEAL

**SUPER KINIS**  
SKIN COAT WHITE



EQUIP  
TILE ADHESIVE

#### HEAD OFFICE

CEBU  
No. 2 3rd Avenue,  
S. Osmeña Boulevard,  
North Reclamation Area,  
Cebu City, Philippines

Tel: (032) 232-0513 to 17  
Fax: (032) 232-0518

#### LUZON

CAVITE  
1530 ME,  
Barangay Toclong  
Kawit, Cavite

Tel: (046) 434-2229

#### VISAYAS

CEBU SHOWROOM  
A.S Fortuna Street,  
Mandaue City

Tel: (032) 345-2139  
Fax: (032) 345-2130

#### MINDANAO

DAVAO  
No.8 NR  
El Rio St. Subdivision  
Bacaca Road, Davao City

Tel: (082) 224-3409  
Fax: (082) 222-8476

#### EMAIL

sales@islandpaints.com

#### WEBSITE

www.islandpaints.com



## DRYING TIME:

Dry hard: 4 hours

*NOTE: Allow the paint to dry for at least 24 hours or overnight to ensure proper adhesion and full curing of the surface. This will help achieve optimal results and long-lasting durability.*

## THEORETICAL COVERAGE:

Approximately 20–25 sq. m. per gallon @ 50-70 microns DFT depending on surface profile

## PACKAGING:

4L lithographed round can

## SHELF LIFE:

1 year in unopened container

*NOTE: High humidity might reduce the shelf-life of the product.*

## STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

## LABEL ELEMENTS:



**Danger:** Flammable liquid and vapour. May cause genetic defects. May cause cancer. Toxic to aquatic life with long lasting effects. Harmful if inhaled. Causes skin irritation. May be harmful in contact with skin.

**Contains:** Solvent Naphtha (Petroleum), Light Arom, Dimethylbenzene

**Precaution:** Avoid exposure-obtain special instructions before use. Keep locked up and out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable protective clothing, gloves, and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests; neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislation are observed.

Rev. 0



ISO 9001 CERTIFIED

**Treasure Island**  
CHEMICAL CORPORATION

PRIMA



EPOXSEAL

**SUPER KINIS**  
SKIN COAT WHITE



**EQUIP**  
TILE ADHESIVE

### HEAD OFFICE

CEBU  
No. 2 3rd Avenue,  
S. Osmeña Boulevard,  
North Reclamation Area,  
Cebu City, Philippines

Tel: (032) 232-0513 to 17  
Fax: (032) 232-0518

### LUZON

CAVITE  
1530 ME,  
Barangay Toclong  
Kawit, Cavite

Tel: (046) 434-2229

### VISAYAS

CEBU SHOWROOM  
A.S Fortuna Street,  
Mandaue City

Tel: (032) 345-2139  
Fax: (032) 345-2130

### MINDANAO

DAVAO  
No.8 NR  
El Rio St. Subdivision  
Bacaca Road, Davao City

Tel: (082) 224-3409  
Fax: (082) 222-8476

### EMAIL

[sales@islandpaints.com](mailto:sales@islandpaints.com)

### WEBSITE

[www.islandpaints.com](http://www.islandpaints.com)