



ISLAND FLEXIGEL

DESCRIPTION:

ISLAND FLEXIGEL is a self-priming, premium grade and flexible water-proof exterior coating based on aqueous rubber-like polymer.

USE:

Recommended to be used as water-proofing paint for concrete walls.

FEATURES:

- Exceptional water resistance
- Unmatched flexibility
- Excellent bonding property
- Good outdoor durability
- Can seal hairline cracks and crevices of concrete surfaces

COLOR/APPEARANCE:

White

May be tinted with Island Latex Tinting Color to achieve desired color


FINISH:

Low Sheen

APPLICATION:



Brush



Roller



Spray

REDUCTION:

The product is supplied ready to use but it may be reduced with ¼ - ½ liter of clean water per gallon of paint for good brushability and leveling.

RECOMMENDED MIXING RATIO:

For Spray: Add about 1L of clean water for every gallon of paint.

SURFACE PREPARATION:

Remove oils, dirt, dust, laitance, and other contaminants.

A. For New Concrete:

Treat the surface with Island 400CN Concrete Neutralizer diluted in plain water (1 part by volume plain water). Refer to the Island 400CN Concrete Neutralizer TDS for more information. Alternatively, allow the concrete to age for 28 days before use.

B. For Old Chalky Surfaces:

Sand the surface with #60 grit sandpaper, wash thoroughly with high-pressure water, and allow the surface to dry completely. The surface is now ready for coating.

DRYING TIME:

Dry to hard: 2-4 hours

Dry to recoat: 4-6 hours

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests; neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislation are observed.

Rev. 0



ISO 9001 CERTIFIED

Treasure Island
CHEMICAL CORPORATION

PRIMA



EPOX SEAL

SUPER KINIS
SKIN COAT WHITE



EQUIP
TILE ADHESIVE

HEAD OFFICE

CEBU
No. 2 3rd Avenue,
S. Osmeña Boulevard,
North Reclamation Area,
Cebu City, Philippines

Tel: (032) 232-0513 to 17
Fax: (032) 232-0518

LUZON

CAVITE
1530 ME,
Barangay Toclong
Kawit, Cavite

Tel: (046) 434-2229

VISAYAS

CEBU SHOWROOM
A.S Fortuna Street,
Mandaue City

Tel: (032) 345-2139
Fax: (032) 345-2130

MINDANAO

DAVAO
No.8 NR
El Rio St. Subdivision
Bacaca Road, Davao City

Tel: (082) 224-3409
Fax: (082) 222-8476

EMAIL

sales@islandpaints.com

WEBSITE

www.islandpaints.com



THEORETICAL COVERAGE:

Approximately 25 – 30 sq. m. per gallon per coat

PACKAGING:

4L plastic container

SHELF LIFE:

2 years in unopened container

NOTE: High humidity might reduce the shelf-life of the product.

STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

LABEL ELEMENTS:



Warning: May cause an allergic skin reaction. May be harmful if swallowed. May be harmful if inhaled. Toxic to aquatic life.

Contains: Reaction Mass of: 5-Chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Precaution: Keep out of the reach of children. Avoid contact with skin. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests; neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislation are observed.

Rev. 0



ISO 9001 CERTIFIED

Treasure Island
CHEMICAL CORPORATION



HEAD OFFICE

CEBU
No. 2 3rd Avenue,
S. Osmeña Boulevard,
North Reclamation Area,
Cebu City, Philippines

Tel: (032) 232-0513 to 17
Fax: (032) 232-0518

LUZON

CAVITE
1530 ME,
Barangay Toclong
Kawit, Cavite

Tel: (046) 434-2229

VISAYAS

CEBU SHOWROOM
A.S Fortuna Street,
Mandaue City

Tel: (032) 345-2139
Fax: (032) 345-2130

MINDANAO

DAVAO
No.8 NR
El Rio St. Subdivision
Bacaca Road, Davao City

Tel: (082) 224-3409
Fax: (082) 222-8476

EMAIL

sales@islandpaints.com

WEBSITE

www.islandpaints.com