



### TEX-A-KOTE 2800C CAST

#### DESCRIPTION:

TEX-A-KOTE 2800C CAST is a premium patching material in heavy paste-form prepared from combination of finely ground pigments in a solvent-based acrylic resin.

#### USE:

For patching, filling, and leveling minor surface imperfections in concrete and masonry substrates including hairline cracks and small dents to restore surface continuity and achieve a smooth, even profile prior to application of finish coatings.

#### COLOR/APPEARANCE:

Off White

#### FINISH:

Flat  
Textured

#### APPLICATION:



Putty Knife



Masonry Float



Mortar Splatter Gun



Trowel



Notched Trowel

#### REDUCTION:

Tex-a-Kote 2802 Reducer

#### SURFACE PREPARATION:

Remove loosely adherent mortar, dirt, dust, or any adhesion barrier.

#### APPLICATION GUIDELINES:

**For Patching:** Clean the repair area thoroughly, removing all loose material, dust, grease, and contaminants. Ensure the surface is sound and dry. Using a putty knife or trowel, press the material firmly into the defect, working it in to ensure full contact and to remove air pockets. Slightly overfill the area to allow for shrinkage. Smooth and feather the edges to blend with the surrounding surface. For deeper repairs, apply in thin layers, allowing each layer to dry before applying the next. Allow the final repair to dry completely before sanding, priming, or applying finish coatings.

**For Textured effect:** A textured effect is achieved by reducing Tex-a-Kote 2800C Cast with Tex-a-Kote 2802 Reducer and spraying the mixture using a splatter gun. The variation in texture size depends on the spray consistency or percent reduction, air pressure, distance of the gun from the surface, and the amount of cast splattered onto the substrate. About 5–10 minutes after spraying, flatten the texture with a plain metal roller wetted with Tex-a-Kote 2802 Reducer.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests; neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislation are observed.

Rev. 0



ISO 9001 CERTIFIED  
**Treasure Island**  
CHEMICAL CORPORATION

PRIMA



EPOXSEAL

**SUPER KINIS**  
SKIN COAT WHITE



EQUIP  
TILE ADHESIVE

#### HEAD OFFICE

CEBU  
No. 2 3rd Avenue,  
S. Osmeña Boulevard,  
North Reclamation Area,  
Cebu City, Philippines

Tel: (032) 232-0513 to 17  
Fax: (032) 232-0518

#### LUZON

CAVITE  
1530 ME,  
Barangay Toclong  
Kawit, Cavite

Tel: (046) 434-2229

#### VISAYAS

CEBU SHOWROOM  
A.S Fortuna Street,  
Mandaue City

Tel: (032) 345-2139  
Fax: (032) 345-2130

#### MINDANAO

DAVAO  
No.8 NR  
El Rio St. Subdivision  
Bacaca Road, Davao City

Tel: (082) 224-3409  
Fax: (082) 222-8476

#### EMAIL

[sales@islandpaints.com](mailto:sales@islandpaints.com)

#### WEBSITE

[www.islandpaints.com](http://www.islandpaints.com)



### Finishing Preparations

After curing:

- Lightly sand if required to achieve uniform surface profile.
- Remove all sanding dust and debris.
- Apply primer and finish coats per system specification.

### DRYING TIME:

Dry to recoat: 2 – 4 hours depending on desired film thickness, temperature of the applied area and weather condition.

*NOTE: Allow patched areas to dry completely before sanding, priming, or applying finish coats.*

### RECOMMENDED SUBSEQUENT COAT:

Primer: Tex-a-Kote Primer 2800 White

Topcoat: Tex-a-Kote Finishes

### THEORETICAL COVERAGE:

**For Patching:** Depending on the depth and condition of the imperfections.

**For Textured Finish:** Depending on the texture size.

### PACKAGING:

1L and 4L lithographed round can

### SHELF LIFE:

1 year in unopened container

*NOTE: High humidity might reduce the shelf-life of the product.*

### STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

### LABEL ELEMENTS:



**Danger:** Highly flammable liquid and vapour. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. Causes skin and serious eye irritation. May be harmful if inhaled. Harmful to aquatic life with long lasting effects.

**Precaution:** Keep out of the reach of children. Handle and open container with care. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. If swallowed, seek medical advice immediately and show this container or label.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests; neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislation are observed.

Rev. 0



ISO 9001 CERTIFIED

**Treasure Island**  
CHEMICAL CORPORATION



#### HEAD OFFICE

CEBU  
No. 2 3rd Avenue,  
S. Osmeña Boulevard,  
North Reclamation Area,  
Cebu City, Philippines

Tel: (032) 232-0513 to 17  
Fax: (032) 232-0518

#### LUZON

CAVITE  
1530 ME,  
Barangay Toclong  
Kawit, Cavite

Tel: (046) 434-2229

#### VISAYAS

CEBU SHOWROOM  
A.S Fortuna Street,  
Mandaue City

Tel: (032) 345-2139  
Fax: (032) 345-2130

#### MINDANAO

DAVAO  
No.8 NR  
El Rio St. Subdivision  
Bacaca Road, Davao City

Tel: (082) 224-3409  
Fax: (082) 222-8476

#### EMAIL

sales@islandpaints.com

#### WEBSITE

www.islandpaints.com