



TEX-A-KOTE 2800C CAST

DESCRIPTION:

TEX-A-KOTE 2800C CAST is a premium patching material in heavy paste-form prepared from combination of finely ground pigments in an acrylic resin.

USE:

For textured finishes of Tex-a-kote Coatings.

COLOR:

Dirty white

FINISH:

Flat, Textured

APPLICATION TOOLS:



Spray

A textured effect is attained by reducing Tex-a-kote 2800C Cast with Tex-a-kote Reducer and sprayed using a splatter gun. The varying size of texture depend on the spray consistency or percent reduction, air pressure, distance of gun to surface and amount of cast splattered to the substrate. Then in about 5-10 minutes after spraying, flatten the texture with plain metal roller wetted with Tex-a-kote Reducer.

REDUCTION:

Tex-a-kote 2802 Reducer

DRYING TIME:

Dry to recoat: 2-4 hours depending on desired film thickness, temperature of the applied area and weather condition.

SURFACE PREPARATION:

Remove loosely adherent mortar, dirt, dust, or any adhesion barrier.

SUBSEQUENT COAT:

1. Primer: Tex-a-kote Primer 2800 White
2. Topcoat: Tex-a-kote Finishes

COVERAGE:

Depending on the depth and condition of dents.

PACKAGING:

1 L and 4 L lithographed round can

SHELF LIFE:

1 year in unopened container

STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



LABEL ELEMENTS:



Danger. Highly flammable liquid and vapour. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. Causes skin and serious eye irritation. May be harmful if inhaled. Harmful to aquatic life with long lasting effects.

Contains: di-(2-ethylhexyl)phthalate

Precaution: Avoid exposure – obtain special instructions before use. Keep locked up and out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.