

Printing date 20.12.2022 Revision: 15.03.2022

1 Identification

- · Product identifier
- · Trade name: TEX-A-KOTE 2801 TOPCOAT CLEAR
- · Article number: CWPACB-03780
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Treasure Island Industrial Corp. No.2, 3rd Ave. S. Osmena Blvd. North Reclamation Area Ceby City 6000

Cebu City 6000

PHILIPPINES

doo@treasureisland.com.ph

- · Further information obtainable from: Product safety department
- Emergency telephone number: During normal opening times: +63 32 232 05 13

2 Hazard identification

· Classification of the substance or mixture



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Acute Tox. 5 H333 May be harmful if inhaled. Aquatic Acute 2 H401 Toxic to aquatic life.

CWPACB-03780

(Contd. on page 2)



Printing date 20.12.2022 Revision: 15.03.2022

Trade name: TEX-A-KOTE 2801 TOPCOAT CLEAR

(Contd. of page 1)

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



T; Toxic

R45-46: May cause cancer. May cause heritable genetic damage.



Xn; Harmful

R20/21-65: Harmful by inhalation and in contact with skin. Harmful: may cause lung damage if swallowed.



F; Highly flammable

R11: Highly flammable.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· Label elements

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:





T Toxic F Highly flammable

· Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light Solvent naphtha (petroleum), light arom. Dimethylbenzene

Risk phrases:

- 45 May cause cancer.
- 46 May cause heritable genetic damage.
- 11 Highly flammable.
- 20/21 Also harmful by inhalation and in contact with skin.
- 65 Harmful: may cause lung damage if swallowed.

Safety phrases:

- *Avoid exposure obtain special instructions before use.*
- 1/2 Keep locked up and out of the reach of children.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

· Special labelling of certain preparations:

Contains unsaturated C18 fatty acids with coco alkylamines. May produce an allergic reaction.

(Contd. on page 3)





Printing date 20.12.2022 Revision: 15.03.2022

Trade name: TEX-A-KOTE 2801 TOPCOAT CLEAR

(Contd. of page 2)

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

Chemical charact	erisation: Mixtures	
Description: Mixto	re of substances listed below with nonhazardous additions.	
Dangerous compo	onents:	
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light ☐ T Carc. Cat. 2, Muta. Cat. 2 R45-46 ☐ Xn R65 ☐ Flam. Liq. 2, H225 ☐ Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304 ☐ Aquatic Chronic 2, H411 ☐ Skin Irrit. 2, H315; STOT SE 3, H336 Aquatic Acute 2, H401	
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom. T Carc. Cat. 2, Muta. Cat. 2 R45-46 Xn R65 Flam. Liq. 3, H226 Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304 Acute Tox. 4, H332 Acute Tox. 5, H313	
CAS: 108-38-3	Dimethylbenzene Xn R20/21 Xi R38 R10 ₱ Flam. Liq. 3, H226 ↑ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 Acute Tox. 5, H303	
CAS: 67-64-1	propanone Xi R36 F R11 R66-67 Flam. Liq. 2, H225 ↓ Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 68647-95-0	unsaturated C18 fatty acids with coco alkylamines Xn R48/20/21/22 Xi R38 Xi R43 N R50/53 STOT RE 2, H373 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Irrit. 2, H315; Skin Sens. 1B, H317	



Printing date 20.12.2022 Revision: 15.03.2022

Trade name: TEX-A-KOTE 2801 TOPCOAT CLEAR

(Contd. of page 3)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 5)





Printing date 20.12.2022 Revision: 15.03.2022

Trade name: TEX-A-KOTE 2801 TOPCOAT CLEAR

(Contd. of page 4)

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls / personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

· Ingredients	with limit values that require monitoring at the workplace:
CAS: 108-3	8-3 Dimethylbenzene
PEL (USA)	Long-term value: 435 mg/m³, 100 ppm
REL (USA)	Short-term value: 655 mg/m^3 , 150 ppm Long-term value: 435 mg/m^3 , 100 ppm
TLV (USA)	Short-term value: (150) ppm Long-term value: (100) NIC-20 ppm BEI, A4
CAS: 67-64	-1 propanone
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm
REL (USA)	Long-term value: 590 mg/m³, 250 ppm
TLV (USA)	Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI

(Contd. on page 6)





Printing date 20.12.2022 Revision: 15.03.2022

Trade name: TEX-A-KOTE 2801 TOPCOAT CLEAR

(Contd. of page 5)

· Ingredients with biological limit values:

CAS: 108-38-3 Dimethylbenzene

BEI (USA) 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

CAS: 67-64-1 propanone

BEI (USA) 25 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles





Printing date 20.12.2022 Revision: 15.03.2022

Trade name: TEX-A-KOTE 2801 TOPCOAT CLEAR

(Contd. of page 6)

Information on basic physical and chen	nical properties
General Information	neu properues
Appearance:	
Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	:: 78 °C
Flash point:	< 0 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	>200 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vap-mixtures are possible.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20 °C:	6.7-8.2 hPa
Density at 20 °C:	0.89g/cm^3
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	78.6 %
VÕC (EC)	78.59 %
Solids content:	26.0 %
Other information	No further relevant information available.





Printing date 20.12.2022 Revision: 15.03.2022

Trade name: TEX-A-KOTE 2801 TOPCOAT CLEAR

(Contd. of page 7)

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

· Acute toxicity		
· LD/LC50	values rele	vant for classification:
CAS: 6474	12-95-6 So	lvent naphtha (petroleum), light arom.
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
CAS: 108-38-3 Dimethylbenzene		
Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	14,100 mg/kg (rabbit)
CAS: 67-64-1 propanone		
Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Carcinogenic.

The product can cause inheritable damage.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 9)





Printing date 20.12.2022 Revision: 15.03.2022

Trade name: TEX-A-KOTE 2801 TOPCOAT CLEAR

(Contd. of page 8)

- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

1 / //	7		•	•
14 1	ranspor	t int	ormai	10H
	runspor	r viej	OI III III	wii

· UN-Number · ADR, IMDG, IATA	UN1263
· UN proper shipping name · ADR · IMDG	1263 PAINT, ENVIRONMENTALLY HAZARDOUS PAINT (Naphtha (petroleum), hydrotreated light, KEROSENE), MARINE POLLUTANT
· IATA	PAINT

- · Transport hazard class(es)
- · ADR, IATA



ClassLabel3 Flammable liquids.3

· IMDG





· Class
· Label
3 Flammable liquids.
3

(Contd. on page 10)



Printing date 20.12.2022 Revision: 15.03.2022

Trade name: TEX-A-KOTE 2801 TOPCOAT CLEAR

	(Contd. of page
Packing group ADR, IMDG, IATA	II
Environmental hazards:	Product contains environmentally hazardous substance. Naphtha (petroleum), hydrotreated light
Marine pollutant:	Symbol (fish and tree)
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
EMS Number:	F-E, <u>S-E</u>
Transport in bulk according to Annex II of Mar	pol
and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
• •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
• • •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1263 PAINT, 3, II, ENVIRONMENTALL HAZARDOUS

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Philippines Inventory of Chemicals and Chemical Substances

All ingredients are listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

(Contd. on page 11)





Printing date 20.12.2022 Revision: 15.03.2022

Trade name: TEX-A-KOTE 2801 TOPCOAT CLEAR

(Contd. of page 10)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

Keievani pr	ii uses
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
R10	Flammable.
R11	Highly flammable.
R20/21	Harmful by inhalation and in contact with skin.
R36	Irritating to eyes.
R38	Irritating to skin.
R43	May cause sensitisation by skin contact.
R45	May cause cancer.
R46	May cause heritable genetic damage.
R48/20/21/2	22 Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
NOS	
R66	Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Product safety department

· Contact: Mr. Ong

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 12)





Printing date 20.12.2022 Revision: 15.03.2022

Trade name: TEX-A-KOTE 2801 TOPCOAT CLEAR

(Contd. of page 11)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 5: Acute toxicity – Category 5

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1B: Skin sensitisation – Category 1B Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1B: Carcinogenicity - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

PH

^{* *} Data compared to the previous version altered.