



## TEX-A-KOTE 2801 TOPCOAT CLEAR

### DESCRIPTION:

TEX-A-KOTE 2801 TOPCOAT CLEAR is a solvent-thinned Acrylic Resin based finish.

### USE:

Suited for concrete or masonry, wood, plywood, particle board and mactan stones.

### FEATURES:

- Excellent outdoor durability
- Color fast, non-yellowing
- Alkali resistant
- Superior Adhesion

### COLOR:

Clear


### FINISH:

Gloss

### APPLICATION TOOLS:



Brush



Roller



Spray

### REDUCTION:

Tex-a-kote 2802 Reducer

1:1 (1 part Tex-a-kote 2801 Topcoat Clear to 1 part Tex-a-kote 2802 Reducer)

### DRYING TIME:

Dry to recoat: 12-24 hours depending on weather condition.

### SURFACE PREPARATION:

Remove loosely adherent mortar, dirt, dust, or any adhesion barrier.

### COVERAGE:

Approximately 16-20 sq.m. / gallon

### PACKAGING:

4 L lithographed round can

### SHELF LIFE:

5 years in unopened container

### STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



## LABEL ELEMENTS:



**Danger.** Highly flammable liquid and vapour. May cause genetic defects. May cause cancer. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. Causes skin irritation. May cause drowsiness or dizziness. May be harmful if inhaled.

**Contains:** Naphtha (Petroleum), hydrotreated light, Solvent naphtha (Petroleum), light arom., Dimethylbenzene

**Precaution:** Avoid exposure - obtain special instructions before use. Keep locked up and out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable protective clothing, gloves, and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.

