

Safety Data Sheet according to GHS

Printing date 10.12.2022

Revision: 10.12.2022

1 Identification

- **Product identifier**
- **Trade name:** TEX-A-KOTE PENETRATING SEALER 2803 CLEAR
- **Article number:** CWPACB-03798
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Treasure Island Industrial Corp.
No.2, 3rd Ave. S. Osmena Blvd.
North Reclamation Area
Cebu City 6000
PHILIPPINES
doo@treasureisland.com.ph
- **Further information obtainable from:** Product safety department
- **Emergency telephone number:** During normal opening times: +63 32 232 05 13

2 Hazard identification

- **Classification of the substance or mixture**



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Repr. 1B H360 May damage fertility or the unborn child.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.




Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.
Eye Irritation 2A H319 Causes serious eye irritation.
STOT SE 3 H335 May cause respiratory irritation.
Acute Tox. 5 H333 May be harmful if inhaled.
Aquatic Acute 3 H402 Harmful to aquatic life.
CWPACB-03798

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



R45-46-60-61: May cause cancer. May cause heritable genetic damage. May impair fertility. May cause harm to the unborn child.

(Contd. on page 2)

Safety Data Sheet
according to GHS

Printing date 10.12.2022

Revision: 10.12.2022

Trade name: TEX-A-KOTE PENETRATING SEALER 2803 CLEAR

(Contd. of page 1)



Xn; Harmful

R20/21-65: Harmful by inhalation and in contact with skin. Harmful: may cause lung damage if swallowed.



Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.



F; Highly flammable

R11: Highly flammable.



N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **Label elements**

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



T Toxic

F Highly flammable

N Dangerous for the environment

· **Hazard-determining components of labelling:**

Naphtha (petroleum), hydrotreated light

Dimethylbenzene

di-(2-ethylhexyl) phthalate

· **Risk phrases:**

45 May cause cancer.

46 May cause heritable genetic damage.

60 May impair fertility.

61 May cause harm to the unborn child.

11 Highly flammable.

20/21 Also harmful by inhalation and in contact with skin.

36/37/38 Irritating to eyes, respiratory system and skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

· **Safety phrases:**

53 Avoid exposure - obtain special instructions before use.

1/2 Keep locked up and out of the reach of children.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

(Contd. on page 3)

Safety Data Sheet

according to GHS

Printing date 10.12.2022

Revision: 10.12.2022

Trade name: TEX-A-KOTE PENETRATING SEALER 2803 CLEAR

(Contd. of page 2)

36/37/39 Wear suitable protective clothing, gloves and eye/face protection.




















45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition / information on ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 1330-20-7	Dimethylbenzene  Xn R20/21  Xi R38 R10 <hr style="border-top: 1px dashed #000;"/>  Flam. Liq. 3, H226  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315  Acute Tox. 5, H303	
CAS: 95-63-6	1,2,4-trimethylbenzene  Xn R20  Xi R36/37/38  N R51/53 R10 <hr style="border-top: 1px dashed #000;"/>  Flam. Liq. 3, H226  Aquatic Chronic 2, H411  Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335  Acute Tox. 5, H303	
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light  T Carc. Cat. 2, Muta. Cat. 2 R45-46  Xn R65 <hr style="border-top: 1px dashed #000;"/>  Flam. Liq. 2, H225  Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; STOT SE 3, H336  Aquatic Acute 2, H401	

(Contd. on page 4)

PH

Safety Data Sheet















according to GHS

Printing date 10.12.2022

Revision: 10.12.2022

Trade name: TEX-A-KOTE PENETRATING SEALER 2803 CLEAR

(Contd. of page 3)

CAS: 108-67-8	1,3,5-trimethylbenzene  Xi R37  N R51/53 R10 <hr style="border-top: 1px dashed black;"/>  Flam. Liq. 3, H226  Aquatic Chronic 2, H411  STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: C ≥ 25 %	
CAS: 98-82-8	isopropylbenzene  Xn R65  Xi R37  N R51/53 R10 <hr style="border-top: 1px dashed black;"/>  Flam. Liq. 3, H226  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  Acute Tox. 4, H302; STOT SE 3, H335 Acute Tox. 5, H333	
CAS: 117-81-7	di-(2-ethylhexyl) phthalate  T Repr. Cat. 2 R60-61 <hr style="border-top: 1px dashed black;"/>  Repr. 1B, H360	

· SVHC

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

 · **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

 · **Description of first aid measures**

 · **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

 · **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

 · **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

 · **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

 · **After swallowing:** If symptoms persist consult doctor.

 · **Information for doctor:**

 · **Most important symptoms and effects, both acute and delayed** No further relevant information available.

 · **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

 · **Extinguishing media**

 · **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

 · **For safety reasons unsuitable extinguishing agents:** Water with full jet

 · **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 5)

Safety Data Sheet according to GHS

Printing date 10.12.2022

Revision: 10.12.2022

Trade name: TEX-A-KOTE PENETRATING SEALER 2803 CLEAR

(Contd. of page 4)

- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls / personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

CAS: 1330-20-7 Dimethylbenzene

PEL (USA) Long-term value: 435 mg/m³, 100 ppm

(Contd. on page 6)

Safety Data Sheet

according to GHS

Printing date 10.12.2022

Revision: 10.12.2022

Trade name: TEX-A-KOTE PENETRATING SEALER 2803 CLEAR

(Contd. of page 5)

REL (USA) Short-term value: 655 mg/m³, 150 ppm
 Long-term value: 435 mg/m³, 100 ppm

TLV (USA) Short-term value: (150) ppm
 Long-term value: (100) NIC-20 ppm
 BEI, A4

CAS: 95-63-6 1,2,4-trimethylbenzene

REL (USA) Long-term value: 125 mg/m³, 25 ppm

TLV (USA) Long-term value: (25) NIC-10 ppm
 NIC-A4

CAS: 108-67-8 1,3,5-trimethylbenzene

REL (USA) Long-term value: 125 mg/m³, 25 ppm

TLV (USA) Long-term value: (25) NIC-10 ppm

CAS: 98-82-8 isopropylbenzene

PEL (USA) Long-term value: 245 mg/m³, 50 ppm
 Skin

REL (USA) Long-term value: 245 mg/m³, 50 ppm
 Skin

TLV (USA) Long-term value: 5 ppm
 A3

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

PEL (USA) Long-term value: 5 mg/m³

REL (USA) Short-term value: 10 mg/m³
 Long-term value: 5 mg/m³
 See Pocket Guide App. A

TLV (USA) Long-term value: (5) mg/m³, NIC-0.03 ppm
 NIC-Skin, A3

· Ingredients with biological limit values:
CAS: 1330-20-7 Dimethylbenzene

BEI (USA) 1.5 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Methylhippuric acids

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

(Contd. on page 7)

Safety Data Sheet according to GHS

Printing date 10.12.2022

Revision: 10.12.2022

Trade name: TEX-A-KOTE PENETRATING SEALER 2803 CLEAR

(Contd. of page 6)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Fluid

Colour:

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

Melting point/freezing point:

Undetermined.

Initial boiling point and boiling range: 78 °C

· **Flash point:**

23 - 60 °C

· **Flammability (solid, gas):**

Not applicable.

· **Ignition temperature:**

>200 °C

· **Decomposition temperature:**

Not determined.

· **Auto-ignition temperature:**

Product is not selfigniting.

· **Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower:

1.1 Vol %

Upper:

7 Vol %

· **Vapour pressure at 20 °C:**

6.7-8.2 hPa

· **Density at 20 °C:**

0.85 g/cm³

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

(Contd. on page 8)

Safety Data Sheet according to GHS

Printing date 10.12.2022

Revision: 10.12.2022

Trade name: TEX-A-KOTE PENETRATING SEALER 2803 CLEAR

(Contd. of page 7)

· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	64.9 %
VOC (EC)	64.93 %
Solids content:	18.2 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

CAS: 1330-20-7 Dimethylbenzene

Oral	LD50	4,300 mg/kg (rat)
------	------	-------------------

Dermal	LD50	2,000 mg/kg (rabbit)
--------	------	----------------------

CAS: 95-63-6 1,2,4-trimethylbenzene

Oral	LD50	5,000 mg/kg (rat)
------	------	-------------------

CAS: 98-82-8 isopropylbenzene

Oral	LD50	1,400 mg/kg (rat)
------	------	-------------------

Dermal	LD50	12,300 mg/kg (rabbit)
--------	------	-----------------------

Inhalative	LC50/4 h	24.7 mg/l (mouse)
------------	----------	-------------------

CAS: 117-81-7 di-(2-ethylhexyl) phthalate

Oral	LD50	30,600 mg/kg (rat)
------	------	--------------------

Dermal	LD50	25,000 mg/kg (rabbit)
--------	------	-----------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** Irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.

(Contd. on page 9)

Safety Data Sheet according to GHS

Printing date 10.12.2022

Revision: 10.12.2022

Trade name: TEX-A-KOTE PENETRATING SEALER 2803 CLEAR

(Contd. of page 8)

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

Carcinogenic.

The product can cause inheritable damage.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behaviour in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Toxic for fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **ADR, IMDG, IATA**

UN1263

· **UN proper shipping name**

· **ADR**

· **IMDG**

· **IATA**

1263 PAINT, ENVIRONMENTALLY HAZARDOUS

PAINT (1,2,4-trimethylbenzene, Naphtha (petroleum), hydrotreated light), MARINE POLLUTANT

PAINT

(Contd. on page 10)

Safety Data Sheet

according to GHS

Printing date 10.12.2022

Revision: 10.12.2022

Trade name: TEX-A-KOTE PENETRATING SEALER 2803 CLEAR

(Contd. of page 9)

 · **Transport hazard class(es)**

 · **ADR, IATA**

 · **Class**
 · **Label**

 3 Flammable liquids.
 3

 · **IMDG**

 · **Class**
 · **Label**

 3 Flammable liquids.
 3

 · **Packing group**

 · **ADR, IMDG, IATA**

II

 · **Environmental hazards:**

Product contains environmentally hazardous substances: 1,2,4-trimethylbenzene

 · **Marine pollutant:**

Symbol (fish and tree)

 · **Special precautions for user**

Warning: Flammable liquids.

 · **Hazard identification number (Kemler code):**

33

 · **EMS Number:**

F-E,S-E

 · **Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

 · **Transport/Additional information:**

 · **ADR**

 · **Limited quantities (LQ)**

5L

 · **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

 · **Transport category**

2

 · **IMDG**

 · **Limited quantities (LQ)**

5L

 · **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

 · **UN "Model Regulation":**

UN 1263 PAINT, 3, II, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

 · **Safety, health and environmental regulations/legislation specific for the substance or mixture**

 · **Philippines Inventory of Chemicals and Chemical Substances**

CAS: 1330-20-7	Dimethylbenzene
----------------	-----------------

(Contd. on page 11)

Safety Data Sheet

according to GHS

Printing date 10.12.2022

Revision: 10.12.2022

Trade name: TEX-A-KOTE PENETRATING SEALER 2803 CLEAR

(Contd. of page 10)

CAS: 95-63-6	1,2,4-trimethylbenzene
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light
CAS: 108-67-8	1,3,5-trimethylbenzene
CAS: 98-82-8	isopropylbenzene
CAS: 117-81-7	di-(2-ethylhexyl) phthalate
CAS: 8002-43-5	Lecithin

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
E2 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations:**
- **Information about limitation of use:**
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.
- **Other regulations, limitations and prohibitive regulations**

- **Substances of very high concern (SVHC) according to REACH, Article 57**

CAS: 117-81-7	di-(2-ethylhexyl) phthalate
---------------	-----------------------------

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H303 May be harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H333 May be harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H340 May cause genetic defects.
- H350 May cause cancer.
- H360 May damage fertility or the unborn child.
- H401 Toxic to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.
- R10 Flammable.
- R20 Harmful by inhalation.
- R20/21 Harmful by inhalation and in contact with skin.
- R36/37/38 Irritating to eyes, respiratory system and skin.
- R37 Irritating to respiratory system.

(Contd. on page 12)

Safety Data Sheet according to GHS

Printing date 10.12.2022

Revision: 10.12.2022

Trade name: TEX-A-KOTE PENETRATING SEALER 2803 CLEAR

(Contd. of page 11)

- R38 *Irritating to skin.*
R45 *May cause cancer.*
R46 *May cause heritable genetic damage.*
R51/53 *Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*
R60 *May impair fertility.*
R61 *May cause harm to the unborn child.*
R65 *Harmful: may cause lung damage if swallowed.*

· **Department issuing SDS:** Product safety department

· **Contact:** Mr. Ong

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 5: Acute toxicity – Category 5

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1B: Carcinogenicity – Category 1B

Repr. 1B: Reproductive toxicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered.**