



## TEX-A-KOTE PENETRATING SEALER 2803 CLEAR

### DESCRIPTION:

**TEX-A-KOTE PENETRATING SEALER 2803 CLEAR** is an acrylic-based solvent type sealer for concrete. It has excellent surface penetration and sealing properties.

### USE:

Suited for concrete or masonry, pebbles and mactan stones. To reduce absorption of porous new or aged concrete.

### FEATURES:

- Good alkali resistance
- Superior Adhesion
- Resist algae and fungus growth
- Fast Drying


### COLOR:

Water White Clear

### APPLICATION TOOLS:



Brush



Roller



Spray

### REDUCTION:

Tex-a-kote 2802 Reducer

Apply as is for brush and roller

Reduce as needed for spray

### DRYING TIME:

Dry to recoat: 12-24 hours depending on weather condition.

### SURFACE PREPARATION:

Remove loosely adherent mortar, dirt, dust, or any adhesion barrier.

### COVERAGE:

Approximately 16-20 sq.m. / gallon @ 25-30  $\mu$  dry film thickness

### PACKAGING:

4 L lithographed round can

### SHELF LIFE:

5 years in unopened container


### STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



## LABEL ELEMENTS:



**Danger.** Highly flammable liquid and vapour. May damage fertility or the unborn child. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. Causes skin and serious eye irritation. May cause respiratory irritation. May be harmful if inhaled.

**Contains:** Naphtha (petroleum), hydrotreated light, Dimethylbenzene, di-(2-ethylhexyl)phthalate

**Precaution:** Avoid exposure – obtain special instructions before use. Keep locked up and out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable protective clothing, gloves, and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.

