



TEX-A-KOTE PRIMER 2800 WHITE

DESCRIPTION:

TEX-A-KOTE PRIMER 2800 WHITE is an acrylic based solvent type primer for exterior & interior applications. It has an excellent adhesion, filling and sealing properties; reduces surface absorption making it ideal foundation for subsequent coat.

USE:

Suited for concrete or masonry, wood, plywood, metal, particle board or hardiflex.


COLOR:

Available in White, maybe tinted with Tex-a-kote Tinting Color when desired.

FINISH:

Flat

APPLICATION TOOLS:



Brush

Roller

Spray

Note: To patch up joints and surface imperfections, use Tex-a-kote 2800C Cast

REDUCTION:

Tex-a-kote 2802 Reducer

Applied by roller- approx. 5% reducer

Applied by spray- approx. 10% or more reducer may be required.

Brush is used on hard-to-reach areas or corner.

DRYING TIME:

Dry to recoat: 12-24 hours depending on weather condition.

SURFACE PREPARATION:

Remove loosely adherent mortar, dirt, dust, or any adhesion barrier. Tex-a-kote Primer 2800 White is an alkali resistant, however, for best result, neutralize highly alkaline new concrete. Dry surface thoroughly prior to priming.

SUBSEQUENT COAT:

Tex-a-kote Finishes and Latex Finishes

COVERAGE:

Approximately 20-25 sq.m. / gallon, depending on surface porosity

PACKAGING:

1L and 4L lithographed round can, 16L pail

SHELF LIFE:

5 years in unopened container

STORAGE & DISPOSAL:

Keep container tightly sealed. Do not store above 35 °C. Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be according to government regulations.

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.



LABEL ELEMENTS:



Danger. Flammable liquid and vapour. May cause cancer. Route of exposure: Inhalation. May damage fertility or the unborn child. Causes skin irritation. May be harmful if inhaled. Harmful to aquatic life with long lasting effects.

Contains: Dimethylbenzene, di-(2-ethylhexyl)phthalate

Precaution: Avoid exposure – obtain special instructions before use. Keep locked up and out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable protective clothing, gloves, and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

The information in this data sheet is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve users from the responsibility of carrying out their own tests neither do they imply any legally binding assurance of certain properties or suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any propriety rights and existing laws and legislation are observed.

